

6016-010 Information

Heisener.com

For Reference Only

Part Number 6016-010

Manufacturer API Delevan Inc. Category

Transformers

Power Transformers

Description XFRMR LAMINATED 20VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









6016-010 Specifications

Manufacturer Part Number 6016-010 Manufacturer API Delevan Inc. Category Transformers Package - Series 6016 Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 4A, Series 2A Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 20 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.15mm L x 47.63mm W Height - Seated (Max) 36.50mm Voltage - Isolation 2500Vrms Weight 0.8 lb (362.87g)		
Category Transformers Package - Series 6016 Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 4A, Series 2A Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 20 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.15mm L x 47.63mm W Height - Seated (Max) 36.50mm Voltage - Isolation 2500Vrms Weight 0.8 lb (362.87g)	Manufacturer Part Number	6016-010
Package Power Transformers Fackage Formination Style Formination	Manufacturer	API Delevan Inc.
Package - Series 6016 Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 4A, Series 2A Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 20 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.15mm L x 47.63mm W Height - Seated (Max) 36.50mm Voltage - Isolation 2500Vrms Weight 0.8 lb (362.87g)	Category	Transformers
Series6016TypeLaminated CoreVoltage - Primary115 VVoltage - Secondary (Full Load)Parallel 5V, Series 10 VCurrent - Output (Max)Parallel 4A, Series 2APrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max20 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension57.15mm L x 47.63mm WHeight - Seated (Max)36.50mmVoltage - Isolation2500VrmsWeight0.8 lb (362.87g)		Power Transformers
Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 4A, Series 2A Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 20 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.15mm L x 47.63mm W Height - Seated (Max) 36.50mm Voltage - Isolation 2500Vrms Weight 0.8 lb (362.87g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 4A, Series 2A Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 20 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension Final L x 47.63mm W Height - Seated (Max) Voltage - Isolation Weight Weight	Series	6016
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 5V, Series 10V Parallel 4A, Series 2A Primary Winding(s) Single Secondary Winding(s) Dual Center Tap No Power - Max 20 VA Mounting Type Through Hole Termination Style Size / Dimension FOR Pin Size / Dimension 57.15mm L x 47.63mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Weight Parallel 5V, Series 10V Parallel 4A, Series 2A Primary Ed. Single Single Single Single No 20 VA Mounting Type Through Hole 25 Dimension 57.15mm L x 47.63mm W 47.63mm W 48.650mm Voltage - Isolation 0.8 lb (362.87g)	Туре	Laminated Core
Current - Output (Max)Parallel 4A, Series 2APrimary Winding(s)SingleSecondary Winding(s)DualCenter TapNoPower - Max20 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension57.15mm L x 47.63mm WHeight - Seated (Max)36.50mmVoltage - Isolation2500VrmsWeight0.8 lb (362.87g)	Voltage - Primary	115V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 20 VA Mounting Type Through Hole Termination Style Size / Dimension Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Single Single Single Single Single Single No 80 80 80 80 80 80 80 80 80 80 80 80 80	Voltage - Secondary (Full Load)	Parallel 5V, Series 10V
Secondary Winding(s)DualCenter TapNoPower - Max20 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension57.15mm L x 47.63mm WHeight - Seated (Max)36.50mmVoltage - Isolation2500VrmsWeight0.8 lb (362.87g)	Current - Output (Max)	Parallel 4A, Series 2A
Center Tap No Power - Max 20 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.15mm L x 47.63mm W Height - Seated (Max) 36.50mm Voltage - Isolation 2500Vrms Weight 0.8 lb (362.87g)	Primary Winding(s)	Single
Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension 57.15mm L x 47.63mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Weight 20 VA PC Pin 57.15mm L x 47.63mm W 36.50mm 0.8 1b (362.87g)	Secondary Winding(s)	Dual
Mounting Type Through Hole PC Pin Size / Dimension 57.15mm L x 47.63mm W Height - Seated (Max) Voltage - Isolation 2500Vrms Weight 0.8 lb (362.87g)	Center Tap	No
Termination Style PC Pin Size / Dimension 57.15mm L x 47.63mm W Height - Seated (Max) 36.50mm Voltage - Isolation 2500Vrms Weight 0.8 lb (362.87g)	Power - Max	20 VA
Size / Dimension 57.15mm L x 47.63mm W Height - Seated (Max) 36.50mm Voltage - Isolation 2500Vrms Weight 0.8 lb (362.87g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation Weight 36.50mm 2500Vrms 0.8 lb (362.87g)	Termination Style	PC Pin
Voltage - Isolation 2500Vrms Weight 0.8 lb (362.87g)	Size / Dimension	57.15mm L x 47.63mm W
Weight 0.8 lb (362.87g)	Height - Seated (Max)	36.50mm
	Voltage - Isolation	2500Vrms
Report errors?	Weight	0.8 lb (362.87g)
		Report errors?

6016-010 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

6016-010 Payment Methods





















6016-010 Shipping Methods













If you have any question about 6016-010, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com