

6027R-056 Information

Heisener.com

For Reference Only

Part Number6027R-056ManufacturerAPI Delevan Inc.CategoryTransformers

Power Transformers

Description XFRMR LAMINATED 36VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









6027R-056 Specifications

Manufacturer Part Number 6027R-056 Manufacturer API Delevan Inc. Category Transformers Package - Series 6027R Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 28V, Series 56V Current - Output (Max) Parallel 1.3A, Series 650mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) 39.67mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)		
Category Transformers Power Transformers Package - Series 6027R Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 28V, Series 56V Current - Output (Max) Parallel 1.3A, Series 650mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) 39.67mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Manufacturer Part Number	6027R-056
Package Series 6027R Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Parallel 28V, Series 56V Current - Output (Max) Parallel 1.3A, Series 650mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Telephane Secondary Winding(s) Secondary Winding(s) Through Hole Termination Style Size / Dimension Size / Dimension Size / Seated (Max) Secondary Winding(s) Size / Dimension Size / Dimension Size / Dimension Size / Dimension Size / Seated (Max) Secondary Winding(s) Size / Dimension Size / Dimension Size / Seated (Max) Secondary Winding(s) Size / Dimension Size / Seated (Max) Secondary Winding(s) Size / Dimension	Manufacturer	API Delevan Inc.
Package-Series6027RTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 28V, Series 56VCurrent - Output (Max)Parallel 1.3A, Series 650mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max36 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Category	Transformers
Series6027RTypeLaminated CoreVoltage - Primary115 V, 230 VVoltage - Secondary (Full Load)Parallel 28 V, Series 56 VCurrent - Output (Max)Parallel 1.3A, Series 650mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max36 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)		Power Transformers
Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 28V, Series 56V Current - Output (Max) Parallel 1.3A, Series 650mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) 39.67mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 28V, Series 56V Current - Output (Max) Parallel 1.3A, Series 650mA Primary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension Height - Seated (Max) Voltage - Isolation Voltage - Isolation Weight 1.1 lbs (499g)	Series	6027R
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 28V, Series 56V Current - Output (Max) Parallel 1.3A, Series 650mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Weight Parallel 28V, Series 56V Parallel 2.8A, Series 650mA Dual Secondary Winding(s) Solution 1	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style Size / Dimension Fixed (Max) Voltage - Isolation Voltage - Isolation Parallel 1.3A, Series 650mA Dual Dual Powal P	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Dual No Powal No 86 (ABM) No 97 (ABM) No 1.1 lbs (499g)	Voltage - Secondary (Full Load)	Parallel 28V, Series 56V
Secondary Winding(s)DualCenter TapNoPower - Max36 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Current - Output (Max)	Parallel 1.3A, Series 650mA
Center TapNoPower - Max36 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation2500VrmsWeight1.1 lbs (499g)	Primary Winding(s)	Dual
Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Weight 36 VA PC Pin 66.68mm L x 55.55mm W 39.67mm 1.1 lbs (499g)	Secondary Winding(s)	Dual
Mounting Type Through Hole Termination Style PC Pin Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) 39.67mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Center Tap	No
Termination Style PC Pin Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) 39.67mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Power - Max	36 VA
Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) 39.67mm Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation Veight 39.67mm 2500Vrms 1.1 lbs (499g)	Termination Style	PC Pin
Voltage - Isolation 2500Vrms Weight 1.1 lbs (499g)	Size / Dimension	66.68mm L x 55.55mm W
Weight 1.1 lbs (499g)	Height - Seated (Max)	39.67mm
	Voltage - Isolation	2500Vrms
Report errors?	Weight	1.1 lbs (499g)
		Report errors?

6027R-056 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

6027R-056 Payment Methods



















6027R-056 Shipping Methods













If you have any question about 6027R-056, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com