

6051-020 Information

Heisener.com

Part Number 6051-020

Manufacturer API Delevan Inc.

Category

Transformers **Power Transformers**

Description

XFRMR LAMINATED 2.5VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









6051-020 Specifications

Manufacturer Part Number 6051-020 Manufacturer API Delevan Inc. Category Transformers Package - Series 6051 Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 250mA, Series 125mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.60mm W Height - Seated (Max) 16.50mm Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)		
Category Transformers Package - Series 6051 Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 250mA, Series 125mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.60mm W Height - Seated (Max) 16.50mm Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)	Manufacturer Part Number	6051-020
Power Transformers Package - Series 6051 Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 250mA, Series 125mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.60mm W Height - Seated (Max) 16.50mm Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)	Manufacturer	API Delevan Inc.
Package - Go51 Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 250mA, Series 125mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.60mm W Height - Seated (Max) 1500Vrms Weight Woltage - Isolation 1500Vrms	Category	Transformers
Series 6051 Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 250mA, Series 125mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.60mm W Height - Seated (Max) 16.50mm Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)		Power Transformers
Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 250mA, Series 125mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.60mm W Height - Seated (Max) 16.50mm Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 250mA, Series 125mA Primary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.60mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Weight	Series	6051
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 250mA, Series 125mA Primary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.60mm W Height - Seated (Max) Voltage - Isolation Weight Parallel 10V, Series 20V Parallel 250mA, Series 125mA Parallel 250mA, Series 125mA Parallel 250mA, Series 20V Parallel 250mA, Series 20V Parallel 250mA, Series 20V Parallel 250mA, Series 125mA Pual No 1.50 VA 1.500mm Us 39.60mm W 1.500Vrms Voltage - Isolation Voltage - Isolation 0.313 lb (141.97g)	Туре	Laminated Core
Current - Output (Max) Parallel 250mA, Series 125mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.60mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Weight Parallel 250mA, Series 125mA Dual No 104 105 105 105 105 105 105 105 105 105 105	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Dual No 1000 No 1100 1	Voltage - Secondary (Full Load)	Parallel 10V, Series 20V
Secondary Winding(s)DualCenter TapNoPower - Max2.5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.60mm L x 39.60mm WHeight - Seated (Max)16.50mmVoltage - Isolation1500VrmsWeight0.313 lb (141.97g)	Current - Output (Max)	Parallel 250mA, Series 125mA
Center Tap Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.60mm W Height - Seated (Max) Voltage - Isolation 1500Vrms Weight No 2.5 VA Through Hole PC Pin 47.60mm L x 39.60mm W 16.50mm 0.313 lb (141.97g)	Primary Winding(s)	Dual
Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.60mm W Height - Seated (Max) 16.50mm Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)	Secondary Winding(s)	Dual
Mounting TypeThrough HoleTermination StylePC PinSize / Dimension47.60mm L x 39.60mm WHeight - Seated (Max)16.50mmVoltage - Isolation1500VrmsWeight0.313 lb (141.97g)	Center Tap	No
Termination Style PC Pin Size / Dimension 47.60mm L x 39.60mm W Height - Seated (Max) 16.50mm Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)	Power - Max	2.5 VA
Size / Dimension 47.60mm L x 39.60mm W Height - Seated (Max) 16.50mm Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)	Termination Style	PC Pin
Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)	Size / Dimension	47.60mm L x 39.60mm W
Weight 0.313 lb (141.97g)	Height - Seated (Max)	16.50mm
	Voltage - Isolation	1500Vrms
Donout among 9	Weight	0.313 lb (141.97g)
Report errors?		Report errors?

6051-020 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

6051-020 Payment Methods



















6051-020 Shipping Methods













If you have any question about 6051-020, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com