

6051R-034 Information

Heisener.com

For Reference Only

Part Number6051R-034ManufacturerAPI Delevan Inc.CategoryTransformers

Power Transformers

Description XFRMR LAMINATED 2.5VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









6051R-034 Specifications

Manufacturer Part Number 6051R-034 Manufacturer API Delevan Inc. Category Transformers Power Transformers Power Transformers Series 6051R Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 17V, Series 34V Current - Output (Max) Parallel 146mA, Series 73mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.60mm W Height - Seated (Max) 16.50mm Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)		
Category Transformers Package - Series 6051R Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 17V, Series 34V Current - Output (Max) Parallel 146mA, Series 73mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.60mm W Height - Seated (Max) 16.50mm Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)	Manufacturer Part Number	6051R-034
Package Series 6051R Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 17V, Series 34V Current - Output (Max) Parallel 146mA, Series 73mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style Size / Dimension 47.60mm L x 39.60mm W Height - Seated (Max) Voltage - Isolation Weight Power - Isolation 1500Vrms Power - Isolation 1500Vrms	Manufacturer	API Delevan Inc.
Package - Go51R Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 17V, Series 34V Current - Output (Max) Parallel 146mA, Series 73mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.60mm W Height - Seated (Max) 1500Vrms Weight Woltage - Isolation 1500Vrms	Category	Transformers
Series 6051R Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 17V, Series 34V Current - Output (Max) Parallel 146mA, Series 73mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.60mm W Height - Seated (Max) 16.50mm Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)		Power Transformers
Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 17V, Series 34V Current - Output (Max) Parallel 146mA, Series 73mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.60mm W Height - Seated (Max) 16.50mm Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 17V, Series 34V Current - Output (Max) Parallel 146mA, Series 73mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.60mm W Height - Seated (Max) Voltage - Isolation Weight 115V, 230V Parallel 17V, Series 34V Parallel 146mA, Series 73mA Parallel 17V, Series 34V Parallel 146mA, Series 73mA Pull 5 makes 1	Series	6051R
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 17V, Series 34V Parallel 146mA, Series 73mA Primary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max August 140 Max Primary Winding(s) Power - Max Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.60mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Weight	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Parallel 146mA, Series 73mA Dual Pual Pual Power - Max No Power - Max 2.5 VA Mounting Type Through Hole PC Pin Size / Dimension 47.60mm L x 39.60mm W 16.50mm Voltage - Isolation 0.313 lb (141.97g)	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.60mm W Height - Seated (Max) Voltage - Isolation Dual No 16.50mm Voltage - Isolation 1500Vrms Weight	Voltage - Secondary (Full Load)	Parallel 17V, Series 34V
Secondary Winding(s) Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.60mm W Height - Seated (Max) Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)	Current - Output (Max)	Parallel 146mA, Series 73mA
Center TapNoPower - Max2.5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension47.60mm L x 39.60mm WHeight - Seated (Max)16.50mmVoltage - Isolation1500VrmsWeight0.313 lb (141.97g)	Primary Winding(s)	Dual
Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension 47.60mm L x 39.60mm W Height - Seated (Max) Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)	Secondary Winding(s)	Dual
Mounting Type Through Hole PC Pin Size / Dimension 47.60mm L x 39.60mm W Height - Seated (Max) 16.50mm Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)	Center Tap	No
Termination Style PC Pin Size / Dimension 47.60mm L x 39.60mm W Height - Seated (Max) 16.50mm Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)	Power - Max	2.5 VA
Size / Dimension47.60mm L x 39.60mm WHeight - Seated (Max)16.50mmVoltage - Isolation1500VrmsWeight0.313 lb (141.97g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation Weight 16.50mm 1500Vrms 0.313 lb (141.97g)	Termination Style	PC Pin
Voltage - Isolation 1500Vrms Weight 0.313 lb (141.97g)	Size / Dimension	47.60mm L x 39.60mm W
Weight 0.313 lb (141.97g)	Height - Seated (Max)	16.50mm
	Voltage - Isolation	1500Vrms
Report errors?	Weight	0.313 lb (141.97g)
•		Report errors?

6051R-034 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

6051R-034 Payment Methods





















6051R-034 Shipping Methods













If you have any question about 6051R-034, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com