

6054-010 Information

Part Number 6054-010

Heisener.com

Manufacturer API Delevan Inc.

Category Transformers

Power Transformers

Description XFRMR LAMINATED 24VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









6054-010 Specifications

For Reference Only

Manufacturer Part Number 6054-010 Manufacturer API Delevan Inc. Category Transformers Package - Series 6054 Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 4.8A, Series 2.4A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 24 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 33.32mm Voltage - Isolation 1500Vrms Weight 0.938 lb (425.47g)		
Category Transformers Package - Series 6054 Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 4.8A, Series 2.4A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 24 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 33.32mm Voltage - Isolation 1500Vrms Weight 0.938 lb (425.47g)	Manufacturer Part Number	6054-010
Package Power Transformers Series 6054 Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 4.8A, Series 2.4A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 24 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 33.32mm Voltage - Isolation 1500Vrms Weight 0.938 lb (425.47g)	Manufacturer	API Delevan Inc.
Package - Series 6054 Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 4.8A, Series 2.4A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 24 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 33.32mm Voltage - Isolation 1500Vrms Weight 0.938 lb (425.47g)	Category	Transformers
Series 6054 Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 4.8A, Series 2.4A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 24 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 33.32mm Voltage - Isolation 1500Vrms Weight 0.938 lb (425.47g)		Power Transformers
Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 4.8A, Series 2.4A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 24 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 33.32mm Voltage - Isolation 1500Vrms Weight 0.938 lb (425.47g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 4.8A, Series 2.4A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 44 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm Voltage - Isolation Voltage - Isolation Weight 115V, 230V Parallel 5V, Series 10V Parallel 4.8A, Series 2.4A Primary Winding(s) Dual Secondary Winding(s) Dual Secondary Winding(s) Parallel 4.8A, Series 2.4A Primary Winding(s) Parallel 4.8A, Series 2.4A Primary Winding(s) Dual Secondary Winding(s) Dual Secondary Winding(s) Poul 5 Secondary Winding(s) Dual Secondary Wind	Series	6054
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 5V, Series 10V Parallel 4.8A, Series 2.4A Primary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Parallel 5V, Series 10V Parallel 4.8A, Series 2.4A No Dual Secondary Winding(s) 104 105 105 105 105 105 105 105	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 24 VA Mounting Type Through Hole Termination Style Size / Dimension 41.28mm L x 33.32mm Voltage - Isolation Voltage - Isolation Parallel 4.8A, Series 2.4A Dual Pual No Powal No Powal No Powal No PC Pin 41.28mm L x 33.32mm W 1500Vrms 0.938 lb (425.47g)	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max August Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Pual No 1500Vrms Dual No 1500Vrms 0.938 lb (425.47g)	Voltage - Secondary (Full Load)	Parallel 5V, Series 10V
Secondary Winding(s)DualCenter TapNoPower - Max24 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)33.32mmVoltage - Isolation1500VrmsWeight0.938 lb (425.47g)	Current - Output (Max)	Parallel 4.8A, Series 2.4A
Center Tap No Power - Max 24 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 33.32mm Voltage - Isolation 1500Vrms Weight 0.938 lb (425.47g)	Primary Winding(s)	Dual
Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) Voltage - Isolation 1500Vrms Weight 0.938 lb (425.47g)	Secondary Winding(s)	Dual
Mounting Type Through Hole PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 33.32mm Voltage - Isolation 1500Vrms Weight 0.938 lb (425.47g)	Center Tap	No
Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 33.32mm Voltage - Isolation 1500Vrms Weight 0.938 lb (425.47g)	Power - Max	24 VA
Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 33.32mm Voltage - Isolation 1500Vrms Weight 0.938 lb (425.47g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation 1500Vrms Weight 0.938 lb (425.47g)	Termination Style	PC Pin
Voltage - Isolation 1500Vrms Weight 0.938 lb (425.47g)	Size / Dimension	41.28mm L x 33.32mm W
Weight 0.938 lb (425.47g)	Height - Seated (Max)	33.32mm
	Voltage - Isolation	1500Vrms
Report errors?	Weight	0.938 lb (425.47g)
		Report errors?

6054-010 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

6054-010 Payment Methods



















6054-010 Shipping Methods













If you have any question about 6054-010, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com