

### **60CJ Information**



For Reference Only

Part Number 60CJ Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 60A 600VAC/250VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **60CJ Specifications**

Manufacturer Part Number         60CJ           Manufacturer         Eaton           Category         Circuit Protection           Electrical, Specialty Fuses           Package         Cartridge, Non-Standard           Series         HRCI-J           Fuse Type         Cartridge           Current Rating         60A           Voltage Rating - AC         600V           Voltage Rating - DC         250V           Response Time         Fast           Applications         Electrical, Industrial           Features         -           Class         -           Approvals         CSA           Operating Temperature         -           Breaking Capacity @ Rated Voltage         200kA           Mounting Type         Holder           Package / Case         Cartridge, Non-Standard           Size / Dimension         1.063" Dia x 2.362" L (27.00mm x 60.00mm)    Report errors?		
CategoryCircuit ProtectionPackageCartridge, Non-StandardSeriesHRCI-JFuse TypeCartridgeCurrent Rating60AVoltage Rating - AC600VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSAOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 2.362" L (27.00mm x 60.00mm)	Manufacturer Part Number	60CJ
Beaking Capacity @ Rated Voltage  Castridge, Specialty Fuses  Electrical, Specialty Fuses  Cartridge, Non-Standard  HRCI-J  Fuse Type  Cartridge  Current Rating  60A  Voltage Rating - AC  600V  Voltage Rating - DC  250V  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  - Approvals  CSA  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  Electrical, Specialty Fuses  Cartridge, Non-Standard  Size / Dimension  Electrical, Specialty Fuses  Cartridge, Non-Standard  Size / Dimension  Cartridge, Non-Standard  Size / Dimension	Manufacturer	Eaton
PackageCartridge, Non-StandardSeriesHRCI-JFuse TypeCartridgeCurrent Rating60AVoltage Rating - AC600VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSAOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 2.362" L (27.00mm x 60.00mm)	Category	Circuit Protection
SeriesHRCI-JFuse TypeCartridgeCurrent Rating60AVoltage Rating - AC600VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSAOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 2.362" L (27.00mm x 60.00mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating60AVoltage Rating - AC600VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCSAOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 2.362" L (27.00mm x 60.00mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 60A 60A 60A 60A 60B 60B 60A 60B 60B 60A 60B	Series	HRCI-J
Voltage Rating - AC  Voltage Rating - DC  250V  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  - Approvals  CSA  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  600V  250V  CSA  Fast  Class  Fast  Clectrical, Industrial  - CSA  - CSA  CSA  CSA  CSA  CSA  Cartridge, Non-Standard  1.063" Dia x 2.362" L (27.00mm x 60.00mm)	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Electrical, Industrial  Features - Class - Approvals CSA  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  250V  East Past  CSA  CSA  CSA  CONA  CON	Current Rating	60A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Electrical, Industrial - CSA - CSA - Approvals CSA CSA CSA CSA CSA Cartridge, Non-Standard 1.063" Dia x 2.362" L (27.00mm x 60.00mm)	Voltage Rating - AC	600V
Applications Electrical, Industrial  Features - Class - Approvals CSA Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 2.362" L (27.00mm x 60.00mm)	Voltage Rating - DC	250V
Features - Class - CSA Approvals CSA Operating Temperature - Sereaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 2.362" L (27.00mm x 60.00mm)	Response Time	Fast
Class - CSA Operating Temperature - Class Copacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 2.362" L (27.00mm x 60.00mm)	Applications	Electrical, Industrial
Approvals  CSA  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  CSA  Control  Local  CSA  Control  Control  CSA  Control  Control  Cartridge  Cartridg	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  1.063" Dia x 2.362" L (27.00mm x 60.00mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 1.063" Dia x 2.362" L (27.00mm x 60.00mm)	Approvals	CSA
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 2.362" L (27.00mm x 60.00mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 2.362" L (27.00mm x 60.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.063" Dia x 2.362" L (27.00mm x 60.00mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	1.063" Dia x 2.362" L (27.00mm x 60.00mm)
		Report errors?

#### **60CJ Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **60CJ Payment Methods**



















## **60CJ Shipping Methods**













If you have any question about 60CJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com