

# 614-43-314-31-012000

### 614-43-314-31-012000 Information

www.helsener.com	 614-43-314-31-012000 Mill-Max Manufacturing Corp. Connectors, Interconnects Sockets for ICs, Transistors CONN IC DIP SOCKET 14POS GOLD - For the pricing/inventory/lead time, please contact us	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# 614-43-314-31-012000 Specifications

Manufacturer Part Number614-43-31-012000ManufacturerMill-Max Manufacturing Corp.CategoryConnectors, InterconnectsPackage-Package-Series614TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)14 (2 x 7)Pitch - MatingO.100" (2.54mm)Contact Finish - MatingSolution (CorperContact Finish Thickness - MatingSolution (CorperMounting TypeHroug HoleFeaturesOpen FrameFreminationSolderFreminationSolderFreminationSolderFitch - Post0.100" (2.54mm)Forture Firish - PostSolderFreminationSolderFitch - Post0.100" (2.54mm)Fitch - PostSolderFitch - PostFitch - PostFitch - PostFitch - PostFitch - Po
CategoryConnectors, InterconnectsCategorySockets for ICs, TransistorsPackage-Series614TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)14 (2 x 7)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)
Number of Positions or Pins (Grid)Sockets for ICs, TransistorsPackage-Series614TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)14 (2 x 7)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish - Mating3µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameFreminationSolderPitch - Post0.100" (2.54mm)
Package-Series614TypeDIP,0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)14 (2 x 7)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameFininationSolderPitch - Post0.100" (2.54mm)
Series614TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)14 (2 x 7)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)
TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)14 (2 x 7)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)
Number of Positions or Pins (Grid)14 (2 x 7)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)
Contact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)
Contact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)
Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)
Mounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)
FeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)
TerminationSolderPitch - Post0.100" (2.54mm)
Pitch - Post 0.100" (2.54mm)
Contact Finish Deet
Contact Finish - Post Tin
Contact Finish Thickness - Post 200µin (5.08µm)
Contact Material - Post Brass Alloy
Housing Material Polycyclohexylenedimethylene Terephthalate (PCT), Polyester
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$
Report error

### 614-43-314-31-012000 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### 614-43-314-31-012000 Payment Methods



## 614-43-314-31-012000 Shipping Methods



If you have any question about 614-43-314-31-012000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com