

614-93-306-31-007000

614-93-306-31-007000 Information

Heisener.com Bedal anvectants have	 614-93-306-31-007000 Mill-Max Manufacturing Corp. Connectors, Interconnects Sockets for ICs, Transistors CONN IC DIP SOCKET 6POS GOLD - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



614-93-306-31-007000 Specifications

Manufacturer Part Number614-93-306-31-007000ManufacturerMill-Max Manufacturing Corp.CategoryConnectors, InterconnectsSockets for ICs, TransistorsSockets for ICs, TransistorsPackage-Series614TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)6(2 x 3)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Contact Finish PostSolderPitch - PostDin (0.50µm)Contact Finish Thickness - Post0.00" (2.54mm)Contact Finish Thickness - PostSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - PostSolderContact Finish Thickness - PostSolderContact Finish Thickness - PostSolay (0.50µm)Contact Material - PostSolay (0.50µm)Contact Finish Thickness - PostSolay (0.50µm)Contact Fini			
CategoryConnectors, InterconnectsPackage-Series614TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)6 (2 x 3)Pitch - Mating0.100" (2.54mm)Contact Finish - Mating30µin (0.76µm)Contact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Firth - PostDip 0.3" (2.54mm)Firth - PostOpen FrameFirth - PostSolderContact Finish - Post0.100" (2.54mm)Firth - Post0.100" (2.54mm)Contact Finish Thickness - Post0.00µin (5.08µm)	Manufacturer Part Number	614-93-306-31-007000	
Sockets for ICs, TransistorsPackage-Series614TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)6 (2 x 3)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Pitch - Post0.100" (2.54mm)Contact Finish Thickness - Post20µin (5.08µm)	Manufacturer	Mill-Max Manufacturing Corp.	
Package.Series614TypeDIP,0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)6 (2 x 3)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBerylium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Pitch - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)	Category	Connectors, Interconnects	
Series614TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)6 (2 x 3)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Pitch - Post0.100" (2.54mm)Contact Finish - PostSolderContact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54µm)		Sockets for ICs, Transistors	
TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)6 (2 x 3)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Contact Finish - Post200µin (5.08µm)	Package	-	
Number of Positions or Pins (Grid)6 (2 x 3)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish - Post20µin (5.08µm)	Series	614	
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish - Post200µin (5.08µm)	Туре	DIP, 0.3" (7.62mm) Row Spacing	
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish - Post20µin (5.08µm)	Number of Positions or Pins (Grid)	6 (2 x 3)	
Contact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)	Pitch - Mating	0.100" (2.54mm)	
Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)	Contact Finish - Mating	Gold	
Mounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)	Contact Finish Thickness - Mating	30µin (0.76µm)	
FeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)	Contact Material - Mating	Beryllium Copper	
TerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)	Mounting Type	Through Hole	
Pitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)	Features	Open Frame	
Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)	Termination	Solder	
Contact Finish Thickness - Post 200µin (5.08µm)	Pitch - Post	0.100" (2.54mm)	
	Contact Finish - Post	Tin-Lead	
Contact Material - Post Brass Alloy	Contact Finish Thickness - Post	200µin (5.08µm)	
	Contact Material - Post	Brass Alloy	
Housing Material Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	Housing Material	Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Operating Temperature	-55°C ~ 125°C	
Report errors			Report errors?

614-93-306-31-007000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

614-93-306-31-007000 Payment Methods





If you have any question about 614-93-306-31-007000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com