

614-93-424-31-018000

614-93-424-31-018000 Information

Heisener.com	 614-93-424-31-018000 Mill-Max Manufacturing Corp. Connectors, Interconnects Sockets for ICs, Transistors CONN IC DIP SOCKET 24POS GOLD - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



614-93-424-31-018000 Specifications

Manufacturer Part Number614-93-424-31-018000ManufacturerMill-Max Manufacturing Corp.CategoryConnectors, InterconnectsPackage-Package614TypeDIP, 0.4" (10.16mm) Row SpacingNumber of Positions or Pins (Grid)24 (2 x 12)Pitch - MatingGoldContact Finish - MatingGoldContact Finish Thickness - MatingSocierPacturesOpen FrameFeaturesOpen FramePitch - PostSolderTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostOpen FrameFeaturesOpen FramePitch - Post0.100" (2.54mm)Contact Finish - PostSolderPitch - PostOpen FramePitch - Post0.100" (2.54mm)Contact Finish - PostSolderPitch - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)			
CategoryConnectors, InterconnectsCategorySockets for ICs, TransistorsPackage-Series614TypeDIP, 0.4" (10.16mm) Row SpacingNumber of Positions or Pins (Grid)24 (2 x 12)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Firch - PostOlderContact Finish - PostSolderContact Finish - PostSolderContact Finish - Post0.100" (2.54mm)Contact Finish - PostSolderContact Finish - PostSolderContact Finish - PostSolderContact Finish - PostSolduri (5.08µm)	Manufacturer Part Number	614-93-424-31-018000	
Sockets for ICs, TransistorsPackage-Series614TypeDIP, 0.4" (10.16mm) Row SpacingNumber of Positions or Pins (Grid)24 (2 x 12)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Pitch - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)	Manufacturer	Mill-Max Manufacturing Corp.	
Package.Series614TypeDIP, 0.4" (10.16mm) Row SpacingNumber of Positions or Pins (Grid)24 (2 x 12)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - MatingBerylium CopperContact Material - MatingDen FramePeaturesOpen FrameFeaturesSolderPitch - Post0.100" (2.54mm)Contact Finish - PostSolderContact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm) <td< td=""><td>Category</td><td>Connectors, Interconnects</td><td></td></td<>	Category	Connectors, Interconnects	
Series614TypeDIP, 0.4" (10.16mm) Row SpacingNumber of Positions or Pins (Grid)24 (2 x 12)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Pitch - Post0.100" (2.54mm)Contact Finish - PostSolderContact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - PostSoldpin (5.08µm)		Sockets for ICs, Transistors	
TypeDIP, 0.4" (10.16mm) Row SpacingNumber of Positions or Pins (Grid)24 (2 x 12)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Contact Finish - Post0.100 (2.54mm)	Package	-	
Number of Positions or Pins (Grid)24 (2 x 12)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish - Post200µin (5.08µm)	Series	614	
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish - PostSilpuin (0.508µm)	Туре	DIP, 0.4" (10.16mm) Row Spacing	
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish - Post20µin (5.08µm)	Number of Positions or Pins (Grid)	24 (2 x 12)	
Contact Finish Thickness - Mating30μin (0.76μm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200μin (5.08μm)	Pitch - Mating	0.100" (2.54mm)	
Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)	Contact Finish - Mating	Gold	
Mounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)	Contact Finish Thickness - Mating	30µin (0.76µm)	
FeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)	Contact Material - Mating	Beryllium Copper	
TerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)	Mounting Type	Through Hole	
Pitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)	Features	Open Frame	
Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)	Termination	Solder	
Contact Finish Thickness - Post 200µin (5.08µm)	Pitch - Post	0.100" (2.54mm)	
	Contact Finish - Post	Tin-Lead	
	Contact Finish Thickness - Post	200µin (5.08µm)	
Contact Material - Post Brass Alloy	Contact Material - Post	Brass Alloy	
Housing Material Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	Housing Material	Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Operating Temperature	-55°C ~ 125°C	
Report errors			Report errors?

614-93-424-31-018000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

614-93-424-31-018000 Payment Methods





If you have any question about 614-93-424-31-018000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com