

# 614-93-642-31-018000

## 614-93-642-31-018000 Information

Heisener.com	 614-93-642-31-018000 Mill-Max Manufacturing Corp. Connectors, Interconnects Sockets for ICs, Transistors CONN IC DIP SOCKET 42POS GOLD - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## 614-93-642-31-018000 Specifications

Manufacturer Part Number614-93-642-31-018000ManufacturerMill-Max Manufacturing Corp.CategoryConnectors, InterconnectsSockets for ICs, TransistorsPackage-Series614TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)42 (2 x 21)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish - Mating30µin (0.76µm)Contact Finish Thickness - MatingBeryllium CopperMounting TypeOpen FrameFeaturesOpen FramePitch - Post0.100" (2.54mm)Contact Finish Thickness - Post0.100" (2.54µm)Contact Finish Thickness - Post0.100" (2.54µm			
CategoryConnectors, InterconnectsCategorySockets for ICs, TransistorsPackage-Series614TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)42 (2 x 21)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Contact Finish - PostSolderContact Finish Thickness - PostSolderContact Finish Thickness - PostSolderContact Finish Thickness - PostSolderContact Finish Thickness - PostSolduri (5.08µm)Contact Finish Thickness - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Manufacturer Part Number	614-93-642-31-018000	
NumberSockets for ICs, TransistorsPackage-Series614TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)42 (2 x 21)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Contact Finish Post0.00µin (5.08µm)Contact Finish Thickness - Post200µin (5.08µm)Housing Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Manufacturer	Mill-Max Manufacturing Corp.	
Package.Series614TypeDIP,06"(15.24mm)RowSpacingNumber of Positions or Pins (Grid)42 (2 x 21)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish - Mating30µin (0.76µm)Contact Finish Thickness - MatingBeryllium CopperMounting TypeBeryllium CopperFeaturesOpen FrameFreminationSolderPitch - Post10.0" (2.54mm)Fontact Finish Fhickness - MatingSolderFeaturesJolon" (2.54mm)FortantionSolderContact Finish - Post10.0" (2.54mm)Contact Finish - PostSoldin (0.50µm)Contact Finish - PostSoldin (0.50µm)Contact Finish - PostSoly (0.50µm)Contact Finish - PostSoly (0.50µm)Housing Material - PostBras AlloyHousing MaterialPolycolonexplenedmetuperter	Category	Connectors, Interconnects	
Series614TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)42 (2 x 21)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - PostSolderContact Finish - Post20µin (5.08µm)Contact Material - PostBras AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester		Sockets for ICs, Transistors	
TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)42 (2 x 21)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - PostBrass AlloyHousing Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Package	-	
Number of Positions or Pins (Grid)42 (2 x 21)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - Post200µin (5.08µm)Housing Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Series	614	
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameFreminationSolderPitch - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Туре	DIP, 0.6" (15.24mm) Row Spacing	
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Number of Positions or Pins (Grid)	42 (2 x 21)	
Contact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedfinethylene Terephthalate (PCT), Polyester	Pitch - Mating	0.100" (2.54mm)	
Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Contact Finish - Mating	Gold	
Mounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Contact Finish Thickness - Mating	30µin (0.76µm)	
FeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Contact Material - Mating	Beryllium Copper	
TerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylene Terephthalate (PCT), Polycester	Mounting Type	Through Hole	
Pitch - Post0.100" (2.54mm)Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Features	Open Frame	
Contact Finish - PostTin-LeadContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Termination	Solder	
Contact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Pitch - Post	0.100" (2.54mm)	
Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Contact Finish - Post	Tin-Lead	
Housing Material Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	Contact Finish Thickness - Post	200µin (5.08µm)	
	Contact Material - Post	Brass Alloy	
Occurations Transmission 550C 1250C	Housing Material	Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	
$-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Operating Temperature	-55°C ~ 125°C	
Report erro			Report errors?

## 614-93-642-31-018000 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### 614-93-642-31-018000 Payment Methods





If you have any question about 614-93-642-31-018000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com