

# 61V102KCFCA

Request a Quote

### 61V102KCFCA Information

	Part Number	61V102KCFCA
19 1)	Manufacturer	AVX Corporation
www.heisener.com	Category	Capacitors Ceramic Capacitors
	Description	CAP CER 1000PF 400VAC RADIAL
	Package	Radial, Disc
		For the pricing/inventory/lead time, please contact
		us
For Reference Only		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# 61V102KCFCA Specifications

Manufacturer Part Number61V102KCFCAManufacturer CapacitonsCapacitonsCategoryCapacitonsPackageRadial, DiscPackage-Capacitance1000pFTolerance±10%Voltage - Rated400VACTomperature Coefficient-Operating Temperature-Pactange-RatingsX1, Y1ApplicationsSafetyFailure Rate-Mounting TypeNongh HolePackage / CaseSafetySize / Dimension0.554* Dia (0.00mm)Height - Saetad (Max)0.197* (5.00mm)Tickness (Max)-Lead Spacing0.394* (10.00mm)Lead SpacingSaretyLead SpacingSarety <trr>Lead SpacingSarety<!--</th--><th></th><th></th></trr>		
Arror Capacitors   Package Radial, Disc   Package Radial, Disc   Series -   Capacitance 1000pF   Tolerance ±10%   Voltage - Rated 400VAC   Tomperature Coefficient -   Operating Temperature -   Pactage -   Ratings X1, Y1   Applications Safety   Failure Rate -   Mounting Type Safety   Size / Dimension 0.354" Dia(Polomm)   Size / Dimension 0.197" (Sofomm)   Height - Seated (Max) -   Thickness (Max) 3.04" (10.00mm)   Lead Spacing Safety (10.00mm)	Manufacturer Part Number	61V102KCFCA
AckageCeranic CapacitorsPackageRadial, DiscSeries-Capacitance1000pFTolerance±10%Voltage - Rated400VACTemperature Coefficient-Operating Temperature-40°C ~ 125°CFeatures-RatingsX1, Y1ApplicationsSafetyFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension.197" (5.00mm)Height - Seated (Max).197" (5.00mm)Thickness (Max)-Lead Spacing0.394" (10.00mm)Lead StyleStraight	Manufacturer	AVX Corporation
PackageRadial, DiscSeries-Capacitance1000pFTolerance±10%Voltage - Rated400VACTemperature Coefficient-Operating Temperature-40°C ~ 125°CFeatures-RatingsX1, Y1ApplicationsSafetyFailure Rate-Mounting TypeSafetySize / Dimension0.54* Dia (9.00mm)Height - Seated (Max)0.54* Dia (9.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.394* (10.00mm)Lead SpacingSizely (10.00mm)Lead StyleStraight	Category	Capacitors
Series-Capacitance1000pFTolerance±10%Voltage - Rated400VACTemperature Coefficient-Operating Temperature-40°C ~ 125°CFeatures-RatingsX1, Y1ApplicationsSafetyFailure Rate-Mounting TypeMough HoleSize / Dimension0.354" Dia (9.00mm)Height - Seated (Max)0.197" (5.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.394" (10.00mm)Lead StyleStraight		Ceramic Capacitors
Capacitance1000pFTolerance±10%Voltage - Rated400VACTemperature Coefficient-Operating Temperature-40°C ~ 125°CFeatures-RatingsSafetyApplicationsSafetyFailure Rate-Nounting TypeSafetySize / Dimension0.354" Dia (9.00mm)Size / Dimension0.197" (5.00mm)Height - Seated (Max)0.197" (5.00mm)Lead SpacingSafetyLead SpacingSafetyStarbySafe	Package	Radial, Disc
Tolerance±10%Voltage - Rated400VACTemperature Coefficient-Operating Temperature-40°C ~ 125°CFeatures-RatingsX1, Y1ApplicationsSafetyFailure Rate-Mounting TypeNorde HolePackage / CaseRadial, DiscSize / Dimension0.354" Dia (9.00mm)Height - Seated (Max)0.197" (5.00mm)Thickness (Max)0.394" (10.00mm)Lead SpacingSaringthKate StyleSaringth	Series	-
Voltage - Rated400VACTemperature Coefficient-Operating Temperature-40°C ~ 125°CFeatures-RatingsX1, Y1ApplicationsSafetyFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.1354" Dia (9.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.394" (10.00mm)Lead StyleStraight	Capacitance	1000pF
Temperature Coefficient-Operating Temperature-40°C ~ 125°CFeatures-RatingsX1, Y1ApplicationsSafetyFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.354" Dia (9.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.394" (10.00mm)Lead StyleStraight	Tolerance	±10%
Operating Temperature-40°C ~ 125°CFeatures-RatingsX1, Y1ApplicationsSafetyFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.354" Dia (9.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.394" (10.00mm)Lead StyleStraight	Voltage - Rated	400VAC
Features-Features-RatingsX1, Y1ApplicationsSafetyFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.354" Dia (9.00mm)Height - Seated (Max)0.197" (5.00mm)Thickness (Max)-Lead Spacing0.394" (10.00mm)Lead StyleStraight	Temperature Coefficient	-
RatingsX1, Y1ApplicationsSafetyFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.354" Dia (9.00mm)Height - Seated (Max)0.197" (5.00mm)Thickness (Max)0.394" (10.00mm)Lead SpacingStraight	Operating Temperature	-40°C ~ 125°C
ApplicationsSafetyFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.354" Dia (9.00mm)Height - Seated (Max)0.197" (5.00mm)Thickness (Max)-Lead Spacing0.394" (10.00mm)Lead StyleStraight	Features	-
Failure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.354" Dia (9.00mm)Height - Seated (Max)0.197" (5.00mm)Thickness (Max)-Lead Spacing0.394" (10.00mm)Lead StyleStraight	Ratings	X1, Y1
Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.354" Dia (9.00mm)Height - Seated (Max)0.197" (5.00mm)Thickness (Max)-Lead Spacing0.394" (10.00mm)Lead StyleStraight	Applications	Safety
Package / CaseRadial, DiscSize / Dimension0.354" Dia (9.00mm)Height - Seated (Max)0.197" (5.00mm)Thickness (Max)-Lead Spacing0.394" (10.00mm)Lead StyleStraight	Failure Rate	-
Size / Dimension0.354" Dia (9.00mm)Height - Seated (Max)0.197" (5.00mm)Thickness (Max)-Lead Spacing0.394" (10.00mm)Lead StyleStraight	Mounting Type	Through Hole
Height - Seated (Max)0.197" (5.00mm)Thickness (Max)-Lead Spacing0.394" (10.00mm)Lead StyleStraight	Package / Case	Radial, Disc
Thickness (Max)-Lead Spacing0.394" (10.00mm)Lead StyleStraight	Size / Dimension	0.354" Dia (9.00mm)
Lead Spacing0.394" (10.00mm)Lead StyleStraight	Height - Seated (Max)	0.197" (5.00mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.394" (10.00mm)
Report errors?	Lead Style	Straight
		Report errors?

#### 61V102KCFCA Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# 61V102KCFCA Payment Methods



## 61V102KCFCA Shipping Methods



If you have any question about 61V102KCFCA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com