



61V102SCFCJ Information



For Reference Only

Part Number 61V102SCFCJ
Manufacturer AVX Corporation
Category Capacitors

Ceramic Capacitors

Description CAP CER 1000PF 400VAC RADIAL

Package Radial, Disc

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









61V102SCFCJ Specifications

Manufacturer Part Number 61V102SCFCJ Manufacturer AVX Corporation Category Capacitors Package Radial, Disc Series - Capacitance 1000pF Tolerance -20%, +50% Voltage - Rated 400VAC Temperature Coefficient - Operating Temperature -40°C ~ 125°C Features - Ratings X1, Y1 Applications Safety Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.354" Dia (9.00mm) Height - Seated (Max) 0.197" (5.00mm) Thickness (Max) - Lead Spacing 0.394" (10.00mm) Lead Style Straight		
Category Capacitors Package Radial, Disc Series - Capacitance 1000pF Tolerance -20%, +50% Voltage - Rated 400VAC Temperature Coefficient - Operating Temperature -40°C ~ 125°C Features - Ratings X1, Y1 Applications Safety Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.354" Dia (9.00mm) Height - Seated (Max) 0.197" (5.00mm) Thickness (Max) - Lead Spacing 0.394" (10.00mm) Lead Style Straight	Manufacturer Part Number	61V102SCFCJ
Package Radial, Disc Series - Capacitance 1000pF Tolerance -20%, +50% Voltage - Rated 400VAC Temperature Coefficient - Operating Temperature -40°C ~ 125°C Features - Ratings X1, Y1 Applications Safety Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.354" Dia (9.00mm) Height - Seated (Max) 0.197" (5.00mm) Thickness (Max) - Lead Spacing 0.394" (10.00mm) Lead Style Straight	Manufacturer	AVX Corporation
Package Radial, Disc Series - Capacitance 1000pF Tolerance -20%, +50% Voltage - Rated 400VAC Temperature Coefficient - Operating Temperature -40°C ~ 125°C Features - Ratings X1, Y1 Applications Safety Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.354" Dia (9.00mm) Height - Seated (Max) 0.197" (5.00mm) Thickness (Max) - Lead Spacing 0.394" (10.00mm) Lead Style Straight	Category	Capacitors
Series - Capacitance 1000pF Tolerance -20%, +50% Voltage - Rated 400VAC Temperature Coefficient - Operating Temperature -40°C ~ 125°C Features - Ratings X1, Y1 Applications Safety Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.354" Dia (9.00mm) Height - Seated (Max) 0.197" (5.00mm) Thickness (Max) - Lead Spacing 0.394" (10.00mm) Lead Style Straight		Ceramic Capacitors
Capacitance 1000pF Tolerance -20%, +50% Voltage - Rated 400VAC Temperature Coefficient - Operating Temperature -40°C ~ 125°C Features - Ratings X1, Y1 Applications Safety Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.354" Dia (9.00mm) Height - Seated (Max) 0.197" (5.00mm) Thickness (Max) - Lead Spacing 0.394" (10.00mm) Lead Style Straight	Package	Radial, Disc
Tolerance -20%, +50% Voltage - Rated 400VAC Temperature Coefficient - Operating Temperature -40°C ~ 125°C Features - Ratings X1, Y1 Applications Safety Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.354" Dia (9.00mm) Height - Seated (Max) 0.197" (5.00mm) Thickness (Max) - Lead Spacing 0.394" (10.00mm) Lead Style Straight	Series	-
Voltage - Rated400VACTemperature Coefficient-Operating Temperature-40°C ~ 125°CFeatures-RatingsX1, Y1ApplicationsSafetyFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.354" Dia (9.00mm)Height - Seated (Max)0.197" (5.00mm)Thickness (Max)-Lead Spacing0.394" (10.00mm)Lead StyleStraight	Capacitance	1000pF
Temperature Coefficient Operating Temperature -40°C ~ 125°C Features - Ratings X1, Y1 Applications Safety Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style Straight	Tolerance	-20%, +50%
Operating Temperature -40°C ~ 125°C Features - Ratings X1, Y1 Applications Safety Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.354" Dia (9.00mm) Height - Seated (Max) Thickness (Max) - Lead Spacing 0.394" (10.00mm) Lead Style Straight	Voltage - Rated	400VAC
Features - Catings - Catin	Temperature Coefficient	-
Ratings X1, Y1 Applications Safety Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.354" Dia (9.00mm) Height - Seated (Max) 0.197" (5.00mm) Thickness (Max) - Lead Spacing 0.394" (10.00mm) Lead Style Straight	Operating Temperature	-40°C ~ 125°C
Applications Safety Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.354" Dia (9.00mm) Height - Seated (Max) 0.197" (5.00mm) Thickness (Max) - Lead Spacing 0.394" (10.00mm) Lead Style Straight	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.354" Dia (9.00mm) Height - Seated (Max) 0.197" (5.00mm) Thickness (Max) - Lead Spacing 0.394" (10.00mm) Lead Style Straight	Ratings	X1, Y1
Mounting Type Package / Case Radial, Disc Size / Dimension 0.354" Dia (9.00mm) Height - Seated (Max) 0.197" (5.00mm) Thickness (Max) - Lead Spacing 0.394" (10.00mm) Lead Style Straight	Applications	Safety
Package / Case Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style Radial, Disc 0.354" Dia (9.00mm)	Failure Rate	-
Size / Dimension 0.354" Dia (9.00mm) Height - Seated (Max) 0.197" (5.00mm) Thickness (Max) - Lead Spacing 0.394" (10.00mm) Lead Style Straight	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style 0.197" (5.00mm) - Under Style 0.394" (10.00mm) Straight	Package / Case	Radial, Disc
Thickness (Max) Lead Spacing 0.394" (10.00mm) Lead Style Straight	Size / Dimension	0.354" Dia (9.00mm)
Lead Spacing0.394" (10.00mm)Lead StyleStraight	Height - Seated (Max)	0.197" (5.00mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.394" (10.00mm)
Report errors?	Lead Style	Straight
		Report errors?

61V102SCFCJ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

61V102SCFCJ Payment Methods



















61V102SCFCJ Shipping Methods













If you have any question about 61V102SCFCJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com