

62002 Information



For Reference Only

Part Number 62002

Manufacturer Talema Group LLC

Category Transformers

Power Transformers

Description XFRMR TOROIDAL 1.6VA CHAS MOUNT

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









62002 Specifications

Manufacturer Part Number 62002 Manufacturer Talema Group LLC Category Transformers Power Transformers Package - Series Standard Mini Type Toroidal Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 134mA, Series 67mA Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 1.6 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 17.00mm Voltage - Isolation 4000Vrms		
CategoryTransformersPackage-SeriesStandard MiniTypeToroidalVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 134mA, Series 67mAPrimary Winding(s)DualSecondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max1.6 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension-Height - Seated (Max)17.00mm	Manufacturer Part Number	62002
Package - Standard Mini Type Toroidal Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 134mA, Series 67mA Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 1.6 VA Mounting Type Chassis Mount Termination Style Size / Dimension - Height - Seated (Max) 17.00mm	Manufacturer	Talema Group LLC
Package - Series Standard Mini Type Toroidal Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 134mA, Series 67mA Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 1.6 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 17.00mm	Category	Transformers
Series Standard Mini Type Toroidal Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 134mA, Series 67mA Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 1.6 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 17.00mm		Power Transformers
Type Toroidal Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 134mA, Series 67mA Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 1.6 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 17.00mm	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 134mA, Series 67mA Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 1.6 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension Height - Seated (Max) 17.00mm	Series	Standard Mini
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 134mA, Series 67mA Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 1.6 VA Mounting Type Chassis Mount Termination Style Size / Dimension - Height - Seated (Max) Parallel 12V, Series 24V Parallel 134mA, Series 67mA Dual Single, Multiple Taps No Vo 1.6 VA 1.6 VA 1.6 VA Mounting Type Chassis Mount 1.7.00mm	Type	Toroidal
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max Mounting Type Chassis Mount Termination Style Size / Dimension	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Center Tap No Power - Max 1.6 VA Mounting Type Chassis Mount Termination Style Size / Dimension - Height - Seated (Max) Dual Single, Multiple Taps No 1.6 VA Wive Leads 1.6 VA Wire Leads 1.7.00mm	Voltage - Secondary (Full Load)	Parallel 12V, Series 24V
Secondary Winding(s) Center Tap No Power - Max 1.6 VA Mounting Type Chassis Mount Termination Style Size / Dimension - Height - Seated (Max) Single, Multiple Taps No 1.6 VA Wive Leads 1.6 VA 1.7 VA	Current - Output (Max)	Parallel 134mA, Series 67mA
Center Tap No Power - Max 1.6 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 17.00mm	Primary Winding(s)	Dual
Power - Max 1.6 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 17.00mm	Secondary Winding(s)	Single, Multiple Taps
Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 17.00mm	Center Tap	No
Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 17.00mm	Power - Max	1.6 VA
Size / Dimension - Height - Seated (Max) 17.00mm	Mounting Type	Chassis Mount
Height - Seated (Max) 17.00mm	Termination Style	Wire Leads
	Size / Dimension	-
Voltage - Isolation 4000Vrms	Height - Seated (Max)	17.00mm
	Voltage - Isolation	4000Vrms
Weight 0.157 lb (71.21g)	Weight	0.157 lb (71.21g)
Report errors?		Report errors?

62002 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

62002 Payment Methods



















62002 Shipping Methods













If you have any question about 62002, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com