

62051 Information



For Reference Only

Part Number 62051

Manufacturer Talema Group LLC

Category Transformers
Power Transformers

Description XFRMR TOROIDAL 15VA CHAS MOUNT

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









62051 Specifications

Manufacturer Part Number 62051 Manufacturer Talema Group LLC Category Transformers Power Transformers Power Transformers Package - Series Standard Mini Type Toroidal Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 9V, Series 18V Current - Output (Max) Parallel 1.66A, Series 833mA Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 15 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 24.00mm Voltage - Isolation 4000Vrms Weight 0.578 lb (262 18g)		
Category Power Transformers Power Transformers Package Series Standard Mini Type Toroidal Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 9V, Series 18V Current - Output (Max) Parallel 1.66A, Series 833mA Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 15 VA Mounting Type Chassis Mount Termination Style Size / Dimension - Height - Seated (Max) Voltage - Isolation Transformers Power Transformers - Category Transformers Power Transformers Standard Mini No Parallel 9V, Series 18V Parallel 1.66A, Series 833mA Primary Winding(s) Dual Single, Multiple Taps Chassis Mount 45 VA Mounting Type Chassis Mount 4000Vrms	Manufacturer Part Number	62051
Package Series Standard Mini Type Toroidal Voltage - Primary Voltage - Secondary (Full Load) Parallel 9V, Series 18V Current - Output (Max) Parallel 1.66A, Series 833mA Primary Winding(s) Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max I5 VA Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Power - Isolation Power Transformers - Standard Mini Standard Mini Toroidal Parallel 1.66A, Series 837mA Parallel 1.66A, Series 833mA Primary Winding(s) Chassis Mount Single, Multiple Taps No Chassis Mount 45 VA Mounting Type Chassis Mount 4600Vrms	Manufacturer	Talema Group LLC
Package - Series Standard Mini Type Toroidal Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 9V, Series 18V Current - Output (Max) Parallel 1.66A, Series 833mA Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 15 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) Voltage - Isolation 4000Vrms	Category	Transformers
Series Standard Mini Type Toroidal Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 9V, Series 18V Current - Output (Max) Parallel 1.66A, Series 833mA Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 15 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 24.00mm Voltage - Isolation 4000Vrms		Power Transformers
Type Toroidal Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 9V, Series 18V Current - Output (Max) Parallel 1.66A, Series 833mA Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 15 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 24.00mm Voltage - Isolation 4000Vrms	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 9V, Series 18V Current - Output (Max) Parallel 1.66A, Series 833mA Primary Winding(s) Secondary Winding(s) Center Tap No Power - Max Mounting Type Chassis Mount Termination Style Size / Dimension - Height - Seated (Max) Voltage - Isolation 115V, 230V Parallel 1.66A, Series 833mA Dual Single, Multiple Taps Chassis Mount 15 VA Wire Leads 24.00mm 4000Vrms	Series	Standard Mini
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 1.66A, Series 833mA Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 15 VA Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Parallel 9V, Series 18V Parallel 1.66A, Series 833mA Dual Single, Multiple Taps No Chassis Mount 15 VA Chassis Mount 4000Vrms	Type	Toroidal
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 15 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension Height - Seated (Max) Voltage - Isolation Parallel 1.66A, Series 833mA Dual Single, Multiple Taps No 15 VA Voltage - Isolation Automatical Style Automatical Style Automatical Size / Output Automatical Size / O	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Center Tap No Power - Max Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Dual Single, Multiple Taps No Chassis Mount 15 VA Chassis Mount - Height - Wire Leads 24.00mm 4000Vrms	Voltage - Secondary (Full Load)	Parallel 9V, Series 18V
Secondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max15 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension-Height - Seated (Max)24.00mmVoltage - Isolation4000Vrms	Current - Output (Max)	Parallel 1.66A, Series 833mA
Center Tap No Power - Max 15 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 24.00mm Voltage - Isolation 4000Vrms	Primary Winding(s)	Dual
Power - Max 15 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 24.00mm Voltage - Isolation 4000Vrms	Secondary Winding(s)	Single, Multiple Taps
Mounting TypeChassis MountTermination StyleWire LeadsSize / Dimension-Height - Seated (Max)24.00mmVoltage - Isolation4000Vrms	Center Tap	No
Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 24.00mm Voltage - Isolation 4000Vrms	Power - Max	15 VA
Size / Dimension - Height - Seated (Max) 24.00mm Voltage - Isolation 4000Vrms	Mounting Type	Chassis Mount
Height - Seated (Max) Voltage - Isolation 24.00mm 4000Vrms	Termination Style	Wire Leads
Voltage - Isolation 4000Vrms	Size / Dimension	-
	Height - Seated (Max)	24.00mm
Weight 0.578 lb (262.18g)	Voltage - Isolation	4000Vrms
0.570 to (202.10g)	Weight	0.578 lb (262.18g)
Report errors?		Report errors?

62051 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

62051 Payment Methods



















62051 Shipping Methods













If you have any question about 62051, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com