

6282-2PG-519 Information

Heisener.com

Part Number 6282-2PG-519

Manufacturer Conxall/Switchcraft

Category Connectors, Interconnects
Circular Connectors

Description CONN PLUG 2POS INLINE PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









6282-2PG-519 Specifications

| Manufacturer Part Number6282-2PG-519ManufacturerConxall/SwitchcraftCategoryConnectors, InterconnectsPackage-SeriesMini-Con-X?Connector TypePlug, Male PinsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshellVoltage - Rated600VCurrent Rating-Report errors? | | |
|--|--------------------------|---------------------------|
| CategoryConnectors, InterconnectsPackage-SeriesMini-Con-X?Connector TypePlug, Male PinsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshellVoltage - Rated600VCurrent Rating- | Manufacturer Part Number | 6282-2PG-519 |
| PackageCircular ConnectorsSeriesMini-Con-X?Connector TypePlug, Male PinsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshellVoltage - Rated600VCurrent Rating- | Manufacturer | Conxall/Switchcraft |
| Package-SeriesMini-Con-X?Connector TypePlug, Male PinsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshellVoltage - Rated600VCurrent Rating- | Category | Connectors, Interconnects |
| SeriesMini-Con-X?Connector TypePlug, Male PinsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshellVoltage - Rated600VCurrent Rating- | | Circular Connectors |
| Connector TypePlug, Male PinsNumber of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshellVoltage - Rated600VCurrent Rating- | Package | - |
| Number of Positions2Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshellVoltage - Rated600VCurrent Rating- | Series | Mini-Con-X? |
| Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation Keyed Ingress Protection Weathertight Shell Material, Finish Nylon Contact Finish Gold Features Backshell Voltage - Rated Current Rating - | Connector Type | Plug, Male Pins |
| Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation Keyed Ingress Protection Weathertight Shell Material, Finish Nylon Contact Finish Gold Features Backshell Voltage - Rated OOV Current Rating | Number of Positions | 2 |
| Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationKeyedIngress ProtectionWeathertightShell Material, FinishNylonContact FinishGoldFeaturesBackshellVoltage - Rated600VCurrent Rating- | Shell Size - Insert | - |
| Termination Solder Cup Fastening Type Bayonet Lock Orientation Keyed Ingress Protection Weathertight Shell Material, Finish Nylon Contact Finish Gold Features Backshell Voltage - Rated 600V Current Rating - | Shell Size, MIL | - |
| Fastening Type Orientation Keyed Ingress Protection Weathertight Shell Material, Finish Nylon Contact Finish Gold Features Backshell Voltage - Rated 600V Current Rating - | Mounting Type | Free Hanging (In-Line) |
| Orientation Keyed Ingress Protection Weathertight Shell Material, Finish Nylon Contact Finish Gold Features Backshell Voltage - Rated 600V Current Rating - | Termination | Solder Cup |
| Ingress Protection Weathertight Shell Material, Finish Nylon Contact Finish Gold Features Backshell Voltage - Rated 600V Current Rating - | Fastening Type | Bayonet Lock |
| Shell Material, FinishNylonContact FinishGoldFeaturesBackshellVoltage - Rated600VCurrent Rating- | Orientation | Keyed |
| Contact Finish Gold Features Backshell Voltage - Rated 600V Current Rating - | Ingress Protection | Weathertight |
| Features Backshell Voltage - Rated 600V Current Rating - | Shell Material, Finish | Nylon |
| Voltage - Rated 600V Current Rating - | Contact Finish | Gold |
| Current Rating - | Features | Backshell |
| | Voltage - Rated | 600V |
| Report errors? | Current Rating | - |
| | | Report errors? |

6282-2PG-519 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

6282-2PG-519 Payment Methods



















6282-2PG-519 Shipping Methods













If you have any question about 6282-2PG-519, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com