



## 62O681MADCA Information



For Reference Only

Part Number 62O681MADCA
Manufacturer AVX Corporation
Category Capacitors

Ceramic Capacitors

**Description** CAP CER 680PF 400VAC RADIAL

Package Radial, Disc

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 62O681MADCA Specifications

Manufacturer Part Number         620681MADCA           Manufacturer         AVX Corporation           Category         Capacitors           Package         Radial, Disc           Series         -           Capacitance         680pF           Tolerance         ±20%           Voltage - Rated         400V AC           Temperature Coefficient         -           Operating Temperature         -40°C ~ 125°C           Features         X1, Y2           Applications         Safety           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         0.276" Dia (7.00mm)           Height - Seated (Max)         0.157" (4.00mm)           Thickness (Max)         -           Lead Spacing         0.197" (5.00mm)           Lead Style         Straight		
Category         Capacitors           Package         Radial, Disc           Series         -           Capacitance         680pF           Tolerance         ±20%           Voltage - Rated         400VAC           Temperature Coefficient         -           Operating Temperature         -40°C ~ 125°C           Features         -           Ratings         X1, Y2           Applications         Safety           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         0.276" Dia (7.00mm)           Height - Seated (Max)         0.157" (4.00mm)           Thickness (Max)         -           Lead Spacing         0.197" (5.00mm)           Lead Style         Straight	Manufacturer Part Number	62O681MADCA
Package         Radial, Disc           Series         -           Capacitance         680pF           Tolerance         ±20%           Voltage - Rated         400VAC           Temperature Coefficient         -           Operating Temperature         -40°C ~ 125°C           Features         -           Ratings         X1, Y2           Applications         Safety           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         0.276" Dia (7.00mm)           Height - Seated (Max)         0.157" (4.00mm)           Thickness (Max)         -           Lead Spacing         0.197" (5.00mm)           Lead Style         Straight	Manufacturer	AVX Corporation
Package         Radial, Disc           Series         -           Capacitance         680pF           Tolerance         ±20%           Voltage - Rated         400VAC           Temperature Coefficient         -           Operating Temperature         -40°C ~ 125°C           Features         -           Ratings         X1, Y2           Applications         Safety           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         0.276" Dia (7.00mm)           Height - Seated (Max)         0.157" (4.00mm)           Thickness (Max)         -           Lead Spacing         0.197" (5.00mm)           Lead Style         Straight	Category	Capacitors
Series         -           Capacitance         680pF           Tolerance         ±20%           Voltage - Rated         400VAC           Temperature Coefficient         -           Operating Temperature         -40°C ~ 125°C           Features         -           Ratings         X1, Y2           Applications         Safety           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         0.276" Dia (7.00mm)           Height - Seated (Max)         0.157" (4.00mm)           Thickness (Max)         -           Lead Spacing         0.197" (5.00mm)           Lead Style         Straight		Ceramic Capacitors
Capacitance       680pF         Tolerance       ±20%         Voltage - Rated       400VAC         Temperature Coefficient       -         Operating Temperature       -40°C ~ 125°C         Features       -         Ratings       X1, Y2         Applications       Safety         Failure Rate       -         Mounting Type       Through Hole         Package / Case       Radial, Disc         Size / Dimension       0.276" Dia (7.00mm)         Height - Seated (Max)       0.157" (4.00mm)         Thickness (Max)       -         Lead Spacing       0.197" (5.00mm)         Lead Style       Straight	Package	Radial, Disc
Tolerance ±20%  Voltage - Rated 400VAC  Temperature Coefficient - 40°C ~ 125°C  Features - Katings X1, Y2  Applications Safety  Failure Rate - Mounting Type Through Hole  Package / Case Radial, Disc  Size / Dimension 0.276" Dia (7.00mm)  Height - Seated (Max) 0.157" (4.00mm)  Thickness (Max) - Lead Spacing 0.197" (5.00mm)  Lead Style Size / Size / Size / Straight	Series	-
Voltage - Rated 400VAC  Temperature Coefficient	Capacitance	680pF
Temperature Coefficient Operating Temperature -40°C ~ 125°C Features - Ratings X1, Y2 Applications Safety Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style Straight	Tolerance	±20%
Operating Temperature -40°C ~ 125°C Features - Ratings X1, Y2 Applications Safety Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.276" Dia (7.00mm) Height - Seated (Max) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Voltage - Rated	400VAC
Features  Ratings  X1, Y2  Applications  Safety  Failure Rate  - Mounting Type  Through Hole  Package / Case  Radial, Disc  Size / Dimension  Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  -  Straight  X1, Y2  X1, Y2  X2  X2  X3  X4  X1  X1  X2  X3  X4  X4  X4  X4  X4  X4  X4  X4  X4	Temperature Coefficient	-
Ratings X1, Y2  Applications Safety  Failure Rate - Mounting Type Through Hole  Package / Case Radial, Disc  Size / Dimension 0.276" Dia (7.00mm)  Height - Seated (Max) 0.157" (4.00mm)  Thickness (Max) - Lead Spacing 0.197" (5.00mm)  Lead Style Straight	Operating Temperature	-40°C ~ 125°C
Applications Safety Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.276" Dia (7.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.276" Dia (7.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Ratings	X1, Y2
Mounting Type Package / Case Radial, Disc Size / Dimension 0.276" Dia (7.00mm) Height - Seated (Max) 0.157" (4.00mm)  Thickness (Max) - Lead Spacing 0.197" (5.00mm) Lead Style Straight	Applications	Safety
Package / CaseRadial, DiscSize / Dimension0.276" Dia (7.00mm)Height - Seated (Max)0.157" (4.00mm)Thickness (Max)-Lead Spacing0.197" (5.00mm)Lead StyleStraight	Failure Rate	-
Size / Dimension       0.276" Dia (7.00mm)         Height - Seated (Max)       0.157" (4.00mm)         Thickness (Max)       -         Lead Spacing       0.197" (5.00mm)         Lead Style       Straight	Mounting Type	Through Hole
Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  0.157" (4.00mm)  -  0.197" (5.00mm)  Straight	Package / Case	Radial, Disc
Thickness (Max)  Lead Spacing  0.197" (5.00mm)  Lead Style  Straight	Size / Dimension	0.276" Dia (7.00mm)
Lead Spacing0.197" (5.00mm)Lead StyleStraight	Height - Seated (Max)	0.157" (4.00mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.197" (5.00mm)
Report errors?	Lead Style	Straight
		Report errors?

#### 62O681MADCA Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 62O681MADCA Payment Methods



















### 62O681MADCA Shipping Methods













If you have any question about 62O681MADCA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com