

630NH3G-690

630NH3G-690 Information

Heisener.com Betal Write Bana Ser	Part Number Manufacturer Category Description Package	630NH3G-690 Eaton Circuit Protection Electrical, Specialty Fuses FUSE SQ 630A 690VAC RECTANGULAR Rectangular, Blade For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



630NH3G-690 Specifications

Manufacturer Part Number630NH3G-690ManufacturerEatonCategoryCircuit ProtectionPackageElectrical, Specialty FusesPackageRetangular, BladeSeries-Fuse TypeSquareCurrent Rating630AVoltage Rating - AC690VVoltage Rating - DC-ApplicationsElectrical, IndustrialApplicationsElectrical, IndustrialCursent SameMidApprovalsCity DEApprovalsCity DEApprovalsCity DEApprovals-Aprovals-Apontage Same-Mouning TypeHolderPackage / CaseRetangel BaleSiz / Dimension2,07" the 2,835" Where S.OUT "H (68.00mm x 72.00mm x 78.00mm)Marce Marcel Ma		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareFuse TypeSquareCurrent RatingS00Voltage Rating - AC690VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFastIndicatingClassNHOperating Temperature-ApprovalsCE, VDEOperating Temperature-Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)	Manufacturer Part Number	630NH3G-690
ConstraintElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating630AVoltage Rating - AC690VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassNHOperating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2,677" L x 2,835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating630AVoltage Rating - AC690VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingOperating Temperature-Operating Capacity @ Rated Voltage-Nunting Type-Package / CaseRectangular, BladeSize / Dimension2.671" Lx 2.835" W x 3.071" H (68.00mnx 72.00mnx 78.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating630AVoltage Rating - AC690VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingOlarge NameCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage-Holder-Preakage / CaseRectangular, BladeSize / Dimension2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent RatingG30AVoltage Rating - AC690VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassNHApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage-HolderHolderPorkage / CaseRectangulandSize / Dimension2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)	Package	Rectangular, Blade
Current Rating630AVoltage Rating - AC690VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassNHApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectanguland, BladeSize / Dimension2,677 "L x 2,835" W x 3,071" H (68.00mm x 72.00mm x 78.00mm)	Series	-
Voltage Rating - AC690VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassNHApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangulandSize / Dimension2.67" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)	Fuse Type	Square
Voltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassNHApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage-Nounting TypeHolderPackage / CaseRectanguland, BladeSize / Dimension2.671" L x 2.835" W x 3.071" H (68.00m x 72.00m x 78.00m	Current Rating	630A
Response TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassNHApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2,677" L x 2,835" W x 3,071" H (68.00m x 72.00m x 75.00m x 7	Voltage Rating - AC	690V
ApplicationsElectrical, IndustrialFeaturesIndicatingClassNHApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage-HolderHolderPackage / CaseRectangular, BladeSize / Dimension2.671" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)	Voltage Rating - DC	-
FeaturesIndicatingClassNHApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangulang BalaeSize / Dimension2,671" L x 2,835" W x 3,071" H (68,00m x 72,00m x 78,00m	Response Time	Fast
ClassNHApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)	Applications	Electrical, Industrial
ApprovalsCE, VDEOperating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)	Class	NH
Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)	Approvals	CE, VDE
Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)	Operating Temperature	-
Package / Case Rectangular, Blade Size / Dimension 2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)	Breaking Capacity @ Rated Voltage	-
Size / Dimension 2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)	Mounting Type	Holder
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	2.677" L x 2.835" W x 3.071" H (68.00mm x 72.00mm x 78.00mm)
		Report errors?

630NH3G-690 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

630NH3G-690 Payment Methods





If you have any question about 630NH3G-690, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com