

# 63453-010LF

equest a Quote

### 63453-010LF Information

	Part Number	63453-010LF	
Heisener.com		Amphenol FCI	
	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	
	Description	CONN RECEPT 10POS 2MM STR DL PCB	
	Package	-	
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com	
		E-mail: salesdept@heisener.com	

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# 63453-010LF Specifications

Manufacturer Part Number63453-010LFManufacturerAmphenol FCICategoryConnectors, InterconnectsPackage-Package-SeriesMinitek?Connector TypeReceptacles, Female SocketsContact TypeFemale SocketSyleBoard to BoardNumber of Positions0Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - MatingNorg" (2.00mm)Mounting TypeHouge HoleFerminationSolderFerminationSolderFortinationSolderFortinationSolderFortinationSolderFortinationSolderFortinationSolderFortinationSolderFortinationSolderFastening TypeSolderFortinationSolderFortinationSolderFortinationSolderFortinationSolderFortinationSolderFortinationSolderFortinationSolderFortinationSolderFortinationSolderFortinationSolderFortinationSolderFortinationSolderFortinationSolderFortinationSolderFortinationSolderFortinationSolderFortinationSolderFortinationSolderFortinationSolder <th></th> <th></th>			
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesMinitek?Connector TypeReceptacleContact TypeReceptacleStyleBoard to BoardNumber of Positions10Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeDidleTerminationSolderFastening TypeSolderContact Finish - MatingGoldContact Finish - MatingBiak	Manufacturer Part Number	63453-010LF	
Actangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesMinitek?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions10Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeQuestContact Finish - MatingGoldContact Finish - MatingBiak	Manufacturer	Amphenol FCI	
Package-SeriesMinitek?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions10Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeQuichContact Finish - MatingGoldContact Finish - MatingBin (0.20µm)Isulation ColorBlack	Category	Connectors, Interconnects	
SeriesMinitek?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions10Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeQuidContact Finish - MatingGoldInsulation ColorBlack		Rectangular Connectors - Headers, Receptacles, Female Sockets	
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions10Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleFastening TypeSolderContact Finish - MatingGoldContact Finish - MatingBiak	Package	-	
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions10Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeNorgh HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlack	Series	Minitek?	
StyleBoard to BoardStyleBoard to BoardNumber of Positions10Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldKontart Finish Thickness - MatingBiack	Connector Type	Receptacle	
Number of Positions10Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBiack	Contact Type	Female Socket	
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlack	Style	Board to Board	
Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldKontact Finish Thickness - MatingBjan (0.20µm)Insulation ColorBlack	Number of Positions	10	
Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBjain (0.20µm)Insulation ColorBlack	Number of Positions Loaded	All	
Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBjan (0.20µm)Insulation ColorBlack	Pitch - Mating	0.079" (2.00mm)	
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingSµin (0.20µm)Insulation ColorBlack	Number of Rows	2	
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating8µin (0.20µm)Insulation ColorBlack	Row Spacing - Mating	0.079" (2.00mm)	
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating8µin (0.20µm)Insulation ColorBlack	Mounting Type	Through Hole	
Contact Finish - MatingGoldContact Finish Thickness - Mating8µin (0.20µm)Insulation ColorBlack	Termination	Solder	
Contact Finish Thickness - Mating8μin (0.20μm)Insulation ColorBlack	Fastening Type	Push-Pull	
Insulation Color Black	Contact Finish - Mating	Gold	
	Contact Finish Thickness - Mating	8µin (0.20µm)	
	Insulation Color	Black	
Insulation Height 0.177" (4.50mm)	Insulation Height	0.177" (4.50mm)	
Contact Length - Post 0.098" (2.50mm)	Contact Length - Post	0.098" (2.50mm)	
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Operating Temperature	-55°C ~ 125°C	
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0	

Contact Finish - Post	Tin	
Mated Stacking Heights	-	
Ingress Protection	-	
Features	-	
		Report errors?

## 63453-010LF Guarantees




#### **Quality Guarantees**

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 63453-010LF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com