

### 6368532-2 Information

Heisener.com

**Part Number** 6368532-2

Manufacturer TRP Connector B.V.

Category Connectors, Interconnects

Modular Connectors - Jacks With Magnetics

**Description** CONN MAGJACK 1PORT 100 BASE-T

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 6368532-2 Specifications

ManufacturerTRP Connector B.V.CategoryConnectors, Interconnects Modular Connectors - Jacks With MagneticsPackage-SeriesMagJack?Connector TypeRJ45 with USB A, DualNumber of Ports1Number of Rows1Applications10/100 Base-TMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board1.237" (31.42mm)LED ColorYellow - GreenNumber of Cores per Jack5ShieldingShielded, EMI FingerFeaturesBoard Lock, Decoupling CapacitanceTab DirectionUpContact MaterialPhosphor BronzeContact FinishGold		
Category  Connectors, Interconnects  Modular Connectors - Jacks With Magnetics  Package  - Series  MagJack?  Connector Type  RJ45 with USB A, Dual  Number of Ports  1 Number of Rows  1 Applications  10/100 Base-T  Mounting Type  Through Hole  Orientation  90° Angle (Right)  Termination  Solder  Height Above Board  1.237" (31.42mm)  LED Color  Yellow - Green  Number of Cores per Jack  5 Shielding  Shielded, EMI Finger  Features  Board Lock, Decoupling Capacitance  Tab Direction  Up  Contact Material  Phosphor Bronze  Contact Finish  Gold	Manufacturer Part Number	6368532-2
Package - Series MagJack? Connector Type RJ45 with USB A, Dual Number of Ports 1 Number of Rows 1 Applications 10/100 Base-T Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 1.237" (31.42mm) LED Color Yellow - Green Number of Cores per Jack 5 Shielding Shielded, EMI Finger Features Board Lock, Decoupling Capacitance Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold	Manufacturer	TRP Connector B.V.
Package-SeriesMagJack?Connector TypeRJ45 with USB A, DualNumber of Ports1Number of Rows1Applications10/100 Base-TMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board1.237" (31.42mm)LED ColorYellow - GreenNumber of Cores per Jack5ShieldingShielded, EMI FingerFeaturesBoard Lock, Decoupling CapacitanceTab DirectionUpContact MaterialPhosphor BronzeContact FinishGold	Category	Connectors, Interconnects
Series MagJack? Connector Type RJ45 with USB A, Dual Number of Ports 1 Number of Rows 1 Applications 10/100 Base-T Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 1.237" (31.42mm) LED Color Yellow - Green Number of Cores per Jack 5 Shielding Shielded, EMI Finger Features Board Lock, Decoupling Capacitance Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold		Modular Connectors - Jacks With Magnetics
Connector Type RJ45 with USB A, Dual  Number of Ports 1  Number of Rows 1  Applications 10/100 Base-T  Mounting Type Through Hole  Orientation 90° Angle (Right)  Termination Solder  Height Above Board 1.237" (31.42mm)  LED Color Yellow - Green  Number of Cores per Jack 5  Shielding Shielded, EMI Finger  Features Board Lock, Decoupling Capacitance  Tab Direction Up  Contact Material Phosphor Bronze  Contact Finish Gold	Package	-
Number of Ports  1 Number of Rows  1 Applications  10/100 Base-T  Mounting Type  Through Hole Orientation  90° Angle (Right)  Termination  Solder  Height Above Board  1.237" (31.42mm)  LED Color  Yellow - Green  Number of Cores per Jack  5 Shielding  Shielded, EMI Finger  Features  Board Lock, Decoupling Capacitance  Tab Direction  Up  Contact Material  Phosphor Bronze  Contact Finish  Gold	Series	MagJack?
Number of Rows1Applications10/100 Base-TMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board1.237" (31.42mm)LED ColorYellow - GreenNumber of Cores per Jack5ShieldingShielded, EMI FingerFeaturesBoard Lock, Decoupling CapacitanceTab DirectionUpContact MaterialPhosphor BronzeContact FinishGold	Connector Type	RJ45 with USB A, Dual
Applications 10/100 Base-T  Mounting Type Through Hole  Orientation 90° Angle (Right)  Termination Solder  Height Above Board 1.237" (31.42mm)  LED Color Yellow - Green  Number of Cores per Jack 5  Shielding Shielded, EMI Finger  Features Board Lock, Decoupling Capacitance  Tab Direction Up  Contact Material Phosphor Bronze  Contact Finish Gold	Number of Ports	1
Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 1.237" (31.42mm) LED Color Yellow - Green Number of Cores per Jack 5 Shielding Shielded, EMI Finger Features Board Lock, Decoupling Capacitance Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold	Number of Rows	1
Orientation 90° Angle (Right)  Termination Solder  Height Above Board 1.237" (31.42mm)  LED Color Yellow - Green  Number of Cores per Jack 5  Shielding Shielded, EMI Finger  Features Board Lock, Decoupling Capacitance  Tab Direction Up  Contact Material Phosphor Bronze  Contact Finish Gold	Applications	10/100 Base-T
Termination Solder  Height Above Board 1.237" (31.42mm)  LED Color Yellow - Green  Number of Cores per Jack 5  Shielding Shielded, EMI Finger  Features Board Lock, Decoupling Capacitance  Tab Direction Up  Contact Material Phosphor Bronze  Contact Finish Gold	Mounting Type	Through Hole
Height Above Board  LED Color  Yellow - Green  Number of Cores per Jack  Shielding  Shielded, EMI Finger  Features  Board Lock, Decoupling Capacitance  Tab Direction  Up  Contact Material  Phosphor Bronze  Contact Finish  1.237" (31.42mm)  Yellow - Green  Yellow - Green  Yellow - Green  Up  Shielded, EMI Finger  Board Lock, Decoupling Capacitance  Up  Contact Finish  Gold	Orientation	90° Angle (Right)
LED ColorYellow - GreenNumber of Cores per Jack5ShieldingShielded, EMI FingerFeaturesBoard Lock, Decoupling CapacitanceTab DirectionUpContact MaterialPhosphor BronzeContact FinishGold	Termination	Solder
Number of Cores per Jack 5 Shielding Shielded, EMI Finger Features Board Lock, Decoupling Capacitance Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold	Height Above Board	1.237" (31.42mm)
Shielding Shielded, EMI Finger Features Board Lock, Decoupling Capacitance Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold	LED Color	Yellow - Green
Features Board Lock, Decoupling Capacitance Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold	Number of Cores per Jack	5
Tab Direction Up Contact Material Phosphor Bronze Contact Finish Gold	Shielding	Shielded, EMI Finger
Contact Material Phosphor Bronze Contact Finish Gold	Features	Board Lock, Decoupling Capacitance
Contact Finish Gold	Tab Direction	Up
	Contact Material	Phosphor Bronze
Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$	Contact Finish	Gold
	Operating Temperature	0°C ~ 70°C
Report errors?		Report errors?

### **6368532-2 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 6368532-2 Payment Methods



















# 6368532-2 Shipping Methods













If you have any question about 6368532-2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com