

63ZLH1800MEFCGC16X40

63ZLH1800MEFCGC16X40 Information



For Reference Only

Part Number 63ZLH1800MEFCGC16X40

Manufacturer Rubycon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 1800UF 20% 63V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









63ZLH1800MEFCGC16X40 Specifications

Manufacturer Part Number 63ZLH1800MEFCGC16X40 Manufacturer Rubycon Category Capacitors Package Radial, Can Series ZLH Capacitance 1800µF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 10000 Hrs @ 105°C Operating Temperature +40°C ~ 105°C Polarization General Purpose Ripple Current - Low Frequency 2.202A @ 120Hz Ripple Current - High Frequency - Lead Spacing 0.929° (7.50mm) Size / Dimension 0.630° Dia (16.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	_	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series ZLH Capacitance 1800µF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 10000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 19 mOhms Lead Spacing 19 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Radial, Can	Manufacturer Part Number	63ZLH1800MEFCGC16X40
Package Radial, Can Series ZLH Capacitance 1800µF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 10000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.202A @ 120Hz Ripple Current - High Frequency 19 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Taked 1800µF Radial, Can	Manufacturer	Rubycon
Package Radial, Can Series ZLH Capacitance 1800µF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 10000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.202A @ 120Hz Ripple Current - High Frequency - Impedance 19 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series ZLH Capacitance 1800μF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 10000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.202A @ 120Hz Ripple Current - High Frequency - Impedance 19 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 1800µF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 10000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.202A @ 120Hz Ripple Current - High Frequency - Impedance 19 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 10000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.202A @ 120Hz Ripple Current - High Frequency - Impedance 19 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	ZLH
Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.10000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.202A @ 120HzRipple Current - High Frequency-Impedance19 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	1800μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 10000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 2.202A @ 120Hz Ripple Current - High Frequency Impedance 19 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 10000 Hrs @ 105°C -40°C ~	Voltage - Rated	63V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.202A @ 120Hz Ripple Current - High Frequency - Impedance 19 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.202A @ 120Hz Ripple Current - High Frequency - Impedance 19 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	10000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 2.202A @ 120Hz Ripple Current - High Frequency - Impedance 19 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 19 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency - Impedance 19 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance19 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	2.202A @ 120Hz
Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	19 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.630" Dia (16.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	1.654" (42.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

63ZLH1800MEFCGC16X40 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

63ZLH1800MEFCGC16X40 Payment Methods



















63ZLH1800MEFCGC16X40 Shipping Methods













If you have any question about 63ZLH1800MEFCGC16X40, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com