

6443-036 Information

Heisener.com

For Reference Only

Part Number 6443-036

Manufacturer API Delevan Inc.

Category

Transformers **Power Transformers**

Description

XFRMR LAMINATED 2.5VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









6443-036 Specifications

Manufacturer Part Number Manufacturer API Delevan Inc. Transformers Power Transformers Power Transformers Power Transformers - Series 6443 Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Parallel 18V, Series 36V Current - Output (Max) Parallel 140mA, Series 70mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style Size / Dimension 34.93mm L x 28.58mm W Height - Seated (Max) Voltage - Isolation Weight Report errors?		
Category Transformers Power Transformers Package - Series 6443 Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 18V, Series 36V Current - Output (Max) Parallel 140mA, Series 70mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 34.93mm L x 28.58mm W Height - Seated (Max) 30.15mm Voltage - Isolation 4000Vrms Weight 0.25 lb (113.4g)	Manufacturer Part Number	6443-036
Package Series 6443 Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 18V, Series 36V Current - Output (Max) Parallel 140mA, Series 70mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style Size / Dimension 34.93mm L x 28.58mm W Height - Seated (Max) Weight Weight Power - Isolation 4000Vrms Weight	Manufacturer	API Delevan Inc.
Package - Gette 6443 Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 18V, Series 36V Current - Output (Max) Parallel 140mA, Series 70mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 34.93mm L x 28.58mm W Height - Seated (Max) 30.15mm Voltage - Isolation 4000Vrms Weight	Category	Transformers
Series 6443 Type Laminated Core Voltage - Primary 115 V, 230 V Voltage - Secondary (Full Load) Parallel 18 V, Series 36 V Current - Output (Max) Parallel 140 mA, Series 70 mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 34.93 mm L x 28.58 mm W Height - Seated (Max) 30.15 mm Voltage - Isolation 4000 Vrms Weight 0.25 lb (113.4g)		Power Transformers
Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 18V, Series 36V Current - Output (Max) Parallel 140mA, Series 70mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 34.93mm L x 28.58mm W Height - Seated (Max) 30.15mm Voltage - Isolation 4000Vrms Weight	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 18V, Series 36V Current - Output (Max) Parallel 140mA, Series 70mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension Height - Seated (Max) Voltage - Isolation Weight 115V, 230V Parallel 18V, Series 36V Parallel 140mA, Series 70mA Parallel 140mA, Series 70mA Parallel 18V, Series 36V Parallel 18V, Series 70mA Paral	Series	6443
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 140mA, Series 70mA Primary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Parallel 18V, Series 36V Parallel 18V, Series 70mA Push No 2.5 VA Mounting Type Through Hole PC Pin 34.93mm L x 28.58mm W 4000Vrms Voltage - Isolation Voltage - Isolation 0.25 lb (113.4g)	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Parallel 140mA, Series 70mA Dual Pual Pual Powal Powal Powal No Powal No Powal Powal No Powa	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 4000Vrms Weight Dual No 2.5 VA No 2.5 VA Through Hole PC Pin 34.93mm L x 28.58mm W 4000Vrms	Voltage - Secondary (Full Load)	Parallel 18V, Series 36V
Secondary Winding(s)DualCenter TapNoPower - Max2.5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension34.93mm L x 28.58mm WHeight - Seated (Max)30.15mmVoltage - Isolation4000VrmsWeight0.25 lb (113.4g)	Current - Output (Max)	Parallel 140mA, Series 70mA
Center Tap No Power - Max 2.5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 34.93mm L x 28.58mm W Height - Seated (Max) 30.15mm Voltage - Isolation 4000Vrms Weight 0.25 lb (113.4g)	Primary Winding(s)	Dual
Power - Max Mounting Type Through Hole PC Pin Size / Dimension Size / Dimension Height - Seated (Max) Voltage - Isolation Weight 2.5 VA PC Pin 34.93mm L x 28.58mm W 30.15mm 4000Vrms 0.25 lb (113.4g)	Secondary Winding(s)	Dual
Mounting Type Through Hole PC Pin Size / Dimension 34.93mm L x 28.58mm W Height - Seated (Max) Voltage - Isolation 4000Vrms Weight 0.25 lb (113.4g)	Center Tap	No
Termination Style PC Pin Size / Dimension 34.93mm L x 28.58mm W Height - Seated (Max) 30.15mm Voltage - Isolation 4000Vrms Weight 0.25 lb (113.4g)	Power - Max	2.5 VA
Size / Dimension34.93mm L x 28.58mm WHeight - Seated (Max)30.15mmVoltage - Isolation4000VrmsWeight0.25 lb (113.4g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation Weight 30.15mm 4000Vrms 0.25 lb (113.4g)	Termination Style	PC Pin
Voltage - Isolation 4000Vrms Weight 0.25 lb (113.4g)	Size / Dimension	34.93mm L x 28.58mm W
Weight 0.25 lb (113.4g)	Height - Seated (Max)	30.15mm
	Voltage - Isolation	4000Vrms
Report errors?	Weight	0.25 lb (113.4g)
		Report errors?

6443-036 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

6443-036 Payment Methods





















6443-036 Shipping Methods













If you have any question about 6443-036, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com