

#### 6448-012 Information

Heisener.com

For Reference Only

**Part Number** 6448-012

Manufacturer API Delevan Inc.

Category

Transformers

**Description** 

**Power Transformers** XFRMR LAMINATED 56VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 6448-012 Specifications

Manufacturer Part Number         6448-012           Manufacturer         API Delevan Inc.           Category         Transformers           Power Transformers         Power Transformers           Series         6448           Type         Laminated Core           Voltage - Primary         115V, 230V           Voltage - Secondary (Full Load)         Parallel 6.3V, Series 12.6V           Current - Output (Max)         Parallel 8.8A, Series 4.4A           Primary Winding(s)         Dual           Secondary Winding(s)         Dual           Center Tap         No           Power - Max         56 VA           Mounting Type         Through Hole           Termination Style         PC Pin           Size / Dimension         76.20mm L x 63.50mm W           Height - Seated (Max)         45.97mm           Voltage - Isolation         4000Vrms           Weight         1.7 lbs (771.1g)		
Category         Transformers           Package         -           Series         6448           Type         Laminated Core           Voltage - Primary         115V, 230V           Voltage - Secondary (Full Load)         Parallel 6.3V, Series 12.6V           Current - Output (Max)         Parallel 8.8A, Series 4.4A           Primary Winding(s)         Dual           Secondary Winding(s)         Dual           Center Tap         No           Power - Max         56 VA           Mounting Type         Through Hole           Termination Style         PC Pin           Size / Dimension         76.20mm L x 63.50mm W           Height - Seated (Max)         45.97mm           Voltage - Isolation         4000Vrms           Weight         1.7 lbs (771.1g)	Manufacturer Part Number	6448-012
Package         Power Transformers           Series         6448           Type         Laminated Core           Voltage - Primary         115V, 230V           Voltage - Secondary (Full Load)         Parallel 6.3V, Series 12.6V           Current - Output (Max)         Parallel 8.8A, Series 4.4A           Primary Winding(s)         Dual           Secondary Winding(s)         Dual           Center Tap         No           Power - Max         56 VA           Mounting Type         Through Hole           Termination Style         PC Pin           Size / Dimension         76.20mm L x 63.50mm W           Height - Seated (Max)         45.97mm           Voltage - Isolation         4000Vrms           Weight         1.7 lbs (771.1g)	Manufacturer	API Delevan Inc.
Package         -           Series         6448           Type         Laminated Core           Voltage - Primary         115V, 230V           Voltage - Secondary (Full Load)         Parallel 6.3V, Series 12.6V           Current - Output (Max)         Parallel 8.8A, Series 4.4A           Primary Winding(s)         Dual           Secondary Winding(s)         Dual           Center Tap         No           Power - Max         56 VA           Mounting Type         Through Hole           Termination Style         PC Pin           Size / Dimension         76.20mm L x 63.50mm W           Height - Seated (Max)         45.97mm           Voltage - Isolation         4000Vrms           Weight         1.7 lbs (771.1g)	Category	Transformers
Series         6448           Type         Laminated Core           Voltage - Primary         115V, 230V           Voltage - Secondary (Full Load)         Parallel 6.3V, Series 12.6V           Current - Output (Max)         Parallel 8.8A, Series 4.4A           Primary Winding(s)         Dual           Secondary Winding(s)         Dual           Center Tap         No           Power - Max         56 VA           Mounting Type         Through Hole           Termination Style         PC Pin           Size / Dimension         76.20mm L x 63.50mm W           Height - Seated (Max)         45.97mm           Voltage - Isolation         4000Vrms           Weight         1.7 lbs (771.1g)		Power Transformers
Type Laminated Core  Voltage - Primary 115V, 230V  Voltage - Secondary (Full Load) Parallel 6.3V, Series 12.6V  Current - Output (Max) Parallel 8.8A, Series 4.4A  Primary Winding(s) Dual  Secondary Winding(s) Dual  Center Tap No  Power - Max 56 VA  Mounting Type Through Hole  Termination Style PC Pin  Size / Dimension 76.20mm L x 63.50mm W  Height - Seated (Max) 45.97mm  Voltage - Isolation 4000Vrms  Weight	Package	-
Voltage - Primary  Voltage - Secondary (Full Load)  Parallel 6.3V, Series 12.6V  Current - Output (Max)  Parallel 8.8A, Series 4.4A  Primary Winding(s)  Dual  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  56 VA  Mounting Type  Through Hole  Termination Style  PC Pin  Size / Dimension  76.20mm L x 63.50mm W  Height - Seated (Max)  Voltage - Isolation  Weight  1.7 lbs (771.1g)	Series	6448
Voltage - Secondary (Full Load)  Current - Output (Max)  Parallel 8.8A, Series 12.6V  Primary Winding(s)  Dual  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  Mounting Type  Through Hole  Termination Style  PC Pin  Size / Dimension  Teight - Seated (Max)  Voltage - Isolation  Weight  Parallel 6.3V, Series 12.6V  Parallel 8.8A, Series 4.4A  Primary Winding (s)  Dual  No  Poul  No  Poul  Through Hole  PC Pin  4000Vrms  4000Vrms  Voltage - Isolation  1.7 lbs (771.1g)	Туре	Laminated Core
Current - Output (Max)Parallel 8.8A, Series 4.4APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max56 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension76.20mm L x 63.50mm WHeight - Seated (Max)45.97mmVoltage - Isolation4000VrmsWeight1.7 lbs (771.1g)	Voltage - Primary	115V, 230V
Primary Winding(s)  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  56 VA  Mounting Type  Through Hole  Termination Style  PC Pin  Size / Dimension  76.20mm L x 63.50mm W  Height - Seated (Max)  Voltage - Isolation  Weight  Dual  No  1.7 lbs (771.1g)	Voltage - Secondary (Full Load)	Parallel 6.3V, Series 12.6V
Secondary Winding(s)DualCenter TapNoPower - Max56 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension76.20mm L x 63.50mm WHeight - Seated (Max)45.97mmVoltage - Isolation4000VrmsWeight1.7 lbs (771.1g)	Current - Output (Max)	Parallel 8.8A, Series 4.4A
Center Tap No  Power - Max 56 VA  Mounting Type Through Hole  Termination Style PC Pin  Size / Dimension 76.20mm L x 63.50mm W  Height - Seated (Max) 45.97mm  Voltage - Isolation 4000Vrms  Weight 1.7 lbs (771.1g)	Primary Winding(s)	Dual
Power - Max  Mounting Type  Through Hole  Termination Style  PC Pin  Size / Dimension  76.20mm L x 63.50mm W  Height - Seated (Max)  Voltage - Isolation  4000Vrms  Weight  1.7 lbs (771.1g)	Secondary Winding(s)	Dual
Mounting Type Through Hole  PC Pin  Size / Dimension 76.20mm L x 63.50mm W  Height - Seated (Max) 45.97mm  Voltage - Isolation 4000Vrms  Weight 1.7 lbs (771.1g)	Center Tap	No
Termination Style PC Pin Size / Dimension 76.20mm L x 63.50mm W Height - Seated (Max) 45.97mm Voltage - Isolation 4000Vrms Weight 1.7 lbs (771.1g)	Power - Max	56 VA
Size / Dimension 76.20mm L x 63.50mm W  Height - Seated (Max) 45.97mm  Voltage - Isolation 4000Vrms  Weight 1.7 lbs (771.1g)	Mounting Type	Through Hole
Height - Seated (Max)  Voltage - Isolation  Weight  45.97mm  4000Vrms  1.7 lbs (771.1g)	Termination Style	PC Pin
Voltage - Isolation 4000Vrms Weight 1.7 lbs (771.1g)	Size / Dimension	76.20mm L x 63.50mm W
Weight 1.7 lbs (771.1g)	Height - Seated (Max)	45.97mm
	Voltage - Isolation	4000Vrms
Report errors?	Weight	1.7 lbs (771.1g)
		Report errors?

#### 6448-012 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 6448-012 Payment Methods





















### 6448-012 Shipping Methods













If you have any question about 6448-012, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com