

6448R-010 Information

Heisener.com

Part Number 6448R-010

Manufacturer API Delevan Inc. Category Transformers

Power Transformers

Description XFRMR LAMINATED 56VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









6448R-010 Specifications

Manufacturer Part Number 6448R-010 Manufacturer API Delevan Inc. Category Transformers Power Transformers Power Transformers Series 6448R Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 11.2A, Series 5.6A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 56 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 76.20mm L x 63.50mm W Height - Seated (Max) 45.97mm Voltage - Isolation 4000Vrms Weight 1.7 lbs (771.1g)		
CategoryTransformersPackage-Series6448RTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 5V, Series 10VCurrent - Output (Max)Parallel 11.2A, Series 5.6APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max56 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension76.20mm L x 63.50mm WHeight - Seated (Max)45.97mmVoltage - Isolation4000VrmsWeight1.7 lbs (771.1g)	Manufacturer Part Number	6448R-010
Package Power Transformers Series 6448R Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 11.2A, Series 5.6A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 56 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 76.20mm L x 63.50mm W Height - Seated (Max) 45.97mm Voltage - Isolation 4000Vrms Weight 1.7 lbs (771.1g)	Manufacturer	API Delevan Inc.
Package - Series 6448R Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 11.2A, Series 5.6A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 56 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 76.20mm L x 63.50mm W Height - Seated (Max) 45.97mm Voltage - Isolation 4000Vrms Weight 1.7 lbs (771.1g)	Category	Transformers
Series 6448R Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 11.2A, Series 5.6A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 56 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 76.20mm L x 63.50mm W Height - Seated (Max) 45.97mm Voltage - Isolation 4000Vrms Weight 1.7 lbs (771.1g)		Power Transformers
Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 11.2A, Series 5.6A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 56 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 76.20mm L x 63.50mm W Height - Seated (Max) 45.97mm Voltage - Isolation 4000Vrms Weight	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 5V, Series 10V Current - Output (Max) Parallel 11.2A, Series 5.6A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max Secondary Mounting Type Through Hole Termination Style PC Pin Size / Dimension 76.20mm L x 63.50mm W Height - Seated (Max) Voltage - Isolation Weight 1.7 lbs (771.1g)	Series	6448R
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 5V, Series 10V Parallel 11.2A, Series 5.6A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 56 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 76.20mm L x 63.50mm W Height - Seated (Max) Voltage - Isolation Weight Parallel 5V, Series 10V Parallel 11.2A, Series 5.6A Parallel 11.2A, Series 5.6A Parallel 11.2A, Series 10V Parallel 11.2A, Series 10V Pual No 400 4000Vrms 1.7 lbs (771.1g)	Туре	Laminated Core
Current - Output (Max) Parallel 11.2A, Series 5.6A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 56 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 76.20mm L x 63.50mm W Height - Seated (Max) Voltage - Isolation Weight 1.7 lbs (771.1g)	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 56 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 76.20mm L x 63.50mm W Height - Seated (Max) Voltage - Isolation Weight Dual No 1.7 lbs (771.1g)	Voltage - Secondary (Full Load)	Parallel 5V, Series 10V
Secondary Winding(s)DualCenter TapNoPower - Max56 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension76.20mm L x 63.50mm WHeight - Seated (Max)45.97mmVoltage - Isolation4000VrmsWeight1.7 lbs (771.1g)	Current - Output (Max)	Parallel 11.2A, Series 5.6A
Center Tap No Power - Max 56 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 76.20mm L x 63.50mm W Height - Seated (Max) 45.97mm Voltage - Isolation 4000Vrms Weight 1.7 lbs (771.1g)	Primary Winding(s)	Dual
Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension 76.20mm L x 63.50mm W Height - Seated (Max) 45.97mm Voltage - Isolation 4000Vrms Weight 1.7 lbs (771.1g)	Secondary Winding(s)	Dual
Mounting Type Through Hole PC Pin Size / Dimension 76.20mm L x 63.50mm W Height - Seated (Max) 45.97mm Voltage - Isolation 4000Vrms Weight 1.7 lbs (771.1g)	Center Tap	No
Termination Style PC Pin Size / Dimension 76.20mm L x 63.50mm W Height - Seated (Max) 45.97mm Voltage - Isolation 4000Vrms Weight 1.7 lbs (771.1g)	Power - Max	56 VA
Size / Dimension 76.20mm L x 63.50mm W Height - Seated (Max) 45.97mm Voltage - Isolation 4000Vrms Weight 1.7 lbs (771.1g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation Weight 45.97mm 4000Vrms 1.7 lbs (771.1g)	Termination Style	PC Pin
Voltage - Isolation 4000Vrms Weight 1.7 lbs (771.1g)	Size / Dimension	76.20mm L x 63.50mm W
Weight 1.7 lbs (771.1g)	Height - Seated (Max)	45.97mm
	Voltage - Isolation	4000Vrms
Report errors?	Weight	1.7 lbs (771.1g)
report circus.		Report errors?

6448R-010 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

6448R-010 Payment Methods



















6448R-010 Shipping Methods













If you have any question about 6448R-010, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com