



### 6560N562J602LE Information



For Reference Only

Part Number 6560N562J602LE
Manufacturer Knowles Novacap
Category Capacitors

Capacitors
Ceramic Capacitors

**Description** CAP RADIAL 6560,5600PF,6KV,5%,C0

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### 6560N562J602LE Specifications

Manufacturer Part Number         6560N562J602LE           Manufacturer         Knowles Novacap           Category         Capacitors           Package         Radial           Series         -           Capacitance         5600pF           Tolerance         ±5%           Voltage - Rated         6000V (6kV)           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         High Voltage           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.800" L x 0.402" W (20.30mm x 10.20mm)           Height - Seated (Max)         0.873" (22.18mm)           Thickness (Max)         -           Lead Spacing         0.681" (17.30mm)           Lead Spacing         0.681" (17.30mm)           Report errors?		
Category         Capacitors           Package         Radial           Series         -           Capacitance         5600pF           Tolerance         ±5%           Voltage - Rated         6000V (6kV)           Temperature Coefficient         COG, NPO           Operating Temperature         -55°C ~ 125°C           Features         High Voltage           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.800" L x 0.402" W (20.30mm x 10.20mm)           Height - Seated (Max)         0.873" (22.18mm)           Thickness (Max)         -           Lead Spacing         0.681" (17.30mm)           Lead Style         Straight	Manufacturer Part Number	6560N562J602LE
Package         Radial           Series         -           Capacitance         5600pF           Tolerance         ±5%           Voltage - Rated         6000V (6kV)           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         High Voltage           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.800" L x 0.402" W (20.30mm x 10.20mm)           Height - Seated (Max)         0.873" (22.18mm)           Thickness (Max)         -           Lead Spacing         0.681" (17.30mm)           Lead Style         Straight	Manufacturer	Knowles Novacap
Package         Radial           Series         -           Capacitance         5600pF           Tolerance         ±5%           Voltage - Rated         6000V (6kV)           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         High Voltage           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.800" L x 0.402" W (20.30mm x 10.20mm)           Height - Seated (Max)         0.873" (22.18mm)           Thickness (Max)         -           Lead Spacing         0.681" (17.30mm)           Lead Style         Straight	Category	Capacitors
Series         -           Capacitance         5600pF           Tolerance         ±5%           Voltage - Rated         6000V (6kV)           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         High Voltage           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.800" L x 0.402" W (20.30mm x 10.20mm)           Height - Seated (Max)         0.873" (22.18mm)           Thickness (Max)         -           Lead Spacing         0.681" (17.30mm)           Lead Style         Straight		Ceramic Capacitors
Capacitance         5600pF           Tolerance         ±5%           Voltage - Rated         6000V (6kV)           Temperature Coefficient         COG, NPO           Operating Temperature         -55°C ~ 125°C           Features         High Voltage           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.800" L x 0.402" W (20.30mm x 10.20mm)           Height - Seated (Max)         0.873" (22.18mm)           Thickness (Max)         -           Lead Spacing         0.681" (17.30mm)           Lead Style         Straight	Package	Radial
Tolerance         ±5%           Voltage - Rated         6000V (6kV)           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         High Voltage           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.800" L x 0.402" W (20.30mm x 10.20mm)           Height - Seated (Max)         0.873" (22.18mm)           Thickness (Max)         -           Lead Spacing         0.681" (17.30mm)           Lead Style         Straight	Series	-
Voltage - Rated6000V (6kV)Temperature CoefficientC0G, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.800" L x 0.402" W (20.30mm x 10.20mm)Height - Seated (Max)0.873" (22.18mm)Thickness (Max)-Lead Spacing0.681" (17.30mm)Lead StyleStraight	Capacitance	5600pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension Height - Seated (Max) Thickness (Max) - Lead Spacing Lead Style  COG, NP0 -55°C ~ 125°C Right General Purpose Fillow General Purpose Failure Rate - 0.800" L x 0.402" W (20.30mm x 10.20mm)  - 0.873" (22.18mm)  - 1.681" (17.30mm) Straight	Tolerance	±5%
Operating Temperature-55°C ~ 125°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.800" L x 0.402" W (20.30mm x 10.20mm)Height - Seated (Max)0.873" (22.18mm)Thickness (Max)-Lead Spacing0.681" (17.30mm)Lead StyleStraight	Voltage - Rated	6000V (6kV)
Features High Voltage  Ratings - Applications General Purpose  Failure Rate - Mounting Type Through Hole  Package / Case Radial  Size / Dimension 0.800" L x 0.402" W (20.30mm x 10.20mm)  Height - Seated (Max) 0.873" (22.18mm)  Thickness (Max) - Lead Spacing 0.681" (17.30mm)  Lead Style Straight	Temperature Coefficient	C0G, NP0
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.800" L x 0.402" W (20.30mm x 10.20mm)Height - Seated (Max)0.873" (22.18mm)Thickness (Max)-Lead Spacing0.681" (17.30mm)Lead StyleStraight	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.800" L x 0.402" W (20.30mm x 10.20mm) Height - Seated (Max) 0.873" (22.18mm) Thickness (Max) - Lead Spacing 0.681" (17.30mm) Lead Style Straight	Features	High Voltage
Failure Rate  Mounting Type Through Hole Package / Case Radial Size / Dimension 0.800" L x 0.402" W (20.30mm x 10.20mm) Height - Seated (Max) 0.873" (22.18mm)  Thickness (Max) - Lead Spacing 0.681" (17.30mm) Lead Style Straight	Ratings	-
Mounting Type  Package / Case  Radial  Size / Dimension  0.800" L x 0.402" W (20.30mm x 10.20mm)  Height - Seated (Max)  0.873" (22.18mm)  Thickness (Max)  -  Lead Spacing  0.681" (17.30mm)  Lead Style  Straight	Applications	General Purpose
Package / CaseRadialSize / Dimension0.800" L x 0.402" W (20.30mm x 10.20mm)Height - Seated (Max)0.873" (22.18mm)Thickness (Max)-Lead Spacing0.681" (17.30mm)Lead StyleStraight	Failure Rate	-
Size / Dimension       0.800" L x 0.402" W (20.30mm x 10.20mm)         Height - Seated (Max)       0.873" (22.18mm)         Thickness (Max)       -         Lead Spacing       0.681" (17.30mm)         Lead Style       Straight	Mounting Type	Through Hole
Height - Seated (Max)  Thickness (Max)  Lead Spacing  O.873" (22.18mm)  -  Lead Style  Straight	Package / Case	Radial
Thickness (Max)  Lead Spacing  0.681" (17.30mm)  Lead Style  Straight	Size / Dimension	0.800" L x 0.402" W (20.30mm x 10.20mm)
Lead Spacing0.681" (17.30mm)Lead StyleStraight	Height - Seated (Max)	0.873" (22.18mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.681" (17.30mm)
Report errors?	Lead Style	Straight
		Report errors?

#### 6560N562J602LE Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 6560N562J602LE Payment Methods



















### 6560N562J602LE Shipping Methods













If you have any question about 6560N562J602LE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com