



656C12503I2T Information



For Reference Only

Part Number 656C12503I2T

Manufacturer CTS-Frequency Controls

Category Crystals, Oscillators, Resonators

Oscillators

DescriptionOSC HCMOS SMDPackage6-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









656C12503I2T Specifications

Manufacturer Part Number Manufacturer CTS-Frequency Controls Category Crystals, Oscillators, Resonators Oscillators Package 6-SMD, No Lead Series 656C Type XO (Standard) Frequency 125MHz Function Enable/Disable Output HCMOS Voltage - Supply 2.5V Frequency Stability Departing Temperature -40°C ~ 85°C
Category Crystals, Oscillators, Resonators Oscillators Package 6-SMD, No Lead Series 656C Type XO (Standard) Frequency 125MHz Function Enable/Disable Output HCMOS Voltage - Supply Frequency Stability Operating Temperature Crystals, Oscillators, Resonators Oscillators Resonators 6-SMD, No Lead 6-SMD, No Lead 656C YOU (Standard) Frequency Stability 2.5 W 5-Supply 5-Supply 5-Supply 5-Supply 6-40°C ~ 85°C
Package 6-SMD, No Lead Series 656C Type XO (Standard) Frequency 125MHz Function Enable/Disable Output HCMOS Voltage - Supply 2.5V Frequency Stability ±50ppm Operating Temperature -40°C ~ 85°C
Package 6-SMD, No Lead Series 656C Type XO (Standard) Frequency 125MHz Function Enable/Disable Output HCMOS Voltage - Supply 2.5V Frequency Stability ±50ppm Operating Temperature -40°C ~ 85°C
Series $656C$ TypeXO (Standard)Frequency $125MHz$ FunctionEnable/DisableOutputHCMOSVoltage - Supply $2.5V$ Frequency Stability ± 50 ppmOperating Temperature -40 °C ~ 85 °C
Type XO (Standard) Frequency 125MHz Function Enable/Disable Output HCMOS Voltage - Supply 2.5V Frequency Stability ± 50 ppm Operating Temperature -40 °C ~ 85 °C
Frequency 125MHz Function Enable/Disable Output HCMOS Voltage - Supply 2.5V Frequency Stability ± 50 ppm Operating Temperature -40 °C ~ 85 °C
Function Enable/Disable Output HCMOS Voltage - Supply 2.5V Frequency Stability ± 50 ppm Operating Temperature -40°C ~ 85°C
Output HCMOS Voltage - Supply 2.5V Frequency Stability ± 50 ppm Operating Temperature -40°C ~ 85°C
Voltage - Supply 2.5V Frequency Stability ± 50 ppm Operating Temperature -40 °C ~ 85 °C
Frequency Stability $\pm 50 \text{ppm}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Community Community (Mars)
Current - Supply (Max) 20mA (Typ)
Ratings -
Mounting Type Surface Mount
Package / Case 6-SMD, No Lead
Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm)
Height - Seated (Max) 0.079" (2.00mm)
Report errors?

656C12503I2T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

656C12503I2T Payment Methods





















656C12503I2T Shipping Methods













If you have any question about 656C12503I2T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com