

65E1CL8.25 Information

Man Cate Heisener.com

Part Number65E1CL8.25ManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 65A 8.25KVAC CYL

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









65E1CL	Q 25 (Snacif	ications
	0.42	JUCCII	ications

Manufacturer Part Number65EICL8.25ManufacturerLittelfuse Inc.CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating65AVoltage Rating - AC8250V (8.25kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension16.130" L x 3.000" W x 4.310" H (409.70mm x 76.20mm x 109.47mm)Report errors?			
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating65AVoltage Rating - AC8250V (8.25kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension16.130" L x 3.000" W x 4.310" H (409.70mm x 76.20mm x 109.47mm)	Manufacturer Part Number	65E1CL8.25	
Blectrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? Fuse Type Cartridge Current Rating 65A Voltage Rating - AC 8250V (8.25kV) Voltage Rating - DC Response Time - Applications Transformer Protection Features Indicating Class E Approvals Operating Temperature Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Specialty Fuses Clarminal (Bolt) Size / Dimension Electrical, Specialty Fuses POWR-GARD? Cartringle Blade Terminal (Bolt) Size / Dimension Class Indicating Size / Dimension Electrical, Specialty Fuses Size / Dimension Cartridge Car	Manufacturer	Littelfuse Inc.	
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating65AVoltage Rating - AC8250V (8.25kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension16.130" L x 3.000" W x 4.310" H (409.70mm x 76.20mm x 109.47mm)	Category	Circuit Protection	
SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating65AVoltage Rating - AC8250V (8.25kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension16.130" L x 3.000" W x 4.310" H (409.70mm x 76.20mm x 109.47mm)		Electrical, Specialty Fuses	
Fuse Type Cartridge Current Rating 65A Voltage Rating - AC 8250V (8.25kV) Voltage Rating - DC - Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 16.130" L x 3.000" W x 4.310" H (409.70mm x 76.20mm x 109.47mm)	Package	Cylindrical, Blade Terminal (Bolt)	
Current Rating 65A Voltage Rating - AC 8250V (8.25kV) Voltage Rating - DC - Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 16.130" L x 3.000" W x 4.310" H (409.70mm x 76.20mm x 109.47mm)	Series	POWR-GARD?	
Voltage Rating - AC Voltage Rating - DC Response Time Applications Transformer Protection Indicating Class E Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 8250V (8.25kV)	Fuse Type	Cartridge	
Voltage Rating - DC Response Time Applications Transformer Protection Features Indicating Class E Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Indicating Cupacity Fransformer Protection Fransformer Protection	Current Rating	65A	
Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 16.130" L x 3.000" W x 4.310" H (409.70mm x 76.20mm x 109.47mm)	Voltage Rating - AC	8250V (8.25kV)	
Applications Features Indicating Class E Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Transformer Protection Indicating E Bolt Mount Class E Approvals - Cylindrical, Blade Terminal (Bolt) I 6.130" L x 3.000" W x 4.310" H (409.70mm x 76.20mm x 109.47mm)	Voltage Rating - DC	-	
Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 16.130" L x 3.000" W x 4.310" H (409.70mm x 76.20mm x 109.47mm)	Response Time	-	
Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 16.130" L x 3.000" W x 4.310" H (409.70mm x 76.20mm x 109.47mm)	Applications	Transformer Protection	
Approvals Operating Temperature Breaking Capacity @ Rated Voltage Bolt Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 16.130" L x 3.000" W x 4.310" H (409.70mm x 76.20mm x 109.47mm)	Features	Indicating	
Operating Temperature Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 16.130" L x 3.000" W x 4.310" H (409.70mm x 76.20mm x 109.47mm)	Class	E	
Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 16.130" L x 3.000" W x 4.310" H (409.70mm x 76.20mm x 109.47mm)	Approvals	-	
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 16.130" L x 3.000" W x 4.310" H (409.70mm x 76.20mm x 109.47mm)	Operating Temperature	-	
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 16.130" L x 3.000" W x 4.310" H (409.70mm x 76.20mm x 109.47mm)	Breaking Capacity @ Rated Voltage	80kA	
Size / Dimension 16.130" L x 3.000" W x 4.310" H (409.70mm x 76.20mm x 109.47mm)	Mounting Type	Bolt Mount	
·	Package / Case	Cylindrical, Blade Terminal (Bolt)	
Report errors?	Size / Dimension	16.130" L x 3.000" W x 4.310" H (409.70mm x 76.20mm x 109.47mm)	
		Report errors?	

65E1CL8.25 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

65E1CL8.25 Payment Methods



















65E1CL8.25 Shipping Methods













If you have any question about 65E1CL8.25, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com