



65SPB015A Information

Nyw hersener.com

For Reference Only

Part Number 65SPB015A

Manufacturer SMC Diode Solutions

Category Discrete Semiconductor Products

Diodes - Rectifiers - Single

Description DIODE SCHOTTKY 15V 60A SPD-2A

Package SPD-2A

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









65SPB015A Specifications

Manufacturer Part Number65SPB015AManufacturerSMC Diode SolutionsCategoryDiscrete Semiconductor ProductsPackageSPD-2ASeries-Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)15VCurrent - Average Rectified (Io)60AVoltage - Forward (Vf) (Max) @ If410mV @ 60ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr20mA @ 15VCapacitance @ Vr, F3600pF @ 5V, 1MHzMounting TypeSurface MountPackage / CaseSPD-2ASupplier Device PackageSPD-2AOperating Temperature - Junction-55°C ~ 125°CReport errors?	obbi Boibii Specifications	
Category Discrete Semiconductor Products Diodes - Rectifiers - Single Package SPD-2A Series - Diode Type Schottky Voltage - DC Reverse (Vr) (Max) 15V Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If 410mV @ 60A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Surface Mount Package / Case SPD-2A Supplier Device Package Operating Temperature - Junction Discrete Semiconductor Products Diodes - Rectifiers - Single SPD-2A SpD-2A Operating Temperature - Junction	Manufacturer Part Number	65SPB015A
Diodes - Rectifiers - Single Package SPD-2A Series - Diode Type Schottky Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Surface Mount Package / Case SpD-2A Supplier Device Package Operating Temperature - Junction Diodes - Rectifiers - Single SPD-2A SpD-2A SpD-2A SpD-2A Operating Temperature - Junction	Manufacturer	SMC Diode Solutions
PackageSPD-2ASeries-Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)15VCurrent - Average Rectified (Io)60AVoltage - Forward (Vf) (Max) @ If410mV @ 60ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr20mA @ 15VCapacitance @ Vr, F3600pF @ 5V, 1MHzMounting TypeSurface MountPackage / CaseSPD-2ASupplier Device PackageSPD-2AOperating Temperature - Junction-55°C ~ 125°C	Category	Discrete Semiconductor Products
Series - Diode Type Schottky Voltage - DC Reverse (Vr) (Max) 15V Current - Average Rectified (Io) 60A Voltage - Forward (Vf) (Max) @ If 410mV @ 60A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 20mA @ 15V Capacitance @ Vr, F 3600pF @ 5V, 1MHz Mounting Type Surface Mount Package / Case SPD-2A Supplier Device Package SPD-2A Operating Temperature - Junction -55°C ~ 125°C		Diodes - Rectifiers - Single
Diode Type Schottky Voltage - DC Reverse (Vr) (Max) 15V Current - Average Rectified (Io) 60A Voltage - Forward (Vf) (Max) @ If Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 20mA @ 15V Capacitance @ Vr, F 3600pF @ 5V, 1MHz Mounting Type Surface Mount Package / Case SPD-2A Supplier Device Package Operating Temperature - Junction Schottky 60A 410mV @ 60A 500 Fast Recovery =< 500ns, > 200mA (Io) - Supplier	Package	SPD-2A
Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If 410mV @ 60A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 20mA @ 15V Capacitance @ Vr, F 3600pF @ 5V, 1MHz Mounting Type Surface Mount Package / Case SPD-2A Supplier Device Package Operating Temperature - Junction 15V 410mV @ 60A Fast Recovery =< 500ns, > 200mA (Io) - Surface Mount Surface Mount Surface Mount SPD-2A Supplier Device Package SPD-2A Operating Temperature - Junction -55°C ~ 125°C	Series	-
Current - Average Rectified (Io) 60A Voltage - Forward (Vf) (Max) @ If 410mV @ 60A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 20mA @ 15V Capacitance @ Vr, F 3600pF @ 5V, 1MHz Mounting Type Surface Mount Package / Case SPD-2A Supplier Device Package SPD-2A Operating Temperature - Junction -55°C ~ 125°C	Diode Type	Schottky
Voltage - Forward (Vf) (Max) @ If Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Surface Mount Package / Case Supplier Device Package Operating Temperature - Junction 410mV @ 60A Fast Recovery =< 500ns, > 200mA (Io) - Suma @ 15V 20mA @ 15V 3600pF @ 5V, 1MHz Surface Mount SPD-2A -55°C ~ 125°C	Voltage - DC Reverse (Vr) (Max)	15V
Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Surface Mount Package / Case SPD-2A Supplier Device Package Operating Temperature - Junction Fast Recovery =< 500ns, > 200mA (Io) - 0 Supplier	Current - Average Rectified (Io)	60A
Reverse Recovery Time (trr) Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Surface Mount Package / Case Supplier Device Package Operating Temperature - Junction - 20mA @ 15V 3600pF @ 5V, 1MHz Surface Mount SPD-2A -55°C ~ 125°C	Voltage - Forward (Vf) (Max) @ If	410mV @ 60A
Current - Reverse Leakage @ Vr Capacitance @ Vr, F 3600pF @ 5V, 1MHz Mounting Type Surface Mount Package / Case SPD-2A Supplier Device Package Operating Temperature - Junction 20mA @ 15V 20mA @ 15V 3600pF @ 5V, 1MHz Surface Mount SPD-2A -55°C ~ 125°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F 3600pF @ 5V, 1MHz Mounting Type Surface Mount Package / Case SPD-2A Supplier Device Package SPD-2A Operating Temperature - Junction -55°C ~ 125°C	Reverse Recovery Time (trr)	-
Mounting Type Surface Mount Package / Case SPD-2A Supplier Device Package SPD-2A Operating Temperature - Junction -55°C ~ 125°C	Current - Reverse Leakage @ Vr	20mA @ 15V
Package / Case SPD-2A Supplier Device Package SPD-2A Operating Temperature - Junction -55°C ~ 125°C	Capacitance @ Vr, F	3600pF @ 5V, 1MHz
Supplier Device Package SPD-2A Operating Temperature - Junction -55°C ~ 125°C	Mounting Type	Surface Mount
Operating Temperature - Junction -55°C ~ 125°C	Package / Case	SPD-2A
	Supplier Device Package	SPD-2A
Report errors?	Operating Temperature - Junction	-55°C ~ 125°C
		Report errors?

65SPB015A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

65SPB015A Payment Methods



















65SPB015A Shipping Methods













If you have any question about 65SPB015A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com