

66527-014LF

uest a Quote

66527-014LF Information

Contract and they be a contract	Part Number	66527-014LF	
	Manufacturer	Amphenol FCI	
	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	
	Description	CONN RCPT 28POS T/H R/A GOLD	
	Package	-	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us	
,		Website: https://www.heisener.com	
		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



66527-014LF Specifications

Manufacturer Part Number66527-014LFManufacturerAmphenol FCICategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesDubox?Connector TypeReceptacleConnector TypeReceptacleConnector TypeBoardStyleBoard BoardNumber of Positions LoadedAllNumber of Rows2Number of Rows0.100° (2.54mm)Mounting TypeThrough Hole, Right AngleNumber of RowsSolderFastening TypeSolderFortact Finish - MatingGoldContact Finish - MatingGoldStation ColorBlackInsulation ColorBlackInsulation ColorC.240° (6.10mm)Contact Length - PostO.115° (2.92mm)Contact Length - PostO.115° (2.92mm)Contact Length - PostGiffe Life forContact Length - PostC.240° (6.10mm)Contact Length - PostContact Finish ColorContact Le			
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesDubox?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions28Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.240" (6.10mm)Contact Length - Post0.115" (2.92mm)	Manufacturer Part Number	66527-014LF	
Package-SeriesDubox?Connector TypeReceptacleContact TypeReceptacleStyleBoard to BoardNumber of Positions28Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeDidore. StyleFerninationSolderFastening TypeOldore. StyleContact Finish - MatingGoldForture TimistionGoldFastening TypeBoard to SolderFinish - MatingJoin (0.76µm)Forture TimistionSolderFastening TypeBoardInsulation ColorBlackInsulation Height0.240" (6.10mm)Contact Funsh Thickness - Mating0.15" (2.92mm)	Manufacturer	Amphenol FCI	
Package-SeriesDubox?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions28Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeOntor (2.54mm)Youngh Hole, Right AngleTerminationSolderFastening TypeOldon (2.54mm)Contact Finish - MatingOldon (2.54mm)Contact Finish - MatingSolderInsulation ColorJojin (0.76µm)Insulation Finish - MatingOldon (2.54mm)Insulation Height0.240" (6.10mm)Insulation Height0.240" (6.10mm)	Category	Connectors, Interconnects	
SeriesDubox?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions28Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Right AngleFastening TypeSolderContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBackInsulation Height0.240" (6.10mm)Contact Length - Post0.115" (2.92mm)		Rectangular Connectors - Headers, Receptacles, Female Sockets	
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions28Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.240" (6.10mm)Contact Length - Post0.115" (2.92mm)	Package	-	
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions28Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting Type0.100" (2.54mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish - MatingBackInsulation ColorBlackInsulation Height0.240" (6.10mm)Contact Length - Post0.115" (2.92mm)	Series	Dubox?	
StyleBoard to BoardStyleBoard to BoardNumber of Positions28Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.240" (6.10mm)Contact Length - Post0.115" (2.92mm)	Connector Type	Receptacle	
Number of Positions28Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Right AngleMounting TypeSolderTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.240" (6.10mm)Contact Length - Post0.115" (2.92mm)	Contact Type	Female Socket	
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating3µin (0.76µm)Insulation ColorBlackInsulation Height0.240" (6.10mm)Contact Length - Post0.115" (2.92mm)	Style	Board to Board	
Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting Type0.100" (2.54mm)TerminationSolderFastening TypeSolderContact Finish - MatingGoldContact Finish - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.240" (6.10mm)Contact Length - Post0.115" (2.92mm)	Number of Positions	28	
Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.240" (6.10mm)Contact Length - Post0.115" (2.92mm)	Number of Positions Loaded	All	
Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.240" (6.10mm)Contact Length - Post0.115" (2.92mm)	Pitch - Mating	0.100" (2.54mm)	
Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.240" (6.10mm)Contact Length - Post0.115" (2.92mm)	Number of Rows	2	
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.240" (6.10mm)Contact Length - Post0.115" (2.92mm)	Row Spacing - Mating	0.100" (2.54mm)	
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.240" (6.10mm)Contact Length - Post0.115" (2.92mm)	Mounting Type	Through Hole, Right Angle	
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.240" (6.10mm)Contact Length - Post0.115" (2.92mm)	Termination	Solder	
Contact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.240" (6.10mm)Contact Length - Post0.115" (2.92mm)	Fastening Type	Push-Pull	
Insulation ColorBlackInsulation Height0.240" (6.10mm)Contact Length - Post0.115" (2.92mm)	Contact Finish - Mating	Gold	
Insulation Height0.240" (6.10mm)Contact Length - Post0.115" (2.92mm)	Contact Finish Thickness - Mating	30µin (0.76µm)	
Contact Length - Post 0.115" (2.92mm)	Insulation Color	Black	
• • • • • • • • • • • • • • • • • • •	Insulation Height	0.240" (6.10mm)	
Operating Temperature (5°C 125°C	Contact Length - Post	0.115" (2.92mm)	
operating remperature -os C ~ 125 C	Operating Temperature	-65°C ~ 125°C	
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0	

Contact Finish - Post	Tin	
Mated Stacking Heights	-	
Ingress Protection	-	
Features	-	
		Report errors?

66527-014LF Guarantees




Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.





If you have any question about 66527-014LF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com