

672D477H025DS5J

672D477H025DS5J Information

Containance canteries		672D477H025DS5J Vishay Sprague Capacitors Aluminum Electrolytic Capacitors CAP ALUM 470UF 25V RADIAL Radial, Can For the pricing/inventory/lead time, please contact	
For Reference Only	For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



672D477H025DS5J Specifications

Manufacturer Part Number672D477H025DS5JManufacturerVishay SpragueCategoryCapacitorsPackageAluninum Electrolytic CapacitorsPackageRadial, CanSeries672DCapacitance470µFTolerance-Voltage - Rated25VESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipbe Current - Low Frequency-Impedance-Lad Spacing0.197" (5.00mm)Size / Dimension0.197" (5.00mm)Mauting Type-	_	
CategoryCapacitorsPackageRadial, CanSeries672DCapacitance470µFTolerance-Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lad Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.791" (45.50mm)Surface Mount Land Size-	Manufacturer Part Number	672D477H025DS5J
Aluminum Electrolytic CapacitorsPackageRadial, CanSeries672DCapacitance470µFTolerance-Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)-Surface Mount Land Size-	Manufacturer	Vishay Sprague
PackageRadial, CanSeries672DCapacitance470µFTolerance25VVoltage - Rated25VESR (Equivalent Series Resistance)-Derating Temperature-Operating Temperature60°C - 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Ingedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.791" (45.50mm)Surface Mount Land Size-Surface Mount Land Size- <td>Category</td> <td>Capacitors</td>	Category	Capacitors
Series672DCapacitance470μFTolerance-Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance-Liad Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)-Surface Mount Land Size-		Aluminum Electrolytic Capacitors
Capacitance470μFTolerance-Voltage - Rated25VESR (Equivalent Senisstance)-Lifetime @ TempOperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Inpedance-Inpedance0197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)-Surface Mount Land Size-	Package	Radial, Can
Tolerance-Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max).791" (45.50mm)Surface Mount Land Size-	Series	672D
Voltage - Rated25VVoltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)-Surface Mount Land Size-	Capacitance	470µF
ESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Icad Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)-Surface Mount Land Size-	Tolerance	-
Lifetime @ TempOperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)-Surface Mount Land Size-	Voltage - Rated	25V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Icad Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.791" (45.50mm)Surface Mount Land Size-	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.791" (45.50mm)Surface Mount Land Size-	Lifetime @ Temp.	-
ApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.791" (45.50mm)Surface Mount Land Size-	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.791" (45.50mm)Surface Mount Land Size-	Polarization	Polar
Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.791" (45.50mm)Surface Mount Land Size-	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.791" (45.50mm)Surface Mount Land Size-	Ripple Current - Low Frequency	-
Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.791" (45.50mm)Surface Mount Land Size-	Ripple Current - High Frequency	-
Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.791" (45.50mm)Surface Mount Land Size-	Impedance	-
Height - Seated (Max) 1.791" (45.50mm) Surface Mount Land Size -	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size -	Size / Dimension	0.492" Dia (12.50mm)
	Height - Seated (Max)	1.791" (45.50mm)
Mounting Type Through Hole	Surface Mount Land Size	-
	Mounting Type	Through Hole
Package / Case Radial, Can	Package / Case	Radial, Can
Report err		Report errors?

672D477H025DS5J Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

672D477H025DS5J Payment Methods





If you have any question about 672D477H025DS5J, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com