



### 672D786H100DS5J Information

Ma Car Heisener.com

Part Number 672D786H100DS5J
Manufacturer Vishay Sprague
Category Capacitors

Aluminum Electrolytic Capacitors

**Description** CAP ALUM 78UF 100V RADIAL

Package Radial, Can

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 672D786H100DS5J Specifications

Manufacturer Part Number         672D786H100DS5J           Manufacturer         Vishay Sprague           Category         Capacitors           Package         Radial, Can           Series         672D           Capacitance         78μF           Tolerance         -           Voltage - Rated         100V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         -           Operating Temperature         -55°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.791" (45.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	1	
Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can           Series         672D           Capacitance         78µF           Tolerance         -           Voltage - Rated         100V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         -           Operating Temperature         -55°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.791" (45.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Manufacturer Part Number	672D786H100DS5J
PackageRadial, CanSeries672DCapacitance78μFTolerance-Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.791" (45.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer	Vishay Sprague
Package         Radial, Can           Series         672D           Capacitance         78μF           Tolerance         -           Voltage - Rated         100V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         -           Operating Temperature         -55°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.791" (45.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Category	Capacitors
Series         672D           Capacitance         78µF           Tolerance         -           Voltage - Rated         100V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         -           Operating Temperature         -55°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.791" (45.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		Aluminum Electrolytic Capacitors
Capacitance         78µF           Tolerance         -           Voltage - Rated         100V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         -           Operating Temperature         -55°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         0.197" (5.00mm)           Size / Dimension         0.492" Dia (12.50mm)           Height - Seated (Max)         1.791" (45.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can	Package	Radial, Can
Tolerance - 100V  ESR (Equivalent Series Resistance)	Series	672D
Voltage - Rated100VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.791" (45.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	78μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  Operating Temperature  -55°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  -Ripple Current - High Frequency  Impedance  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  -  Lead Spacing  Through Hole  Radial, Can	Tolerance	-
Lifetime @ Temp. Operating Temperature -55°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency -Ripple Current - High Frequency Impedance Lead Spacing O.197" (5.00mm) Size / Dimension O.492" Dia (12.50mm) Height - Seated (Max) Surface Mount Land Size  Mounting Type Through Hole Package / Case Radial, Can	Voltage - Rated	100V
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.791" (45.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency -  Ripple Current - High Frequency -  Impedance -  Lead Spacing 0.197" (5.00mm)  Size / Dimension 0.492" Dia (12.50mm)  Height - Seated (Max) 1.791" (45.50mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Lifetime @ Temp.	-
Applications General Purpose  Ripple Current - Low Frequency -  Ripple Current - High Frequency -  Impedance -  Lead Spacing 0.197" (5.00mm)  Size / Dimension 0.492" Dia (12.50mm)  Height - Seated (Max) 1.791" (45.50mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.791" (45.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.791" (45.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.791" (45.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.791" (45.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.492" Dia (12.50mm)  Height - Seated (Max) 1.791" (45.50mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	1.791" (45.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
•	Mounting Type	Through Hole
D ( 0	Package / Case	Radial, Can
Report errors?		Report errors?

#### 672D786H100DS5J Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 672D786H100DS5J Payment Methods



















## 672D786H100DS5J Shipping Methods













If you have any question about 672D786H100DS5J, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com