

67S102MCECA

Request a Quote

67S102MCECA Information

	Part Number	67S102MCECA
www.heisener.com	Manufacturer	AVX Corporation
	Category	Capacitors Ceramic Capacitors
	Description	CAP CER 1000PF 2KV Y5U RADIAL
	Package	Radial, Disc
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



67S102MCECA Specifications

CategoryCapacitorsPackageRadial, DiscPackageRadial, DiscSeries-Capacitance1000pFTolerance±20%Voltage - Rated2000V (2kV)Poperature CoefficientY5U (E)Operating Temperature-Ratings-ApplicationsGeneralPurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSiz / Dimension0.315" Dia (8.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.394" (10.00mm)	-	
Capacitors Capacitors Package Radial, Disc Series - Capacitance 1000pF Tolerance ±20% Voltage - Rated 2000V (2kV) Temperature Coefficient YSU (E) Operating Temperature - Pactage - Ratings - Applications GeneralPurpose Failure Rate - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing Size / 10.00mm)	Manufacturer Part Number	67S102MCECA
AckageCeranic CapacitorsPackageRadial, DiscSeries-Capacitance1000pFTolerance±20%Voltage - Rated2000V (2kV)Temperature CoefficientY5U (E)Operating Temperature-Pactangs-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.315" Dia (8.00mm)Height - Seated (Max)-Thickness (Max)-Lead SpacingSize / DinominLead StyleStraight	Manufacturer	AVX Corporation
PackageRadial, DiscSeries-Capacitance1000pFTolerance±20%Voltage - Rated2000V (2kV)Tomperature CoefficientY5U (E)Operating Temperature-40°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeNirough HoleSize / Dimension0.315" Dia (8.00mm)Height - Seated (Max)-Height - Seated (Max)-Height - Seated (Max)0.157" (4.00mm)Height - Seated (Max)0.394" (10.00mm)Lead SpacingStraight	Category	Capacitors
Series-Capacitance1000pFTolerance±20%Voltage - Rated2000V (2kV)Temperature CoefficientY5U (E)Operating Temperature-40°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.157" (4.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.394" (10.00mm)Lead StyleStraight		Ceramic Capacitors
Capacitance1000pFTolerance±20%Voltage - Rated2000V (2kV)Temperature CoefficientV5U (E)Operating Temperature-40°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Nounting TypeNouting TypePackage / CaseRatial, DiscSize / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.157" (4.00mm)Thickness (Max)0.394" (10.00mm)Lead SpacingStraight	Package	Radial, Disc
Tolerance±20%Voltage - Rated2000V (2kV)Temperature CoefficientY5U (E)Operating Temperature-40°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.315" Dia (8.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.394" (10.00mm)Lead StyleStriaght	Series	-
Voltage - Rated2000V (2kV)Temperature CoefficientY5U (E)Operating Temperature-40°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.315" Dia (8.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.394" (10.00mm)Lead StyleStraight	Capacitance	1000pF
Temperature CoefficientY5U (E)Operating Temperature-40°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.315" Dia (8.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.394" (10.00mm)Lead StyleStraight	Tolerance	±20%
Operating Temperature-40°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.315" Dia (8.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.394" (10.00mm)Lead StyleStraight	Voltage - Rated	2000V (2kV)
Features-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.157" (4.00mm)Thickness (Max)-Lead Spacing0.394" (10.00mm)Lead StyleStraight	Temperature Coefficient	Y5U (E)
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.157" (4.00mm)Thickness (Max)-Lead Spacing0.394" (10.00mm)Lead StyleStraight	Operating Temperature	-40°C ~ 125°C
ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.157" (4.00mm)Thickness (Max)-Lead Spacing0.394" (10.00mm)Lead StyleStraight	Features	-
Failure Rate-Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.157" (4.00mm)Thickness (Max)-Lead Spacing0.394" (10.00mm)Lead StyleStraight	Ratings	-
Mounting TypeThrough HolePackage / CaseRadial, DiscSize / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.157" (4.00mm)Thickness (Max)-Lead Spacing0.394" (10.00mm)Lead StyleStraight	Applications	General Purpose
Package / CaseRadial, DiscSize / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.157" (4.00mm)Thickness (Max)-Lead Spacing0.394" (10.00mm)Lead StyleStraight	Failure Rate	-
Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.157" (4.00mm) Thickness (Max) - Lead Spacing 0.394" (10.00mm) Lead Style Straight	Mounting Type	Through Hole
Height - Seated (Max)0.157" (4.00mm)Thickness (Max)-Lead Spacing0.394" (10.00mm)Lead StyleStraight	Package / Case	Radial, Disc
Thickness (Max)-Lead Spacing0.394" (10.00mm)Lead StyleStraight	Size / Dimension	0.315" Dia (8.00mm)
Lead Spacing0.394" (10.00mm)Lead StyleStraight	Height - Seated (Max)	0.157" (4.00mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.394" (10.00mm)
Report errors?	Lead Style	Straight
		Report errors?

67S102MCECA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

67S102MCECA Payment Methods



67S102MCECA Shipping Methods



If you have any question about 67S102MCECA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com