

68046-249LF Information

Heisener.com

For Reference Only

Part Number 68046-249LF **Manufacturer** Amphenol FCI

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description CONN RCPT 98POS .100" DBL SMD

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









68046-249LF Specifications

Manufacturer Part Number Manufacturer Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package Series Dubox? Connector Type Receptacle Contact Type Female Socket Style Board to Board Number of Positions 98 Number of Positions Loaded Pitch - Mating Number of Rows 2 Row Spacing - Mating Mounting Type Surface Mount Fastening Type Push-Pull Contact Finish - Mating Gold or Gold, GXT?		
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package Series Dubox? Connector Type Receptacle Contact Type Female Socket Style Board to Board Number of Positions 98 Number of Positions Loaded Pitch - Mating Number of Rows 2 Row Spacing - Mating Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull	Manufacturer Part Number	68046-249LF
Rectangular Connectors - Headers, Receptacles, Female Sockets Package Series Dubox? Connector Type Receptacle Contact Type Female Socket Style Board to Board Number of Positions 98 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull	Manufacturer	Amphenol FCI
Package - Series Dubox? Connector Type Receptacle Contact Type Female Socket Style Board to Board Number of Positions 98 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull	Category	Connectors, Interconnects
Series Dubox? Connector Type Receptacle Contact Type Female Socket Style Board to Board Number of Positions 98 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector Type Receptacle Contact Type Female Socket Style Board to Board Number of Positions 98 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull	Package	-
Contact Type Female Socket Style Board to Board Number of Positions 98 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull	Series	Dubox?
Style Board to Board Number of Positions 98 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull	Connector Type	Receptacle
Number of Positions98Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-Pull	Contact Type	Female Socket
Number of Positions Loaded Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Surface Mount Termination Fastening Type Push-Pull	Style	Board to Board
Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-Pull	Number of Positions	98
Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull	Number of Positions Loaded	All
Row Spacing - Mating 0.100" (2.54mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull	Pitch - Mating	0.100" (2.54mm)
Mounting TypeSurface MountTerminationSolderFastening TypePush-Pull	Number of Rows	2
Termination Solder Fastening Type Push-Pull	Row Spacing - Mating	0.100" (2.54mm)
Fastening Type Push-Pull	Mounting Type	Surface Mount
	Termination	Solder
Contact Finish - Mating Gold or Gold GXT?	Fastening Type	Push-Pull
Contact I mish Triumg	Contact Finish - Mating	Gold or Gold, GXT?
Contact Finish Thickness - Mating 15µin (0.38µm)	Contact Finish Thickness - Mating	15μin (0.38μm)
Insulation Color Black	Insulation Color	Black
Insulation Height 0.310" (7.87mm)	Insulation Height	0.310" (7.87mm)
Contact Length - Post -	Contact Length - Post	-
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Operating Temperature	-65°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

68046-249LF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

68046-249LF Payment Methods



















68046-249LF Shipping Methods













If you have any question about 68046-249LF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com