

68046-325LF

uest a Quote

68046-325LF Information

Constitution and they	Part Number	68046-325LF	
	Manufacturer	Amphenol FCI	
	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	
	Description	CONN RCPT 50POS .100" DBL SMD	
	Package	-	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us	
		Website: https://www.heisener.com	
		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



68046-325LF Specifications

Manufacturer Part Number 68046-325LF Manufacturer Amphenol FCI Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Scries Dubox? Connector Type Receptacles, Female Sockets Contact Type Receptacle Contact Type Receptacle Style Board to Board Number of Positions Loaded All Number of Positions Loaded 0.100° (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100° (2.54mm) Mounting Type Surface Mount Yourde Kinshn- Mating Solder Contact Finish - Mating Gold or Gold, GXT? Contact Finish - Mating Gold or Gold, GXT? Contact Finish Thickness - Mating Jujin (0.76µm) Insulation Color Black Insulation Height 0.310° (7.87mm) Contact Length - Post - Marcial Elimenschilture Ration -			
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesDubox?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions50Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - MatingSolderMounting TypeSurface MountFreminationSolderFastening TypeGold or Gold, GXT?Contact Finish - MatingJouin (0.76µm)Insulation ColorBlackInsulation FlexitySolir (7.87mm)Contact Length - Post-Operating Temperature-Solor Cate Solution SolutionSolir (7.87mm)	Manufacturer Part Number	68046-325LF	
Package-SeriesDubox?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions50Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - MatingSolderTerminationSolderFastening TypeSurface MountContact Finish - MatingGold or Gold, GXT?Contact Finish Thickness - MatingJujin (0.76µm)Contact Finish Thickness - MatingJujin (0.76µm)Contact Finish Thickness - MatingJujin (0.78µm)Contact Finish Thickness - MatingJujin (0.78µm)Contact Finish Thickness - MatingJujin (0.78µm)Contact Finish Thickness - MatingSolderInsulation Height0.310" (7.87µm)Contact Length - Post-Operating Temperature-65°C ~ 125°C	Manufacturer	Amphenol FCI	
Package-SeriesDubox?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions50Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountYerninationSolderFastening TypePush-PullContact Finish - MatingGold or Gold, GXT?Contact Finish Thickness - MatingJojun (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-Operating Temperature65°C ~ 125°C	Category	Connectors, Interconnects	
SeriesDubox?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions50Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountMounting TypeSurface MountContact Finish - MatingSolderContact Finish - MatingGold or Gold, GXT?Contact Finish Thickness - MatingBiackInsulation ColorBiackInsulation Height0.310" (7.87mm)Contact Length - Post-Operating Temperature65°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets	
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions50Number of Positions LoadedAllNumber of Positions Loaded0.100° (2.54mm)Number of Rows2Row Spacing - Mating0.100° (2.54mm)Mounting TypeSurface MountYourde Contact Finish - MatingSolderContact Finish - MatingSolderContact Finish - MatingGold or Gold, GXT?Sulation ColorBackInsulation Height0.310° (7.87mm)Contact Length - Post-Operating Temperature65°C ~ 125°C	Package	-	
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions50Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGold or Gold, GXT?Contact Finish Thickness - MatingBlackInsulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-Operating Temperature-65°C ~ 125°C	Series	Dubox?	
StyleBoard to BoardNumber of Positions50Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGold or Gold, GXT?Contact Finish Thickness - Mating3ujui (0.76µm)Insulation Height0.310" (7.87mm)Contact Length - Post-Operating Temperature65°C ~ 125°C	Connector Type	Receptacle	
Number of Positions 50 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type 0.100" (2.54mm) Termination Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold or Gold, GXT? Contact Finish Thickness - Mating Jouin (0.76µm) Insulation Color Black Insulation Height 0.310" (7.87mm) Ontact Length - Post - Operating Temperature -65°C ~ 125°C	Contact Type	Female Socket	
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGold or Gold, GXT?Contact Finish Thickness - MatingBlackInsulation ColorSloler"Insulation Height0.310" (7.87mm)Contact Length - Post-Operating Temperature65°C ~ 125°C	Style	Board to Board	
Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSurface MountFastening TypePush-PullContact Finish - MatingGold or Gold, GXT?Contact Finish Thickness - MatingBlackInsulation Color0.310" (7.87mm)Contact Length - Post-Operating Temperature65°C ~ 125°C	Number of Positions	50	
Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGold or Gold, GXT?Contact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-Operating Temperature-65°C ~ 125°C	Number of Positions Loaded	All	
Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGold or Gold, GXT?Contact Finish Thickness - Mating3µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-Operating Temperature-65°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)	
Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGold or Gold, GXT?Contact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-Operating Temperature65°C ~ 125°C	Number of Rows	2	
TerminationSolderFastening TypePush-PullContact Finish - MatingGold or Gold, GXT?Contact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-Operating Temperature-65°C ~ 125°C	Row Spacing - Mating	0.100" (2.54mm)	
Fastening TypePush-PullContact Finish - MatingGold or Gold, GXT?Contact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-Operating Temperature-65°C ~ 125°C	Mounting Type	Surface Mount	
Contact Finish - MatingGold or Gold, GXT?Contact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-Operating Temperature-65°C ~ 125°C	Termination	Solder	
Contact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-Operating Temperature-65°C ~ 125°C	Fastening Type	Push-Pull	
Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-Operating Temperature-65°C ~ 125°C	Contact Finish - Mating	Gold or Gold, GXT?	
Insulation Height0.310" (7.87mm)Contact Length - Post-Operating Temperature-65°C ~ 125°C	Contact Finish Thickness - Mating	30µin (0.76µm)	
Contact Length - Post-Operating Temperature-65°C ~ 125°C	Insulation Color	Black	
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Insulation Height	0.310" (7.87mm)	
	Contact Length - Post	-	
Material Elammability Pating LII 94 V 0	Operating Temperature	$-65^{\circ}C \sim 125^{\circ}C$	
Viaterial Franchia OL74 V-0	Material Flammability Rating	UL94 V-0	

Contact Finish - Post	Tin	
Mated Stacking Heights	-	
Ingress Protection	-	
Features	-	
		Report errors?

68046-325LF Guarantees




Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.





If you have any question about 68046-325LF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com