

68046-342LF

68046-342LF Information

Heisener.com	Part Number Manufacturer Category Description Package	68046-342LF Amphenol FCI Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets CONN RCPT 84POS .100" DBL SMD	
For Reference Only		For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



68046-342LF Specifications

Manufacturer Part Number68046-342L FManufacturerAmphenol FCICategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesDubox?Connector TypeReceptacleConnector TypeReceptacleConnector TypeSerieleStyleBoardNumber of Positions LoadedAlNumber of Rows2Number of Rows0.100° (2.54mm)Number of Rows0.100° (2.54mm)Mounting TypeSuface MountMounting TypeSuface MountFrankation MathingGold or Gold, GXT?Contact Finish - MatingJuin (0.76µm)Insulation ColorBlackInsulation ColorSuface ColorInsulation ForstU.310° (7.87mm)Contact Length - Post-Cortact Length - Post-Contact Length - Post- <th></th> <th></th>			
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesDubox?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions84Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypeGold or Gold, GXT?Contact Finish - Mating0.00 (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-Operating Temperature-5°C ~ 125°C	Manufacturer Part Number	68046-342LF	
Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series Dubox? Connector Type Receptacle Contact Type Board to Board Style Board to Board Number of Positions 84 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold or Gold, GXT? Contact Finish Thickness - Mating 3ujui (0.76µm) Insulation Color Black Insulation Height 0.310" (7.87mm) Contact Length - Post - Operating Temperature -65°C ~ 125°C	Manufacturer	Amphenol FCI	
Package-SeriesDubox?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions84Number of Positions LoadedAllNumber of Rows0.100° (2.54mm)Number of Rows0.100° (2.54mm)Nouring Type0.100° (2.54mm)Mounting TypeSockerFarening TypeSockerFastening TypeSockerContact Finish - MatingGold or Gold, GXT?Fontact Finish Thickness - MatingJoin (0.76mm)Insulation ColorBlackInsulation Height0.301° (7.87mm)Contact Finish PostiSockerSocher Lingth - PostSockerSocher Lingth - PostSockerSocker Lingth - PostSockerSocher Lingth - PostSockerSocker Lingth - PostSocker </td <td>Category</td> <td colspan="2">Connectors, Interconnects</td>	Category	Connectors, Interconnects	
SeriesDubox?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions84Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows2Row Spacing - Mating0.100° (2.54mm)Mounting TypeSolderFerminationSolderFastening TypeSolderContact Finish - MatingGold or Gold, GXT?Contact Finish - MatingJini (0.76µm)Insulation ColorBlackInsulation Height0.310° (7.87mm)Contact Length - Post-Contact Length - Post<		Rectangular Connectors - Headers, Receptacles, Female Sockets	
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions84Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSolderTerminationSolderFastening TypeSolderContact Finish - MatingSolderInsulation ColorBlackInsulation Height0.30" (7.87mm)Contact Length - Post-Solder Catter-Solder Catter-Solder-Solde	Package	-	
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions84Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGold or Gold, GXT?Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-Sore ~ 125°C-	Series	Dubox?	
StyleBoard to BoardNumber of Positions84Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGold or Gold, GXT?Contact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-Operating Temperature-65°C ~ 125°C	Connector Type	Receptacle	
Number of Positions84Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows2Row Spacing - Mating0.100° (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGold or Gold, GXT?Insulation ColorBlackInsulation Height0.310° (7.87mm)Contact Length - Post-Contart Fungerature65°C ~ 125°C	Contact Type	Female Socket	
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSulface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGold or Gold, GXT?Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-Operating Temperature65°C ~ 125°C	Style	Board to Board	
Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGold or Gold, GXT?Contact Finish Thickness - MatingBlackInsulation ColorJ.310" (7.87mm)Contact Length - Post-50°C ~ 125°C	Number of Positions	84	
Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGold or Gold, GXT?Contact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-Operating Temperature-65°C ~ 125°C	Number of Positions Loaded	All	
Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGold or Gold, GXT?Contact Finish Thickness - MatingJuin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-Operating Temperature-65°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)	
Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGold or Gold, GXT?Contact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-Operating Temperature65°C ~ 125°C	Number of Rows	2	
TerminationSolderFastening TypePush-PullContact Finish - MatingGold or Gold, GXT?Contact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-Operating Temperature-65°C ~ 125°C	Row Spacing - Mating	0.100" (2.54mm)	
Fastening TypePush-PullContact Finish - MatingGold or Gold, GXT?Contact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-Operating Temperature65°C ~ 125°C	Mounting Type	Surface Mount	
Contact Finish - MatingGold or Gold, GXT?Contact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-Operating Temperature-65°C ~ 125°C	Termination	Solder	
Contact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-Operating Temperature-65°C ~ 125°C	Fastening Type	Push-Pull	
Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-Operating Temperature-65°C ~ 125°C	Contact Finish - Mating	Gold or Gold, GXT?	
Insulation Height0.310" (7.87mm)Contact Length - Post-Operating Temperature-65°C ~ 125°C	Contact Finish Thickness - Mating	30µin (0.76µm)	
Contact Length - Post-Operating Temperature-65°C ~ 125°C	Insulation Color	Black	
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Insulation Height	0.310" (7.87mm)	
	Contact Length - Post	-	
Material Elementation LIL 04 V.0	Operating Temperature	-65°C ~ 125°C	
Material Flammability Rating 0L94 V-0	Material Flammability Rating	UL94 V-0	

Contact Finish - Post	Tin	
Mated Stacking Heights	-	
Ingress Protection	-	
Features	-	
		Report errors?

68046-342LF Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.





If you have any question about 68046-342LF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com