

68513W3103L461

68513W3103L461 Information

| Heisener.com | Part Number Manufacturer Category Description Package | 68513W3103L461 NorComp Inc. Connectors, Interconnects D-Sub Connectors CONN D-SUB PLUG 13POS R/A SOLDER - For the pricing/inventory/lead time, please contact | |
|--------------------|---|---|-----------------|
| For Reference Only | | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



68513W3103L461 Specifications

| ManufacturerNorComp Inc.CategoryConnectors, Interconnects D-Sub ConnectorsPackage-Series685Connector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions13 (10 + 3 Coax)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeBoard Edge, Through Hole, Right AngleHange FeatureHousing/Shell (4-40)Flange FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Nickel PlatedContact Finish ThicknessGoldContact Finish ThicknessFlashIngress Protection- | | |
|---|------------------------------|--|
| CategoryConnectors, Interconnects D-Sub ConnectorsPackage-Series685Connector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions13 (10 + 3 Coax)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeBoard Edge, Through Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Nickel PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | Manufacturer Part Number | 68513W3103L461 |
| D-Sub ConnectorsPackage-Series685Connector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions13 (10 + 3 Coax)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeCoax and SignalMounting TypeBoard Edge, Through Hole, Right AngleFlange FeatureHousing/Shell (4-40)FreminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Nickel PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | Manufacturer | NorComp Inc. |
| Package-Series685Connector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions13 (10 + 3 Coax)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeCoax and SignalMounting TypeBoard Edge, Through Hole, Right AngleFlange FeatureHousing/Shell (4-40)FeaturesSolderShell Material, FinishSteel, Nickel PlatedContact Finish ThicknessGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | Category | Connectors, Interconnects |
| Series685Connector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions13 (10 + 3 Coax)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeCoax and SignalMounting TypeBoard Edge, Through Hole, Right AngleFlange FeatureHousing/Shell (4-40)FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Nickel PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | | D-Sub Connectors |
| Connector StyleD-Sub, ComboConnector TypePlug, Male PinsNumber of Positions13 (10 + 3 Coax)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeCoax and SignalMounting TypeBoard Edge, Through Hole, Right AngleFlange FeatureSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Nickel PlatedContact FinishGoldIngress Protection-Material Flammability RatingUL94 V-0 | Package | - |
| Connector TypePlug, Male PinsNumber of Positions13 (10 + 3 Coax)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeCoax and SignalMounting TypeBoard Edge, Through Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Nickel PlatedContact FinishGoldIngress Protection-Material Flammability RatingUL94 V-0 | Series | 685 |
| Number of Positions13 (10 + 3 Coax)Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeCoax and SignalMounting TypeBoard Edge, Through Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Nickel PlatedContact Finish ThicknessFlashIngress Protection-UL94 V-0UL94 V-0 | Connector Style | D-Sub, Combo |
| Number of Rows2Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeCoax and SignalMounting TypeBoard Edge, Through Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Nickel PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | Connector Type | Plug, Male Pins |
| Shell Size, Connector Layout3 (DB, B) - 13C3, 13W3Contact TypeCoax and SignalMounting TypeBoard Edge, Through Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Nickel PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | Number of Positions | 13 (10 + 3 Coax) |
| Contact TypeCoax and SignalMounting TypeBoard Edge, Through Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | Number of Rows | 2 |
| Mounting TypeBoard Edge, Through Hole, Right AngleFlange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | Shell Size, Connector Layout | 3 (DB, B) - 13C3, 13W3 |
| Flange FeatureHousing/Shell (4-40)TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | Contact Type | Coax and Signal |
| TerminationSolderFeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | Mounting Type | Board Edge, Through Hole, Right Angle |
| FeaturesBoard Lock, Grounding Indents, Mounting BracketsShell Material, FinishSteel, Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | Flange Feature | Housing/Shell (4-40) |
| Shell Material, FinishSteel, Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | Termination | Solder |
| Contact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | Features | Board Lock, Grounding Indents, Mounting Brackets |
| Contact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0 | Shell Material, Finish | Steel, Nickel Plated |
| Ingress Protection-Material Flammability RatingUL94 V-0 | Contact Finish | Gold |
| Material Flammability Rating UL94 V-0 | Contact Finish Thickness | Flash |
| | Ingress Protection | - |
| Report errors? | Material Flammability Rating | UL94 V-0 |
| | | Report errors? |

68513W3103L461 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

68513W3103L461 Payment Methods



68513W3103L461 Shipping Methods



If you have any question about 68513W3103L461, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com