

## 68622-609LF

## 68622-609LF Information

Heisener.com	Part Number Manufacturer Category Description Package	68622-609LF Amphenol FCI Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets CONN RCPT 18POS .100" DBL SMD	
For Reference Only		For the pricing/inventory/lead time, please contact us	
Tor reference only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## 68622-609LF Specifications

Manufacturer Part Number68622-609LFManufacturerAmphenol FCICategoryConnectors, InterconnectsPackage-SeriesDubox?Contact TypeReceptacles, Fenale SocketsOrnector TypeReceptaclesContact TypeBoard BoardSyleBoard BoardNumber of Positions18Number of Positions LoadedAllNumber of Rows2Rowspacing - Mating0.100° (2.54mm)Number of RowsSolderRowspacing - MatingSolderStrigting TypeSolderContact Finish - MatingGoldContact Finish - MatingGoldStrigting TypeSolderStrigting TypeSolderStrigting TypeSolderStrigting TypeSolderContact Finish - MatingGoldStrigting TypeSoldin CotopStrigting Type		
Category Connectors, Interconnects   Rectangular Connectors - Headers, Receptacles, Female Sockets   Package -   Series Dubox?   Connector Type Receptacle   Contact Type Receptacle   Style Board to Board   Number of Positions 18   Number of Positions Loaded All   Pitch - Mating 0.100" (2.54mm)   Number of Rows 2   Row Spacing - Mating 0.100" (2.54mm)   Mounting Type Surface Mount   Termination Solder   Fastening Type Gold   Contact Finish - Mating Gold   Contact Finish Thickness - Mating Jajún (0.76µm)   Insulation Color Black	Manufacturer Part Number	68622-609LF
AckageRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesDubox?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions18Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows2Row Spacing - Mating0.100° (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypeOldoContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310° (7.87mm)	Manufacturer	Amphenol FCI
Package-SeriesDubox?Conactor TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions18Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountFastening TypeSurface MountFastening TypeGoldContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.310" (7.87mm)	Category	Connectors, Interconnects
SeriesDubox?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions18Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountFastening TypeSolderFastening TypeGoldContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of PositionsI8Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - MatingO.100" (2.54mm)Mounting TypeSurface MountFareminationSolderFortant Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBiackInsulation HeightSolor (7.87mm)	Package	-
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions18Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountFartminationSolderFastening TypePush-PullContact Finish - MatingGoldIonator Finish - MatingBiackInsulation ColorBlackInsulation Height0.310" (7.87mm)	Series	Dubox?
StyleBoard to BoardNumber of Positions18Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows2Row Spacing - Mating0.100° (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.310° (7.87mm)	Connector Type	Receptacle
Number of Positions18Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.310" (7.87mm)	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)	Style	Board to Board
Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSurface MountFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJuin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)	Number of Positions	18
Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)	Number of Positions Loaded	All
Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)	Pitch - Mating	0.100" (2.54mm)
Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)	Row Spacing - Mating	0.100" (2.54mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)	Mounting Type	Surface Mount
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)	Termination	Solder
Contact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.310" (7.87mm)	Contact Finish - Mating	Gold
Insulation Height 0.310" (7.87mm)	Contact Finish Thickness - Mating	30µin (0.76µm)
	Insulation Color	Black
Contact Length - Post -	Insulation Height	0.310" (7.87mm)
	Contact Length - Post	-
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Operating Temperature	-65°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Ingress Protection -	Mated Stacking Heights	-
Features Board Lock	Ingress Protection	



If you have any question about 68622-609LF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com

68622-609LF Guarantees