

68622-622LF

68622-622LF Information

Heisener.com	Part Number Manufacturer Category Description Package	68622-622LF Amphenol FCI Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets CONN RCPT	
For Reference Only		For the pricing/inventory/lead time, please contact us	
·		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



68622-622LF Specifications

Manufacturer Part Number68622-622LFManufacturerAmphenol FCICategoryConnectors, InterconnectsPackage-Package-SeriesDubox?Contact TypeReceptacles, Female SocketsContact TypeFemale SocketStyleBoard to BoardNumber of Positions44Number of Positions Loaded1.00° (2.54mm)Number of Rows2Row Spacing - MatingSolderMuning TypeSolderStrient MatingSolderContact Finish - MatingSolderContact Finish - MatingSolderContact Finish - MatingSolderStrient MatingSolderStrient Finish - MatingSolderContact Finish - MatingSolderStrient Finish - MatingSolderContact Finish - MatingSolderContact Finish - MatingSolidor (7.5mm)Contact Finish - MatingSolidor (7.5mm)Solidor (1.5mm)Solidor (7.5mm)Contact Finish - MatingSolidor (7.5mm)Contact		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesDubox?Connector TypeReceptacleConnector TypeReceptacleConnector TypeBoard to BoardNumber of Positions44Number of Positions LoadedIn10° (2.54mm)Number of Rows2Row Spacing - Mating0.100° (2.54mm)Mounting TypeSurface MountYafee MountSolderTerminationSolderFastening TypeGoldContact Finish - MatingGoldContact Finish Thickness - MatingGulin (7.67mm)Insulation ColorBlackInsulation Height0.310° (7.87mm)Contact Length - Post-	Manufacturer Part Number	68622-622LF
PackageRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesDubox?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions44Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows2Row Spacing - Mating0.100° (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypeGoldContact Finish - MatingGoldContact Finish Thickness - MatingJoin (0.76µm)Insulation ColorBlackInsulation Height0.301° (7.87mm)Contact Length - Post-	Manufacturer	Amphenol FCI
Package-SeriesDubox?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions44Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSolderTerminationSolderFastening TypeGoldContact Finish - MatingGoldContact Finish - MatingJupin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-	Category	Connectors, Interconnects
SeriesDubox?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions44Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountFastening TypeSurface MountContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions44Number of Positions LoadedAllNumber of Rows0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-	Package	-
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions44Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldIonator Finish - MatingJuin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-	Series	Dubox?
StyleBoard to BoardNumber of Positions44Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows2Row Spacing - Mating0.100° (2.54mm)Mounting TypeSurface MountTerminationSurface MountFastening TypePosh-PullContact Finish - MatingGoldInsulation ColorJair (0.76µm)Insulation Height0.310° (7.87mm)Contact Length - Post-	Connector Type	Receptacle
Number of Positions44Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating3µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-	Style	Board to Board
Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting Type0.100" (2.54mm)TerminationSurface MountFastening TypeSolderFontact Finish - MatingOddContact Finish - MatingSoldin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-	Number of Positions	44
Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-	Number of Positions Loaded	All
Row Spacing - Mating0.100" (2.54mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation Height0.310" (7.87mm)Contact Length - Post-	Pitch - Mating	0.100" (2.54mm)
Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-	Row Spacing - Mating	0.100" (2.54mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-	Mounting Type	Surface Mount
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-	Termination	Solder
Contact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post-	Contact Finish - Mating	Gold
Insulation Height0.310" (7.87mm)Contact Length - Post-	Contact Finish Thickness - Mating	30µin (0.76µm)
Contact Length - Post -	Insulation Color	Black
-	Insulation Height	0.310" (7.87mm)
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Contact Length - Post	-
	Operating Temperature	-65°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Ingress Protection -	Mated Stacking Heights	-
Features Board Lock	Ingress Protection	



If you have any question about 68622-622LF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com

68622-622LF Guarantees