

6EX273K3

6EX273K3 Information

Heisener.com	Part Number Manufacturer Category Description Package	6EX273K3 Semtech Corporation Capacitors Ceramic Capacitors CAP CER 0.027UF 3KV X7R RADIAL Radial For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



6EX273K3 Specifications

Manufacturer Part Number GEX273K3 Manufacturer Semech Corporation Category Capacitors Package Radial Series - Capacitance 0.027µF Tolerance 10% Yoltage - Rated 0.000 (3kV) Yoltage - Rated 3000 (3kV) Yoltage - Rated 50% < 125%C Yoltage - Rated Series Yoltage - Rated Series <		
CapacitorsPackageRadialSeries-Capacitance0.027µFTolerance±10%Voltage - Rated3000V (3kV)Tomperature Coefficient×7ROperating Temperature-55°C ~ 125°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.800°L x 0.375° W (20.40mm x 9.53mm)Hight - Seated (Max)-Hight - Seated (Max)-Lead Spacing1.0°('1.78mm)Lead StyleStraight	Manufacturer Part Number	6EX273K3
Indext and the section of the secti	Manufacturer	Semtech Corporation
PackageRadialSeries-Capacitance0.027μFTolerance±10%Voltage Rated3000V (3kV)Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Nounting TypeBadialPackage / CaseRadialSize / Dimension0.80° L x 0.375° W (20.40mm x 9.53mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.70° (17.78mm)Lead StyleStraight	Category	Capacitors
Series - Series 0.027μF Capacitance ±10% Tolerance ±10% Voltage - Rated 3000 V (3kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Noutring Type Through Hole Size / Dimension 0.800" L x 0.375" W (20.40mm x 9.53mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.700" (17.78mm) Lead Style Straight		Ceramic Capacitors
Capacitance0.027μFTolerance±10%Voltage - Rated3000V (3kV)Temperature CoefficientX7ROperating Temperature-5°C ~ 125°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HoleSize / Dimension0.800° L x 0.375° W (20.40mm x 9.53mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.700° (17.78mm)Lead StyleStraight	Package	Radial
Tolerance±10%Voltage - Rated3000V (3kV)Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.800° L x 0.375° W (20.40mm x 9.53mm)Height - Seated (Max)0.874° (22.20mm)Thickness (Max)-Lead Spacing0.700° (17.78mm)Lead StyleStraight	Series	-
Voltage - Rated3000V (3kV)Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.800° L x 0.375° W (20.40mm x 9.53mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.700° (17.78mm)Lead StyleStraight	Capacitance	0.027µF
Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HoleStack p / CaseRadialSize / Dimension0.800" L x 0.375" W (20.40mm x 9.53mm)Hight - Seated (Max)-Thickness (Max)-Lead Spacing0.700" (17.78mm)Lead StyleStraight	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.800" L x 0.375" W (20.40mm x 9.53mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.700" (17.78mm)Kead StyleStraight	Voltage - Rated	3000V (3kV)
FeaturesHigh VoltageRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.800" L x 0.375" W (20.40mm x 9.53mm)Height - Seated (Max)0.874" (22.20mm)Thickness (Max)-Lead Spacing0.700" (17.78mm)Lead StyleStraight	Temperature Coefficient	X7R
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.800" L x 0.375" W (20.40mm x 9.53mm)Height - Seated (Max)0.874" (22.20mm)Thickness (Max)-Lead Spacing0.700" (17.78mm)Lead StyleStrieght	Operating Temperature	-55°C ~ 125°C
ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.800" L x 0.375" W (20.40mm x 9.53mm)Height - Seated (Max)0.874" (22.20mm)Thickness (Max)-Lead Spacing0.700" (17.78mm)Lead StyleStraight	Features	High Voltage
Failure Rate-Failure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.800" L x 0.375" W (20.40mm x 9.53mm)Height - Seated (Max)0.874" (22.20mm)Thickness (Max)-Lead Spacing0.700" (17.78mm)Lead StyleStraight	Ratings	-
Mounting Type Through Hole Package / Case Radial Size / Dimension 0.800" L x 0.375" W (20.40mm x 9.53mm) Height - Seated (Max) 0.874" (22.20mm) Thickness (Max) - Lead Spacing 0.700" (17.78mm) Lead Style Straight	Applications	General Purpose
Package / CaseRadialSize / Dimension0.800" L x 0.375" W (20.40mm x 9.53mm)Height - Seated (Max)0.874" (22.20mm)Thickness (Max)-Lead Spacing0.700" (17.78mm)Lead StyleStraight	Failure Rate	-
Size / Dimension 0.800" L x 0.375" W (20.40mm x 9.53mm) Height - Seated (Max) 0.874" (22.20mm) Thickness (Max) - Lead Spacing 0.700" (17.78mm) Lead Style Straight	Mounting Type	Through Hole
Height - Seated (Max)0.874" (22.20mm)Thickness (Max)-Lead Spacing0.700" (17.78mm)Lead StyleStraight	Package / Case	Radial
Thickness (Max) - Lead Spacing 0.700" (17.78mm) Lead Style Straight	Size / Dimension	0.800" L x 0.375" W (20.40mm x 9.53mm)
Lead Spacing0.700" (17.78mm)Lead StyleStraight	Height - Seated (Max)	0.874" (22.20mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.700" (17.78mm)
Report errors?	Lead Style	Straight
		Report errors?

6EX273K3 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

6EX273K3 Payment Methods WIRE transfer PayPal Methods 6EX273K3 Shipping Methods



If you have any question about 6EX273K3, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com