

6N139S Information



For Reference Only

Part Number 6N139S Manufacturer Lite-On Inc. Category Isolators

Optoisolators - Transistor, Photovoltaic Output

Description OPTOISO 5KV DARL W/BASE 8SMD

Package 8-SMD, Gull Wing

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









6N139S Specifications

Manufacturer Part Number6N139SManufacturerLite-On Inc.CategoryIsolatorsOptoisolators - Transistor, Photovoltaic OutputPackage8-SMD, Gull WingSeries-Number of Channels1Voltage - Isolation5000VrmsCurrent Transfer Ratio (Min)500% @ 1.6mACurrent Transfer Ratio (Max)2600% @ 1.6mATurn On / Turn Off Time (Typ)100ns, 2μs
Category Isolators Optoisolators - Transistor, Photovoltaic Output Package 8-SMD, Gull Wing Series - Number of Channels 1 Voltage - Isolation Current Transfer Ratio (Min) Current Transfer Ratio (Max) Isolators Optoisolators - Transistor, Photovoltaic Output 8-SMD, Gull Wing - 0 1 1 2000 Vrms 2000 © 1.6mA
Optoisolators - Transistor, Photovoltaic Output Package 8-SMD, Gull Wing Series - Number of Channels 1 Voltage - Isolation 5000Vrms Current Transfer Ratio (Min) 500% @ 1.6mA Current Transfer Ratio (Max) 2600% @ 1.6mA
Package 8-SMD, Gull Wing Series - Number of Channels 1 Voltage - Isolation 5000Vrms Current Transfer Ratio (Min) 500% @ 1.6mA Current Transfer Ratio (Max) 2600% @ 1.6mA
Series - Number of Channels 1 Voltage - Isolation 5000Vrms Current Transfer Ratio (Min) 500% @ 1.6mA Current Transfer Ratio (Max) 2600% @ 1.6mA
Number of Channels1Voltage - Isolation5000VrmsCurrent Transfer Ratio (Min)500% @ 1.6mACurrent Transfer Ratio (Max)2600% @ 1.6mA
Voltage - Isolation 5000Vrms Current Transfer Ratio (Min) 500% @ 1.6mA Current Transfer Ratio (Max) 2600% @ 1.6mA
Current Transfer Ratio (Min) 500% @ 1.6mA Current Transfer Ratio (Max) 2600% @ 1.6mA
Current Transfer Ratio (Max) 2600% @ 1.6mA
Turn On / Turn Off Time (Typ) 100ns, 2µs
, · · · · · · · · · · · · · · · · · · ·
Rise / Fall Time (Typ)
Input Type DC
Output Type Darlington with Base
Voltage - Output (Max) 18V
Current - Output / Channel 50mA
Voltage - Forward (Vf) (Typ) 1.1V
Current - DC Forward (If) (Max) 20mA
Vce Saturation (Max)
Operating Temperature $-20^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Mounting Type Surface Mount
Package / Case 8-SMD, Gull Wing
Supplier Device Package 8-SMD
Report errors

6N139S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

6N139S Payment Methods



















6N139S Shipping Methods













If you have any question about 6N139S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com