

6SEPC470M

6SEPC470M Information

	Part Number	6SEPC470M
	Manufacturer	Panasonic Electronic Components
www.Reisener.com	Category	Capacitors Aluminum - Polymer Capacitors
	Description	CAP ALUM POLY 470UF 20% 6.3V T/H
	Package	Radial, Can
. /		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com
		E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



6SEPC470M Specifications

Manufacturer Part Number 6SEPC470M Manufacturer Panasonic Electronic Components Category Capacitors Aluminum - Polymer Capacitors Aluminum - Polymer Capacitors Package Radial, Can Series OS-CON?, SEPC Type Polymer Capacitance 420% Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) 8 mOhm Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications General Purpose Ripple Current - Low Frequency 85mA @ 120Hz Impedance - Lead Spacing 0.315" Dia (8.00mm) Size / Dimension 0.315" Dia (8.00mm) Size / Dimension 0.512" (13.00mm) Size / Dimension 0.512" (13.00mm) Guare Mount Land Size - Mounting Type Aidi, Can		
CategoryCapacitorsAluminum - Polymer CapacitorsPackageRadial, CanSeriesOS-CON?, SEPCTypePolymerCapacitance470µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)8 mOhmLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency85mA @ 120HzRipple Current - High Frequency5.7A @ 100kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.512" (13.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Nounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer Part Number	6SEPC470M
Aluminun - Polymer CapacitorsPackageRadial, CanSeriesOS-CON?, SEPCTypePolymerCapacitance470µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)8 mOhmLifetime @ Temp.5000 Hrs @ 105°COperating Temperature55°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency857A @ 100HzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.512" (13.00mm)Size / Dimension0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKaial, Can	Manufacturer	Panasonic Electronic Components
PackageRadial, CanSeriesOS-CON?, SEPCTypePolymerCapacitance470µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)8 mOhmLifetime @ Temp.5000 Hrs @ 105°COperating Temperature.55°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency285mA @ 120HzImpedance.Lead Spacing0.138" (3.50mm)Size / Dimension0.512" (13.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size.Hounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesOS-CON?, SEPCTypePolymerCapacitance470μFTolerance±20%Voltage - Rated6.3VSSR (Equivalent Series Resistance)8 mOhmLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency285mA @ 120HzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)5.12" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKalia, Can		Aluminum - Polymer Capacitors
TypePolymerCapacitance470µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)8 mOhmLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CApplicationsGeneral PurposeRipple Current - High Frequency5.7A @ 100kHzImpedance-Lead Spacing0.315" Dia (8.00mm)Size / Dimension0.512" (13.00mm)Height - Seated (Max)-Munting TypeThrough HolePackage / CaseRatial, Can	Package	Radial, Can
Capacitance470µFColerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)8 mOhmLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency285mA @ 120HzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Hounting TypeThrough HolePackage / CaseRadial, Can	Series	OS-CON?, SEPC
Tolerance±0%Voltage - Rated6.3VESR (Equivalent Series Resistance)8 mOhmLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency285mA @ 120HzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.515°D ia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Туре	Polymer
Voltage - Rated6.3VESR (Equivalent Series Resistance)8 mOhmLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency285mA @ 120HzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)5.122" (13.00mm)Surface Mount Land Size-Hounting TypeFrequencyPackage / CaseRatial, Can	Capacitance	470µF
For a constraint of the series of the seri	Tolerance	$\pm 20\%$
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency285mA @ 120HzRipple Current - High Frequency5.7A @ 100kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRadial, Can	Voltage - Rated	6.3V
Operating Temperature-55°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency285mA @ 120HzRipple Current - High Frequency5.7A @ 100kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	8 mOhm
ApplicationsGeneral PurposeRipple Current - Low Frequency285mA @ 120HzRipple Current - High Frequency5.7A @ 100kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
Ripple Current - Low Frequency285mA @ 120HzRipple Current - High Frequency5.7A @ 100kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 105°C
In a constraint of the product of t	Applications	General Purpose
Impedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	285mA @ 120Hz
Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	5.7A @ 100kHz
Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.512" (13.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.138" (3.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.315" Dia (8.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.512" (13.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
•		Report errors?

6SEPC470M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

6SEPC470M Payment Methods



6SEPC470M Shipping Methods



If you have any question about 6SEPC470M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com