



6THB330M Information



For Reference Only

Part Number 6THB330M

Manufacturer Panasonic Electronic Components

Category Capacitors

Tantalum - Polymer Capacitors

Description CAP TANT POLY 330UF 6.3V 2917

Package 2917 (7343 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









6THB330M Specifications

Manufacturer Part Number Manufacturer Category Capacitors Tantalum - Polymer Capacitors Package 2917 (7343 Metric) Series POSCAP? TH Capacitance 330µF Tolerance ½0% Voltage - Rated 5.3V Type Molded ESR (Equivalent Series Resistance) Operating Temperature Lifetime @ Temp. Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Surface Mount 1000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.154" (3.90mm) Lead Spacing Manufacturer Size Code Peatures Report errors?		
Category Capacitors Tantalum - Polymer Capacitors Package 2917 (7343 Metric) Series POSCAP? TH Capacitance 330µF Tolerance ±20% Voltage - Rated 6.3V Type Molded ESR (Equivalent Series Resistance) 40 mOhm Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 1000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.154" (3.90mm) Lead Spacing - Manufacturer Size Code D4 Features General Purpose	Manufacturer Part Number	6THB330M
Tantalum - Polymer Capacitors Package 2917 (7343 Metric) Series POSCAP? TH Capacitance 330μF Tolerance ±20% Voltage - Rated 6.3V Type Molded ESR (Equivalent Series Resistance) 40 mOhm Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 1000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.154" (3.90mm) Lead Spacing - Manufacturer Size Code D4 Features General Purpose	Manufacturer	Panasonic Electronic Components
Package 2917 (7343 Metric) Series POSCAP? TH Capacitance 330μF Tolerance ±20% Voltage - Rated 6.3V Type Molded ESR (Equivalent Series Resistance) 40 mOhm Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 1000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.154" (3.90mm) Lead Spacing - Manufacturer Size Code D4 Features General Purpose	Category	Capacitors
Series POSCAP? TH Capacitance 330μF Tolerance ±20% Voltage - Rated 6.3V Type Molded ESR (Equivalent Series Resistance) 40 mOhm Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 1000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.154" (3.90mm) Lead Spacing - Manufacturer Size Code D4 Features General Purpose		Tantalum - Polymer Capacitors
Capacitance 330μF Tolerance ±20% Voltage - Rated 6.3V Type Molded ESR (Equivalent Series Resistance) 40 mOhm Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 1000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.154" (3.90mm) Lead Spacing - Manufacturer Size Code D4 Features General Purpose	Package	2917 (7343 Metric)
Tolerance ±20% Voltage - Rated 6.3V Type Molded ESR (Equivalent Series Resistance) 40 mOhm Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 1000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.154" (3.90mm) Lead Spacing - Manufacturer Size Code D4 Features General Purpose	Series	POSCAP? TH
Voltage - Rated Type Molded ESR (Equivalent Series Resistance) Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 1000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) Lead Spacing Manufacturer Size Code Features General Purpose	Capacitance	330μF
Type Molded ESR (Equivalent Series Resistance) 40 mOhm Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 1000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.154" (3.90mm) Lead Spacing - Manufacturer Size Code D4 Features General Purpose	Tolerance	±20%
ESR (Equivalent Series Resistance) 40 mOhm Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 1000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 1000 Hrs @ 125°C Nounting Type Surface Mount 2917 (7343 Metric) 1000 Hrs @ 125°C Surface Mount 2917 (7343 Metric) Size / Dimension 1000 Hrs @ 125°C Surface Mount 2917 (7343 Metric) Size / Dimension 1000 Hrs @ 125°C Surface Mount 2917 (7343 Metric) Size / Dimension 1000 Hrs @ 125°C Surface Mount Size / Dimension General Purpose	Voltage - Rated	6.3V
Operating Temperature Lifetime @ Temp. 1000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) Lead Spacing Manufacturer Size Code Features General Purpose	Туре	Molded
Lifetime @ Temp. 1000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.154" (3.90mm) Lead Spacing - Manufacturer Size Code D4 Features General Purpose	ESR (Equivalent Series Resistance)	40 mOhm
Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.154" (3.90mm) Lead Spacing Manufacturer Size Code Features General Purpose	Operating Temperature	-55°C ~ 125°C
Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.154" (3.90mm) Lead Spacing - Manufacturer Size Code D4 Features General Purpose	Lifetime @ Temp.	1000 Hrs @ 125°C
Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.154" (3.90mm) Lead Spacing - Manufacturer Size Code D4 Features General Purpose	Mounting Type	Surface Mount
Height - Seated (Max) Lead Spacing Manufacturer Size Code Features O.154" (3.90mm) - Manufacturer Size Code D4 General Purpose	Package / Case	2917 (7343 Metric)
Lead Spacing - Manufacturer Size Code D4 Features General Purpose	Size / Dimension	0.287" L x 0.169" W (7.30mm x 4.30mm)
Manufacturer Size Code D4 Features General Purpose	Height - Seated (Max)	0.154" (3.90mm)
Features General Purpose	Lead Spacing	-
	Manufacturer Size Code	D4
Report errors?	Features	General Purpose
		Report errors?

6THB330M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

6THB330M Payment Methods





















6THB330M Shipping Methods













If you have any question about 6THB330M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com