

6THE150MI

6THE150MI Information

www.helsener.com	Part Number Manufacturer Category Description Package	6THE150MI Panasonic Electronic Components Capacitors Tantalum - Polymer Capacitors CAP TANT POLY 150UF 6.3V 2917 2917 (7343 Metric) For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



6THE150MI Specifications

Manufacturer Part Number GTHE150MI Manufacturer Panasonic Electronic Components Category Capacitors Tantalum - Polymer Capacitors Tantalum - Polymer Capacitors Package 2917 (7343 Metric) Series POSCAP? TH Capacitance 150µF Tolerance ±20% Voltage - Rated 6.3V Type Molded Series 18 mOhm @ 100kHz Operating Temperature -55°C ~ 125°C Lifetime @ Temp. 1000 Hrs @ 125°C Mounting Type Surface Mount Package / Case 2917 (7343 Metric) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.75" (1.90mm) Lead Spacing - Height - Seated (Max) 0.75" (1.90mm)		
CategoryCapacitorsTantalum - Polymer CapacitorsPackage2917 (7343 Metric)SeriesPOSCAP? THCapacitance150µFTolerance±20%Voltage - Rated6.3VTypeMoldedESR (Equivalent Series Resistance)18 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.1000 Hrs @ 125°CMounting TypeSurface MountSize / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.075" (1.90mm)Lead Spacing-FeaturesD2EFeaturesGeneral Purpose	Manufacturer Part Number	6THE150MI
Antalum - Polymer CapacitorsPackage2917 (7343 Metric)SeriesPOSCAP? THCapacitance150µFTolerance±20%Voltage - Rated6.3VTypeMoldedESR (Equivalent Series Resistance)18 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.1000 Hrs @ 125°CMounting TypeSurface MountSize / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.075" (1.90mm)Lead Spacing-<	Manufacturer	Panasonic Electronic Components
Package2917 (7343 Metric)SeriesPOSCAP? THCapacitance150µFTolerance±20%Voltage - Rated6.3VTypeMoldedESR (Equivalent Series Resistance)18 mOhm @ 100kHzOperating Temperature55°C ~ 125°CLifetime @ Temp.1000 Hrs @ 125°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.075" (1.90mm)Lead Spacing-FeaturesOEEFeaturesCancel Purpose	Category	Capacitors
SeriesPOSCAP? THCapacitance150µFTolerance±20%Voltage - Rated6.3VTypeMoldedESR (Equivalent Series Resistance)18 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.1000 Hrs @ 125°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.075" (1.90mm)Lead Spacing-FeaturesOEFeaturesCeneral Purpose		Tantalum - Polymer Capacitors
Capacitance150µFTolerance±20%Voltage - Rated6.3VTypeMoldedESR (Equivalent Series Resistance)18 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.1000 Hrs @ 125°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.028" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max).075" (1.90mm)Lead SpacingDEFeaturesGeneral Purpose	Package	2917 (7343 Metric)
Tolerance±0%Tolerance±20%Voltage - Rated6.3VTypeMoldedTypeMoldedESR (Equivalent Series Resistance)18 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.1000 Hrs @ 125°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.075" (1.90mm)Lead Spacing-FeaturesD2EFeaturesGeneral Purpose	Series	POSCAP? TH
NotationDescriptionVoltage - Rated6.3VTypeMoldedESR (Equivalent Series Resistance)18 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.1000 Hrs @ 125°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.075" (1.90mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Capacitance	150µF
TypeMoldedESR (Equivalent Series Resistance)18 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.1000 Hrs @ 125°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.075" (1.90mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Tolerance	±20%
ArBit Mohm @ 100kHzESR (Equivalent Series Resistance)18 mOhm @ 100kHzOperating Temperature-55°C ~ 125°CLifetime @ Temp.1000 Hrs @ 125°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.075" (1.90mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Voltage - Rated	6.3V
Operating Temperature-55°C ~ 125°CLifetime @ Temp.1000 Hrs @ 125°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.075" (1.90mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Туре	Molded
Lifetime @ Temp.1000 Hrs @ 125°CMounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.075" (1.90mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	ESR (Equivalent Series Resistance)	18 mOhm @ 100kHz
Nounting TypeSurface MountPackage / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.075" (1.90mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Operating Temperature	-55°C ~ 125°C
Package / Case2917 (7343 Metric)Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.075" (1.90mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Lifetime @ Temp.	1000 Hrs @ 125°C
Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.075" (1.90mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Mounting Type	Surface Mount
Height - Seated (Max)0.075" (1.90mm)Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Package / Case	2917 (7343 Metric)
Lead Spacing-Manufacturer Size CodeD2EFeaturesGeneral Purpose	Size / Dimension	0.287" L x 0.169" W (7.30mm x 4.30mm)
Manufacturer Size CodeD2EFeaturesGeneral Purpose	Height - Seated (Max)	0.075" (1.90mm)
Features General Purpose	Lead Spacing	-
	Manufacturer Size Code	D2E
Report errors?	Features	General Purpose
1		Report errors?

6THE150MI Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

6THE150MI Payment Methods



6THE150MI Shipping Methods



If you have any question about 6THE150MI, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com