

7-1393808-3 Information



For Reference Only

Part Number 7-1393808-3

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GEN PURPOSE 4PDT 200MA 20V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









7-1393808-3 Specifications

Manufacturer Part Number7-1393808-3ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPackage-SeriesV23154, AXICOMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36.3mACoil Voltage20VDCContact Form4PDT (4 Form C)Contact Rating (Current)200mASwitching Voltage30VAC, 36VDC - MaxTurn On Voltage (Max)14.4 VDCTurn Off Voltage (Min)-Operate Time7.5msRelease Time3msFeatures-Mounting TypeSocketableTermination StylePlug InReport errors?		
Category Relays Package - Series V23154, AXICOM Relay Type General Purpose Coil Type Non Latching Coil Current 36.3mA Coil Voltage 20VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 200mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 14.4 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features - Mounting Type Socketable Termination Style Plug In	Manufacturer Part Number	7-1393808-3
Package - Series V23154, AXICOM Relay Type General Purpose Coil Type Non Latching Coil Current 36.3mA Coil Voltage 20VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 200mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 14.4 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features - Mounting Type Socketable Termination Style Plug In	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series V23154, AXICOM Relay Type General Purpose Coil Type Non Latching Coil Current 36.3mA Coil Voltage 20VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 200mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 14.4 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features - Mounting Type Socketable Termination Style Plug In	Category	Relays
SeriesV23154, AXICOMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36.3mACoil Voltage20VDCContact Form4PDT (4 Form C)Contact Rating (Current)200mASwitching Voltage30VAC, 36VDC - MaxTurn On Voltage (Max)14.4 VDCTurn Off Voltage (Min)-Operate Time7.5msRelease Time3msFeatures-Mounting TypeSocketableTermination StylePlug In		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36.3mACoil Voltage20VDCContact Form4PDT (4 Form C)Contact Rating (Current)200mASwitching Voltage30VAC, 36VDC - MaxTurn On Voltage (Max)14.4 VDCTurn Off Voltage (Min)-Operate Time7.5msRelease Time3msFeatures-Mounting TypeSocketableTermination StylePlug In	Package	-
Coil Type Non Latching Coil Current 36.3mA Coil Voltage 20VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 200mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 14.4 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features - Mounting Type Socketable Termination Style Plug In	Series	V23154, AXICOM
Coil Current36.3mACoil Voltage20VDCContact Form4PDT (4 Form C)Contact Rating (Current)200mASwitching Voltage30VAC, 36VDC - MaxTurn On Voltage (Max)14.4 VDCTurn Off Voltage (Min)-Operate Time7.5msRelease Time3msFeatures-Mounting TypeSocketableTermination StylePlug In	Relay Type	General Purpose
Coil Voltage20VDCContact Form4PDT (4 Form C)Contact Rating (Current)200mASwitching Voltage30VAC, 36VDC - MaxTurn On Voltage (Max)14.4 VDCTurn Off Voltage (Min)-Operate Time7.5msRelease Time3msFeatures-Mounting TypeSocketableTermination StylePlug In	Coil Type	Non Latching
Contact Form 4PDT (4 Form C) Contact Rating (Current) 200mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 14.4 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features - Mounting Type Socketable Termination Style Plug In	Coil Current	36.3mA
Contact Rating (Current) Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 14.4 VDC Turn Off Voltage (Min) Operate Time 7.5ms Release Time 3ms Features - Mounting Type Socketable Termination Style	Coil Voltage	20VDC
Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 14.4 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features - Mounting Type Socketable Termination Style Plug In	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) 14.4 VDC Turn Off Voltage (Min) Operate Time 7.5ms Release Time 3ms Features - Mounting Type Socketable Termination Style Plug In	Contact Rating (Current)	200mA
Turn Off Voltage (Min) Operate Time 7.5ms Release Time 3ms Features - Mounting Type Socketable Termination Style Plug In	Switching Voltage	30VAC, 36VDC - Max
Operate Time 7.5ms Release Time 3ms Features - Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	14.4 VDC
Release Time 3ms Features - Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	-
Features - Mounting Type Socketable Termination Style Plug In	Operate Time	7.5ms
Mounting Type Socketable Termination Style Plug In	Release Time	3ms
Termination Style Plug In	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

7-1393808-3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

7-1393808-3 Payment Methods



















7-1393808-3 Shipping Methods













If you have any question about 7-1393808-3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com