

## 7-1462037-0 Information

Part Number 7-1462037-0

Manufacturer TE Connectiv

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Signal Relays, Up to 2 Amps

**Description** RELAY TELECOM DPDT 2A 24V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 7-1462037-0 Specifications

Manufacturer Part Number  Manufacturer  TE Connectivity Potter & Brumfield Relays  Relays  Signal Relays, Up to 2 Amps  Package  - Series  IM, AXICOM  Relay Type  Telecom  Coil Type  Latching, Single Coil  Coil Current  8.3mA  Coil Voltage  24VDC  Contact Form  DPDT (2 Form C)  Contact Rating (Current)  2A  Switching Voltage  250VAC, 220VDC - Max  Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Release Time  Features  Sealed - Hermetically  Mounting Type  Surface Mount  Termination Style  TE Connectivity Potter & Brumfield Relays  Tim On Voltage (May)  Telecom  Latching, Single Coil  Latching, Single Coil  ANAICOM  Telecom  Latching, Single Coil  Latching, Single Coil		
CategoryRelaysPackage-SeriesIM, AXICOMRelay TypeTelecomCoil TypeLatching, Single CoilCoil Current8.3mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time3msRelease Time3msFeaturesSealed - HermeticallyMounting TypeSurface MountTermination StyleGull Wing	Manufacturer Part Number	7-1462037-0
Package-SeriesIM, AXICOMRelay TypeTelecomCoil TypeLatching, Single CoilCoil Current8.3mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time3msRelease Time3msFeaturesSealed - HermeticallyMounting TypeSurface MountTermination StyleGull Wing	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package-SeriesIM, AXICOMRelay TypeTelecomCoil TypeLatching, Single CoilCoil Current8.3mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time3msRelease Time3msFeaturesSealed - HermeticallyMounting TypeSurface MountTermination StyleGull Wing	Category	Relays
SeriesIM, AXICOMRelay TypeTelecomCoil TypeLatching, Single CoilCoil Current8.3mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time3msRelease Time3msFeaturesSealed - HermeticallyMounting TypeSurface MountTermination StyleGull Wing		Signal Relays, Up to 2 Amps
Relay TypeTelecomCoil TypeLatching, Single CoilCoil Current8.3mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time3msRelease Time3msFeaturesSealed - HermeticallyMounting TypeSurface MountTermination StyleGull Wing	Package	-
Coil Type Latching, Single Coil Coil Current 8.3mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 3ms Release Time 3ms Features Sealed - Hermetically Mounting Type Surface Mount Termination Style Guil Wing	Series	IM, AXICOM
Coil Current Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 3ms Release Time 3ms Features Sealed - Hermetically Mounting Type Surface Mount Termination Style Gull Wing	Relay Type	Telecom
Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 3ms Release Time 3ms Features Sealed - Hermetically Mounting Type Surface Mount Termination Style Gull Wing	Coil Type	Latching, Single Coil
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  250VAC, 220VDC - Max  Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  3ms  Release Time  3ms  Release Time  Sealed - Hermetically  Mounting Type  Surface Mount  Termination Style  DPDT (2 Form C)  2A  Soma  Sealed - Max  Sealed - Hermetically	Coil Current	8.3mA
Contact Rating (Current)  Switching Voltage  250VAC, 220VDC - Max  Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  Operate Time  3ms  Release Time  3ms  Features  Sealed - Hermetically  Mounting Type  Surface Mount  Termination Style  Gull Wing	Coil Voltage	24VDC
Switching Voltage 250VAC, 220VDC - Max  Turn On Voltage (Max) 18 VDC  Turn Off Voltage (Min) - Operate Time 3ms  Release Time 3ms  Features Sealed - Hermetically  Mounting Type Surface Mount  Termination Style Gull Wing	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Sams  Release Time  Sealed - Hermetically  Mounting Type  Surface Mount  Termination Style  18 VDC	Contact Rating (Current)	2A
Turn Off Voltage (Min)  Operate Time  3ms  Release Time  3ms  Features  Sealed - Hermetically  Mounting Type  Surface Mount  Termination Style  Gull Wing	Switching Voltage	250VAC, 220VDC - Max
Operate Time 3ms  Release Time 3ms  Features Sealed - Hermetically  Mounting Type Surface Mount  Termination Style Gull Wing	Turn On Voltage (Max)	18 VDC
Release Time 3ms Features Sealed - Hermetically Mounting Type Surface Mount Termination Style Gull Wing	Turn Off Voltage (Min)	-
Features Sealed - Hermetically  Mounting Type Surface Mount  Termination Style Gull Wing	Operate Time	3ms
Mounting Type Surface Mount Termination Style Gull Wing	Release Time	3ms
Termination Style Gull Wing	Features	Sealed - Hermetically
	Mounting Type	Surface Mount
Report errors?	Termination Style	Gull Wing
Report criois:		Report errors?

### 7-1462037-0 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **7-1462037-0 Payment Methods**



















## 7-1462037-0 Shipping Methods













If you have any question about 7-1462037-0, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com