

## 7.2TDLSJ40

Request a Quote

### 7.2TDLSJ40 Information

	Part Number	7 2TDI \$140
Contail terrice cards they	Manufacturer	
	Category	Circuit Protection Electrical, Specialty Fuses
	Description	FUSE 7.2KV 40AMP 2" DIN
	Package	Fuse Link
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com E-mail: salesdept@heisener.com

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### 7.2TDLSJ40 Specifications

ManufacturerEatonCategoryCircuit ProtectionElectrical, Specialty FusesPackageFuse LinkSeries*Series*Current Rating-Voltage Rating - DC-Voltage Rating - DC-Applications-Approvals-Class-Approvals-Operating Temperature-Operating Temperature-Breaking Capacity @ Rated Voltage-Noting Type-Sterking Capacity @ Rated Notage-Sterking Capacity @ Rated Notage <th></th> <th></th>		
CategoryCircuit ProtectionPackageElectrical, Specialty FusesPackageFuse LinkSeries*Fuse Type-Current Rating-Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseSuce LinkSize / DimensionSuce Tint 49° Liot 800mm x 292.00mm)	Manufacturer Part Number	7.2TDLSJ40
Bit of the section o	Manufacturer	Eaton
PackageFuse LinkSeries*Fuse Type-Fuse Type-Current Rating-Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Approvals-Operating Type-Breaking Capacity @ Rated Voltage-Houring TypeHolderPackage / CaseSuce LinkSize / Dimension2,008"Dia x 11,496"L (50.80mm x 292.00mm)	Category	Circuit Protection
Series   *     Series   -     Fuse Type   -     Current Rating   -     Voltage Rating - AC   -     Voltage Rating - DC   -     Response Time   -     Applications   -     Features   -     Class   -     Approvals   -     Operating Temperature   -     Breaking Capacity @ Rated Voltage   -     Mounting Type   Holder     Package / Case   Seuse Link     Size / Dimension   2.008" Dia x 11.496" L(50.80mm x 292.00mm)		Electrical, Specialty Fuses
Fuse Type-Fuse Type-Current Rating-Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseSuos Til.496" L (50.80mm x 292.00mm)	Package	Fuse Link
Current Rating-Current Rating - AC-Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseSize / DimensionSize / Dimension2.008" Dia x 11.496" L (50.80mm x 292.00mm)	Series	*
Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseSize / DimensionSize / Dimension2.008" Dia x 11.496" L (50.80mm x 292.00mm)	Fuse Type	-
Voltage Rating - DC-Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseFuse LinkSize / Dimension2008" Dia x 11.496" L (50.80mm x 292.00mm)	Current Rating	-
Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseFuse LinkSize / Dimension2.008" Dia x 11.496" L (50.80mm x 292.00mm)	Voltage Rating - AC	-
Applications-Features-Class-Approvals-Operating Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseFuse LinkSize / Dimension2.008" Dia x 11.496" L (50.80mm x 292.00mm)	Voltage Rating - DC	-
Features-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseFuse LinkSize / Dimension2.008" Dia x 11.496" L (50.80mm x 292.00mm)	Response Time	-
Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseFuse LinkSize / Dimension2.008" Dia x 11.496" L (50.80mm x 292.00mm)	Applications	-
Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseFuse LinkSize / Dimension2.008" Dia x 11.496" L (50.80mm x 292.00mm)	Features	-
Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseFuse LinkSize / Dimension2.008" Dia x 11.496" L (50.80mm x 292.00mm)	Class	-
Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseFuse LinkSize / Dimension2.008" Dia x 11.496" L (50.80mm x 292.00mm)	Approvals	-
Mounting TypeHolderPackage / CaseFuse LinkSize / Dimension2.008" Dia x 11.496" L (50.80mm x 292.00mm)	Operating Temperature	-
Package / CaseFuse LinkSize / Dimension2.008" Dia x 11.496" L (50.80mm x 292.00mm)	Breaking Capacity @ Rated Voltage	-
Size / Dimension   2.008" Dia x 11.496" L (50.80mm x 292.00mm)	Mounting Type	Holder
	Package / Case	Fuse Link
Report errors?	Size / Dimension	2.008" Dia x 11.496" L (50.80mm x 292.00mm)
		Report errors?

### 7.2TDLSJ40 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE GUARANTEE

### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# 7.2TDLSJ40 Payment Methods Image: I

If you have any question about 7.2TDLSJ40, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com