

7023-D-N-350 Information



For Reference Only

Part Number 7023-D-N-350 Manufacturer LEDdynamics Inc.

Category Power Supplies - External/Internal (Off-Board)

LED Drivers

Description LED DRIVER CC BUCK 32V 350MA

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









7023-D-N-350 Specifications

Manufacturer Part Number 7023-D-N-350 Manufacturer LEDdynamics Inc. Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series BuckPlus? 7023 Type Constant Current Topology Buck Number of Outputs 1 Voltage - Input (Min) 5V Voltage - Input (Max) 32V Voltage - Output 32V (Max) Current - Output (Max) 350mA Power (Watts) 11W Voltage - Isolation - Dimming - Features SCP Ratings - Operating Temperature -40°C ~ 80°C Efficiency 95% Termination Style Wire Leads Size / Dimension 0.83" L x 0.83" W x 0.43" H (21.1mm x 21.1mm x 10.9mm)		
Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series BuckPlus? 7023 Type Constant Current Topology Buck Number of Outputs 1 Voltage - Input (Min) 5V Voltage - Input (Max) 32V Voltage - Output 32V (Max) Current - Output (Max) 350mA Power (Watts) 11W Voltage - Isolation - Dimming - Features SCP Ratings - Operating Temperature -40°C ~ 80°C Efficiency 95% Termination Style Wire Leads Size / Dimension 0.83" L x 0.83" W x 0.43" H (21.1mm x 21.1mm x 10.9mm)	Manufacturer Part Number	7023-D-N-350
LED Drivers Package - Series BuckPlus? 7023 Type Constant Current Topology Buck Number of Outputs 1 Voltage - Input (Min) 5V Voltage - Input (Max) 32V Voltage - Output 32V (Max) Current - Output (Max) 350mA Power (Watts) 11W Voltage - Isolation - Dimming - Features SCP Ratings - Operating Temperature -40°C ~ 80°C Efficiency 95% Termination Style Wire Leads Size / Dimension 0.83" L x 0.83" W x 0.43" H (21.1mm x 21.1mm x 10.9mm)	Manufacturer	LEDdynamics Inc.
Package - Series BuckPlus? 7023 Type Constant Current Topology Buck Number of Outputs 1 Voltage - Input (Min) 5V Voltage - Input (Max) 32V Voltage - Output 32V (Max) Current - Output (Max) 350mA Power (Watts) 11W Voltage - Isolation - Dimming - Features SCP Ratings - Operating Temperature -40°C ~ 80°C Efficiency 95% Termination Style Wire Leads Size / Dimension 0.83" L x 0.83" W x 0.43" H (21.1mm x 21.1mm x 10.9mm)	Category	Power Supplies - External/Internal (Off-Board)
Series BuckPlus? 7023 Type Constant Current Topology Buck Number of Outputs 1 Voltage - Input (Min) 5V Voltage - Input (Max) 32V Voltage - Output 32V (Max) Current - Output (Max) 350mA Power (Watts) 11W Voltage - Isolation - Dimming - Features SCP Ratings - Operating Temperature -40°C ~ 80°C Efficiency 95% Termination Style Wire Leads Size / Dimension 0.83" L x 0.83" W x 0.43" H (21.1mm x 21.1mm x 10.9mm)		LED Drivers
Type Constant Current Topology Buck Number of Outputs 1 Voltage - Input (Min) 5V Voltage - Input (Max) 32V Voltage - Output 32V (Max) Current - Output (Max) 350mA Power (Watts) 11W Voltage - Isolation - Dimming - Features SCP Ratings - Operating Temperature -40°C ~ 80°C Efficiency 95% Termination Style Wire Leads Size / Dimension 0.83" L x 0.83" W x 0.43" H (21.1mm x 21.1mm x 10.9mm)	Package	-
Topology Buck Number of Outputs 1 Voltage - Input (Min) 5V Voltage - Output 32V Voltage - Output 32V (Max) Current - Output (Max) 350mA Power (Watts) 11W Voltage - Isolation - Dimming - Features SCP Ratings - Operating Temperature -40°C ~ 80°C Efficiency 95% Termination Style Wire Leads Size / Dimension 0.83" L x 0.83" W x 0.43" H (21.1mm x 21.1mm x 10.9mm)	Series	BuckPlus? 7023
Number of Outputs 1 Voltage - Input (Min) 5V Voltage - Input (Max) 32V Voltage - Output 32V (Max) Current - Output (Max) 350mA Power (Watts) 11W Voltage - Isolation - Dimming - Features SCP Ratings - Operating Temperature -40°C ~ 80°C Efficiency 95% Termination Style Wire Leads Size / Dimension 0.83" L x 0.83" W x 0.43" H (21.1mm x 21.1mm x 10.9mm)	Type	Constant Current
Voltage - Input (Min) 5V Voltage - Input (Max) 32V Voltage - Output 32V (Max) Current - Output (Max) 350mA Power (Watts) 11W Voltage - Isolation - Dimming - Features SCP Ratings - Operating Temperature -40°C ~ 80°C Efficiency 95% Termination Style Wire Leads Size / Dimension 0.83" L x 0.83" W x 0.43" H (21.1mm x 21.1mm x 10.9mm)	Topology	Buck
Voltage - Input (Max) 32V Voltage - Output 32V (Max) Current - Output (Max) 350mA Power (Watts) 11W Voltage - Isolation - Dimming - Features SCP Ratings - Operating Temperature -40°C ~ 80°C Efficiency 95% Termination Style Wire Leads Size / Dimension 0.83" L x 0.83" W x 0.43" H (21.1mm x 21.1mm x 10.9mm)	Number of Outputs	1
Voltage - Output 32V (Max) Current - Output (Max) 350mA Power (Watts) 11W Voltage - Isolation - Dimming - Features SCP Ratings - Operating Temperature -40°C ~ 80°C Efficiency 95% Termination Style Wire Leads Size / Dimension 0.83" L x 0.83" W x 0.43" H (21.1mm x 21.1mm x 10.9mm)	Voltage - Input (Min)	5V
Current - Output (Max) 350mA Power (Watts) 11W Voltage - Isolation - Dimming - Features SCP Ratings - Operating Temperature -40°C ~ 80°C Efficiency 95% Termination Style Wire Leads Size / Dimension 0.83" L x 0.83" W x 0.43" H (21.1mm x 21.1mm x 10.9mm)	Voltage - Input (Max)	32V
Power (Watts) Voltage - Isolation Dimming - Features SCP Ratings - Operating Temperature -40°C ~ 80°C Efficiency 95% Termination Style Size / Dimension 11W - Output - Dimming - Output - Dimming - Output - Dimming - Output - Dimming - Output - O	Voltage - Output	32V (Max)
Voltage - Isolation Dimming - Features SCP Ratings - Operating Temperature -40°C ~ 80°C Efficiency 95% Termination Style Size / Dimension - Output - Voltage - Isolation	Current - Output (Max)	350mA
Dimming - Features SCP Ratings - Operating Temperature -40°C ~ 80°C Efficiency 95% Termination Style Wire Leads Size / Dimension 0.83" L x 0.83" W x 0.43" H (21.1mm x 21.1mm x 10.9mm)	Power (Watts)	11W
Features SCP Ratings - Operating Temperature -40°C ~ 80°C Efficiency 95% Termination Style Wire Leads Size / Dimension 0.83" L x 0.83" W x 0.43" H (21.1mm x 21.1mm x 10.9mm)	Voltage - Isolation	-
Ratings Operating Temperature -40°C ~ 80°C Efficiency 95% Termination Style Wire Leads Size / Dimension 0.83" L x 0.83" W x 0.43" H (21.1mm x 21.1mm x 10.9mm)	Dimming	-
Operating Temperature -40°C ~ 80°C Efficiency 95% Termination Style Wire Leads Size / Dimension 0.83" L x 0.83" W x 0.43" H (21.1mm x 21.1mm x 10.9mm)	Features	SCP
Efficiency 95% Termination Style Wire Leads Size / Dimension 0.83" L x 0.83" W x 0.43" H (21.1mm x 21.1mm x 10.9mm)	Ratings	-
Termination Style Wire Leads Size / Dimension 0.83" L x 0.83" W x 0.43" H (21.1mm x 21.1mm x 10.9mm)		-40°C ~ 80°C
Size / Dimension 0.83" L x 0.83" W x 0.43" H (21.1mm x 21.1mm x 10.9mm)	Efficiency	95%
	Termination Style	Wire Leads
Report errors?	Size / Dimension	0.83" L x 0.83" W x 0.43" H (21.1mm x 21.1mm x 10.9mm)
		Report errors?

7023-D-N-350 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

7023-D-N-350 Payment Methods



















7023-D-N-350 Shipping Methods













If you have any question about 7023-D-N-350, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com