



7101K9AKE Information

Heisener.com

Part Number 7101K9AKE

Manufacturer C&K **Category** Switches

Toggle Switches

Description SWITCH TOGGLE SPDT 0.4VA 20V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









7101K9AKE Specifications

Manufacturer Part Number 7101K9AKE Manufacturer C&K Category Switches Package - Series 7000 Circuit SPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Locking Lever Actuator Length 17.88mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals		
CategorySwitchesPackage-Series7000CircuitSPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeLocking LeverActuator Length17.88mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer Part Number	7101K9AKE
Package - 7000 Circuit SPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Locking Lever Actuator Length 17.88mm Illumination Type, Color 11lumination Type, Color - 1llumination Type, Color 11lumination Voltage (Nominal) - 1 Mounting Type Through Hole, Right Angle PC Pin Panel Cutout Dimensions - 1 Bushing Thread Unthreaded 1 Ingress Protection - Epoxy Sealed Terminals	Manufacturer	C&K
Package-Series7000CircuitSPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeLocking LeverActuator Length17.88mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Category	Switches
Series7000CircuitSPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeLocking LeverActuator Length17.88mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals		Toggle Switches
CircuitSPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeLocking LeverActuator Length17.88mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeLocking LeverActuator Length17.88mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Series	7000
Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Locking Lever Actuator Length 17.88mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Circuit	SPDT
Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeLocking LeverActuator Length17.88mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Switch Function	On-On
Voltage Rating - DC Actuator Type Locking Lever Actuator Length 17.88mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection Features Epoxy Sealed Terminals	Current Rating	0.4VA (AC/DC)
Actuator Type Actuator Length 17.88mm Illumination Non-Illuminated Illumination Type, Color	Voltage Rating - AC	20V
Actuator Length 17.88mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - DC	20V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle PC Pin Panel Cutout Dimensions - Sushing Thread Unthreaded Ingress Protection - Epoxy Sealed Terminals	Actuator Type	Locking Lever
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection Features Epoxy Sealed Terminals	Actuator Length	17.88mm
Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection Features Epoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting Type Through Hole, Right Angle PC Pin Panel Cutout Dimensions Pushing Thread Unthreaded Ingress Protection Features Through Hole, Right Angle PC Pin Panel Cutout Dimensions - Epoxy Sealed Terminals	Illumination Type, Color	-
Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Mounting Type	Through Hole, Right Angle
Bushing Thread Unthreaded Ingress Protection Features Epoxy Sealed Terminals	Termination Style	PC Pin
Ingress Protection - Epoxy Sealed Terminals	Panel Cutout Dimensions	-
Features Epoxy Sealed Terminals	Bushing Thread	Unthreaded
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

7101K9AKE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

7101K9AKE Payment Methods





















7101K9AKE Shipping Methods













If you have any question about 7101K9AKE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com