



7101L2D9ABE Information

Heisener.com

Part Number 7101L2D9ABE

Manufacturer C&K **Category** Switches

Toggle Switches

Description SWITCH TOGGLE SPDT 0.4VA 20V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









7101L2D9ABE Specifications

Manufacturer Part Number 7101L2D9ABE Manufacturer C&K Category Switches Package - Series 7000 Circuit SPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Standard Round Actuator Length 15.75mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals		
CategorySwitchesPackage-Series7000CircuitSPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length15.75mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer Part Number	7101L2D9ABE
Package - 7000 Circuit SPDT Switch Function On-On Current Rating - AC 20V Voltage Rating - DC 20V Actuator Type Standard Round Actuator Length Illumination Type, Color Illumination Type, Color Illumination Voltage (Nominal) - Monuting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Ingress Protection - Illuminates Epoxy Sealed Terminals Toggle Switches - 7000 Around Actuator SPDT SPDT SPDT SPDT SPDT SPDT SPDT SPDT	Manufacturer	C&K
Package - Series 7000 Circuit SPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Standard Round Actuator Length 15.75mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Category	Switches
Series 7000 Circuit SPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Standard Round Actuator Length 15.75mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals		Toggle Switches
CircuitSPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length15.75mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length15.75mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Series	7000
Current Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length15.75mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Circuit	SPDT
Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length15.75mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Switch Function	On-On
Voltage Rating - DC Actuator Type Standard Round Actuator Length 15.75mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection Features Epoxy Sealed Terminals	Current Rating	0.4VA (AC/DC)
Actuator Type Standard Round Actuator Length 15.75mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - AC	20V
Actuator Length 15.75mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection Features Epoxy Sealed Terminals	Voltage Rating - DC	20V
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Actuator Type	Standard Round
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Actuator Length	15.75mm
Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection Features Epoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Mounting Type	Through Hole, Right Angle
Bushing Thread Unthreaded Ingress Protection Features Epoxy Sealed Terminals	Termination Style	PC Pin
Ingress Protection - Epoxy Sealed Terminals	Panel Cutout Dimensions	-
Features Epoxy Sealed Terminals	Bushing Thread	Unthreaded
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

7101L2D9ABE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

7101L2D9ABE Payment Methods



















7101L2D9ABE Shipping Methods













If you have any question about 7101L2D9ABE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com