



7101L2PHCGE Information

Heisener.com

Part Number 7101L2PHCGE

Manufacturer C&K **Category** Switches

Toggle Switches

Description SWITCH TOGGLE SPDT 5A 120V

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









7101L2PHCGE Specifications

| Manufacturer Part Number 7101L2PHCGE Manufacturer C&K Category Switches Package - Series 7000 Circuit SPDT Switch Function On-On Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Anti-Rotation Actuator Length 13.97mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | | |
|--|--------------------------------|------------------------|
| CategorySwitchesPackage-Series7000CircuitSPDTSwitch FunctionOn-OnCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeAnti-RotationActuator Length13.97mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Manufacturer Part Number | 7101L2PHCGE |
| Package - Series 7000 Circuit SPDT Switch Function On-On Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Anti-Rotation Actuator Length 13.97mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | Manufacturer | C&K |
| Package - Series 7000 Circuit SPDT Switch Function On-On Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Anti-Rotation Actuator Length 13.97mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | Category | Switches |
| Series 7000 Circuit SPDT Switch Function On-On Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Anti-Rotation Actuator Length 13.97mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | | Toggle Switches |
| Circuit SPDT Switch Function On-On Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Anti-Rotation Actuator Length 13.97mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | Package | - |
| Switch FunctionOn-OnCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeAnti-RotationActuator Length13.97mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Series | 7000 |
| Current Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeAnti-RotationActuator Length13.97mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Circuit | SPDT |
| Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeAnti-RotationActuator Length13.97mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Switch Function | On-On |
| Voltage Rating - DC Actuator Type Anti-Rotation Actuator Length 13.97mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread Ingress Protection Features Epoxy Sealed Terminals | Current Rating | 5A (AC/DC) |
| Actuator Type Anti-Rotation Actuator Length 13.97mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | Voltage Rating - AC | 120V |
| Actuator Length 13.97mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | Voltage Rating - DC | 28V |
| Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Epoxy Sealed Terminals | Actuator Type | Anti-Rotation |
| Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Actuator Length | 13.97mm |
| Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | Illumination | Non-Illuminated |
| Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Illumination Type, Color | - |
| Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | Illumination Voltage (Nominal) | - |
| Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection Features Epoxy Sealed Terminals | Mounting Type | Panel Mount |
| Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | Termination Style | PC Pin |
| Ingress Protection - Epoxy Sealed Terminals | Panel Cutout Dimensions | Circular - 6.35mm Dia |
| Features Epoxy Sealed Terminals | Bushing Thread | 1/4-40 |
| | Ingress Protection | - |
| Report errors? | Features | Epoxy Sealed Terminals |
| | | Report errors? |

7101L2PHCGE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

7101L2PHCGE Payment Methods





















7101L2PHCGE Shipping Methods













If you have any question about 7101L2PHCGE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com