



7101SPDV3GE Information

Heisener.com

For Reference Only

Part Number 7101SPDV3GE

Manufacturer C&K **Category** Switches

Toggle Switches

Description SWITCH TOGGLE SPDT 5A 120V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









7101SPDV3GE Specifications

Manufacturer Part Number 7101SPDV3GE Manufacturer C&K Category Switches Package - Series 7000 Circuit SPDT Switch Function On-On Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Anti-Rotation Actuator Length 12.45mm Illumination Non-Illuminated Illumination Voltage (Nominal) - Mounting Type, Color Panel Mount Termination Style Panel Mount Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals Report errors?		
CategorySwitchesPackage-Series7000CircuitSPDTSwitch FunctionOn-OnCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeAnti-RotationActuator Length12.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer Part Number	7101SPDV3GE
Package - 7000 Circuit SPDT Switch Function On-On Current Rating AC 120V Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Anti-Rotation Illumination Type, Color 12.45mm Illumination Type, Color - Illumination Voltage (Nominal) - Monuting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1.4-40 Ingress Protection - Epoxy Sealed Terminals	Manufacturer	C&K
Package - Series 7000 Circuit SPDT Switch Function On-On Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Anti-Rotation Actuator Length 12.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Category	Switches
Series 7000 Circuit SPDT Switch Function On-On Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Anti-Rotation Actuator Length 12.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals		Toggle Switches
Circuit SPDT Switch Function On-On Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Anti-Rotation Actuator Length 12.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Package	-
Switch FunctionOn-OnCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeAnti-RotationActuator Length12.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Series	7000
Current Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeAnti-RotationActuator Length12.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Circuit	SPDT
Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeAnti-RotationActuator Length12.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Switch Function	On-On
Voltage Rating - DC Actuator Type Anti-Rotation Actuator Length 12.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection Features Epoxy Sealed Terminals	Current Rating	5A (AC/DC)
Actuator Type Anti-Rotation Actuator Length 12.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Epoxy Sealed Terminals	Voltage Rating - AC	120V
Actuator Length 12.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - DC	28V
Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Actuator Type	Anti-Rotation
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Actuator Length	12.45mm
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection Features Epoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Termination Style	PC Pin
Ingress Protection - Epoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.35mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

7101SPDV3GE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

7101SPDV3GE Payment Methods



















7101SPDV3GE Shipping Methods













If you have any question about 7101SPDV3GE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com